

Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.01	9.98	1.18
0.02	9.97	1.18
0.04	9.98	1.18
0.06	9.98	1.18
0.08	9.98	1.18
0.10	9.98	1.18
0.20	9.98	1.18
0.40	9.98	1.18
0.60	9.98	1.18
0.80	9.98	1.18
1.00	9.98	1.18
1.20	9.98	1.18
1.40	9.98	1.18
1.60	9.97	1.18
1.80	9.98	1.18
2.00	9.98	1.18
3.00	9.97	1.17
4.00	9.97	1.17
5.00	9.97	1.17
6.00	9.97	1.17
7.00	9.96	1.17
8.00	9.96	1.16
9.00	9.96	1.16
10.0	9.96	1.15
11.0	9.96	1.15
12.0	9.98	1.14
13.0	10.0	1.13
14.0	9.98	1.13
15.0	9.97	1.12
16.0	9.97	1.12
17.0	9.98	1.11
18.0	10.0	1.10
19.0	9.99	1.09
20.0	9.95	1.08
21.0	9.94	1.08
22.0	9.91	1.07
23.0	9.89	1.06
24.0	9.86	1.06
25.0	9.84	1.05
26.0	9.86	1.05
27.0	9.87	1.05
28.0	9.84	1.05
29.0	9.81	1.05
30.0	9.79	1.05
31.0	9.82	1.05
32.0	9.80	1.05
33.0	9.75	1.06
34.0	9.69	1.07
35.0	9.63	1.08
36.0	9.64	1.09
37.0	9.57	1.10
38.0	9.55	1.10
39.0	9.49	1.12
40.0	9.40	1.13
41.0	9.52	1.14
42.0	9.43	1.15
43.0	9.38	1.15
43.5	9.38	1.16