

Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.01	14.98	1.18
0.02	14.98	1.18
0.04	14.98	1.18
0.06	14.98	1.18
0.08	14.98	1.18
0.10	14.98	1.18
0.20	14.98	1.18
0.40	14.98	1.18
0.60	14.98	1.18
0.80	14.98	1.18
1.00	14.97	1.18
1.20	14.98	1.18
1.40	14.98	1.18
1.60	14.98	1.18
1.80	14.98	1.18
2.00	14.98	1.18
3.00	14.97	1.18
4.00	14.96	1.18
5.00	14.96	1.17
6.00	14.95	1.17
7.00	14.94	1.17
8.00	14.93	1.17
9.00	14.92	1.16
10.0	14.91	1.16
11.0	14.90	1.16
12.0	14.92	1.15
13.0	14.96	1.14
14.0	14.92	1.14
15.0	14.91	1.14
16.0	14.89	1.13
17.0	14.87	1.11
18.0	14.88	1.11
19.0	14.86	1.10
20.0	14.85	1.09
21.0	14.83	1.08
22.0	14.79	1.08
23.0	14.80	1.07
24.0	14.78	1.06
25.0	14.74	1.05
26.0	14.73	1.04
27.0	14.73	1.03
28.0	14.71	1.02
29.0	14.65	1.01
30.0	14.60	1.01
31.0	14.58	1.01
32.0	14.55	1.02
33.0	14.51	1.04
34.0	14.45	1.06
35.0	14.43	1.06
36.0	14.41	1.07
37.0	14.31	1.08
38.0	14.25	1.09
39.0	14.16	1.11
40.0	14.09	1.12
41.0	14.04	1.14
42.0	13.97	1.15
43.0	13.91	1.16
43.5	13.87	1.18