

Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.01	20.05	1.18
0.02	20.05	1.18
0.04	20.05	1.18
0.06	20.04	1.18
0.08	20.05	1.18
0.10	20.05	1.18
0.20	20.05	1.18
0.40	20.05	1.18
0.60	20.05	1.18
0.80	20.04	1.18
1.00	20.05	1.18
1.20	20.05	1.18
1.40	20.04	1.18
1.60	20.04	1.18
1.80	20.04	1.18
2.00	20.04	1.18
3.00	20.03	1.18
4.00	20.03	1.18
5.00	20.03	1.17
6.00	20.01	1.17
7.00	20.00	1.17
8.00	20.00	1.17
9.00	19.99	1.17
10.0	19.98	1.16
11.0	19.98	1.16
12.0	20.02	1.16
13.0	20.05	1.15
14.0	20.02	1.14
15.0	20.01	1.14
16.0	20.00	1.14
17.0	19.99	1.13
18.0	20.00	1.13
19.0	19.97	1.12
20.0	19.97	1.11
21.0	19.91	1.11
22.0	19.85	1.11
23.0	19.82	1.10
24.0	19.79	1.10
25.0	19.75	1.09
26.0	19.78	1.09
27.0	19.79	1.09
28.0	19.79	1.08
29.0	19.72	1.08
30.0	19.64	1.08
31.0	19.68	1.08
32.0	19.65	1.07
33.0	19.50	1.07
34.0	19.37	1.08
35.0	19.24	1.08
36.0	19.27	1.09
37.0	19.12	1.10
38.0	19.01	1.10
39.0	18.91	1.11
40.0	18.80	1.13
41.0	18.86	1.13
42.0	18.65	1.14
43.0	18.56	1.15
43.5	18.48	1.15