

## Typical Performance Data

FREQUENCY (MHz)	INSERTION LOSS (dB) IN-OUT , "ON"	ISOLATION (dB) IN-OUT , "OFF"	VSWR (:1)		
			IN	OUT , "ON"	OUT , "OFF"
10	1.18	74.26	1.37	1.41	31.26
20	1.06	69.20	1.20	1.22	30.31
50	0.92	61.84	1.12	1.12	30.07
100	0.88	55.48	1.09	1.10	30.07
200	0.88	49.81	1.09	1.09	30.49
500	0.94	42.32	1.11	1.11	29.97
553	0.94	41.56	1.12	1.10	28.88
792	1.02	39.41	1.13	1.12	26.27
1000	1.06	37.86	1.12	1.10	24.84
1103	1.10	37.96	1.12	1.08	22.83
1342	1.16	37.13	1.12	1.06	21.66
1509	1.19	36.81	1.14	1.07	20.69
1653	1.21	37.32	1.17	1.09	19.92
1892	1.27	37.64	1.23	1.14	19.28
2131	1.38	38.60	1.27	1.20	24.87
2370	1.31	36.48	1.31	1.31	19.46
2609	1.50	30.37	1.34	1.37	11.80
2848	1.63	27.51	1.28	1.41	10.49
2920	1.56	26.87	1.27	1.41	9.46
3000	1.58	26.08	1.24	1.35	11.35