

Typical Performance Data

NOTE: Use PDF Bookmarks to view DATA at required conditions

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: $V_{DD} = 5.0V$, $V_{EN} = 5.0V$, $I_{DD} = 78mA$ @ Temperature = +25°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)			(dBm)	(dBm)	(dB)
100.00	13.4	36.7	1.7	2.7	1.6	0.7	21.7	15.5	4.0
200.00	21.0	28.8	7.7	9.2	1.2	0.8	30.2	17.7	1.8
300.00	22.2	27.4	13.5	12.3	1.1	0.7	31.2	19.0	1.5
400.00	22.5	27.0	15.8	12.7	1.1	0.6	30.1	19.3	1.3
500.00	22.6	26.9	16.1	12.8	1.1	0.6	28.7	19.5	1.2
600.00	22.6	26.8	15.9	12.9	1.1	0.6	30.0	19.5	1.2
700.00	22.6	26.8	15.8	13.0	1.1	0.6	30.5	19.6	1.2
800.00	22.6	26.7	15.6	13.3	1.1	0.6	30.7	19.6	1.2
900.00	22.6	26.7	15.6	13.7	1.1	0.6	31.0	19.6	1.2
1000.00	22.5	26.7	15.5	14.1	1.1	0.6	31.6	19.3	1.1
1200.00	22.4	26.6	15.5	15.2	1.1	0.6	33.2	19.3	1.1
1400.00	22.3	26.6	15.4	16.7	1.1	0.6	29.5	19.3	1.2
1600.00	22.1	26.6	15.2	18.7	1.1	0.7	30.7	19.2	1.2
1800.00	21.9	26.5	14.7	20.8	1.1	0.7	30.0	19.0	1.2
2000.00	21.7	26.6	14.1	22.5	1.1	0.7	29.3	18.9	1.2
2200.00	21.5	26.6	13.4	22.1	1.1	0.8	27.5	18.7	1.2
2400.00	21.3	26.6	12.7	19.8	1.1	0.8	27.1	18.7	1.2
2600.00	21.1	26.6	12.2	17.5	1.1	0.8	29.1	18.3	1.2
2800.00	20.8	26.6	11.8	15.7	1.2	0.8	29.0	18.5	1.4
3000.00	20.6	26.6	11.4	14.5	1.2	0.8	31.2	18.7	1.3
3200.00	20.4	26.5	11.3	14.0	1.2	0.8	29.9	18.4	1.2
3400.00	20.2	26.5	11.3	13.5	1.2	0.8	30.0	18.9	1.3
3600.00	20.0	26.4	11.4	13.0	1.2	0.8	27.0	18.8	1.2
3800.00	19.8	26.4	11.7	12.7	1.2	0.8	28.1	18.8	1.2
4000.00	19.6	26.4	11.8	12.7	1.2	0.8	28.9	19.2	1.3
4200.00	19.5	26.4	12.5	12.3	1.2	0.8	27.1	18.6	1.3
4400.00	19.3	26.3	13.3	12.1	1.3	0.8	29.4	19.2	1.3
4600.00	19.1	26.4	14.0	11.6	1.3	0.8	28.0	18.9	1.3
4800.00	18.9	26.4	14.8	11.2	1.3	0.8	26.6	18.2	1.3
5000.00	18.6	26.6	15.3	10.5	1.3	0.8	25.0	18.1	1.3
5200.00	18.4	26.7	15.6	9.7	1.3	0.8	26.2	17.9	1.4
5400.00	18.0	26.9	15.4	8.8	1.4	0.8	26.2	17.8	1.4
5600.00	17.6	27.1	14.7	8.1	1.4	0.8	21.6	17.4	1.5
5800.00	17.3	27.2	14.2	7.6	1.4	0.8	20.7	17.0	1.6
6000.00	16.9	27.4	13.2	7.1	1.5	0.8	21.6	16.5	1.6

Typical Performance Data

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: $V_{DD} = 4.75V$, $V_{EN} = 5.0V$, $I_{DD} = 77mA$ @ Temperature = +25°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)			(dBm)	(dBm)	(dB)
100.00	13.3	36.8	1.7	2.6	1.6	0.7	23.1	15.0	4.0
200.00	21.0	28.7	7.7	9.0	1.2	0.8	28.1	17.2	1.8
300.00	22.2	27.4	13.5	12.0	1.1	0.7	28.3	18.5	1.4
400.00	22.5	27.0	15.8	12.5	1.1	0.6	29.5	18.9	1.3
500.00	22.6	26.8	16.0	12.5	1.1	0.6	29.0	19.1	1.3
600.00	22.6	26.7	15.8	12.6	1.1	0.6	29.5	19.2	1.2
700.00	22.6	26.7	15.7	12.8	1.1	0.6	29.0	19.4	1.2
800.00	22.5	26.6	15.6	13.1	1.1	0.6	29.0	19.2	1.1
900.00	22.5	26.6	15.5	13.4	1.1	0.6	31.9	19.2	1.1
1000.00	22.5	26.6	15.5	13.8	1.1	0.6	30.3	19.1	1.2
1200.00	22.3	26.5	15.5	14.9	1.1	0.6	29.8	19.1	1.2
1400.00	22.2	26.5	15.4	16.4	1.1	0.6	31.6	19.1	1.2
1600.00	22.1	26.5	15.1	18.3	1.1	0.7	29.5	19.1	1.2
1800.00	21.9	26.5	14.7	20.4	1.1	0.7	32.4	18.8	1.2
2000.00	21.7	26.5	14.0	22.2	1.1	0.7	31.1	18.7	1.2
2200.00	21.5	26.5	13.4	22.0	1.1	0.8	29.6	18.5	1.1
2400.00	21.3	26.5	12.7	19.9	1.1	0.8	28.7	18.5	1.3
2600.00	21.1	26.6	12.2	17.6	1.1	0.8	30.9	18.1	1.2
2800.00	20.8	26.6	11.8	15.8	1.2	0.8	29.7	18.3	1.4
3000.00	20.6	26.5	11.5	14.6	1.2	0.8	30.8	18.5	1.3
3200.00	20.4	26.4	11.4	14.0	1.2	0.8	28.5	18.2	1.2
3400.00	20.2	26.4	11.4	13.5	1.2	0.8	30.5	18.7	1.3
3600.00	20.0	26.4	11.4	13.0	1.2	0.8	29.2	18.7	1.2
3800.00	19.8	26.3	11.7	12.7	1.2	0.8	30.5	18.7	1.2
4000.00	19.6	26.3	11.9	12.7	1.2	0.8	27.7	19.0	1.3
4200.00	19.5	26.3	12.6	12.3	1.2	0.8	26.8	18.4	1.2
4400.00	19.3	26.2	13.4	12.0	1.2	0.8	30.9	19.0	1.3
4600.00	19.1	26.3	14.1	11.6	1.3	0.8	27.1	18.9	1.3
4800.00	18.9	26.3	14.9	11.1	1.3	0.8	26.8	18.2	1.2
5000.00	18.6	26.5	15.4	10.4	1.3	0.8	26.7	18.1	1.3
5200.00	18.3	26.6	15.7	9.6	1.3	0.8	25.3	17.9	1.3
5400.00	18.0	26.8	15.5	8.8	1.4	0.8	25.9	17.8	1.4
5600.00	17.6	27.1	14.8	8.0	1.4	0.8	24.9	17.4	1.4
5800.00	17.3	27.1	14.2	7.5	1.4	0.8	21.3	17.0	1.5
6000.00	16.9	27.3	13.3	7.0	1.4	0.8	22.6	16.5	1.6

Typical Performance Data

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: $V_{DD} = 5.25V$, $V_{EN} = 5.0V$, $I_{DD} = 79mA$ @ Temperature = +25°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)			(dBm)	(dBm)	(dB)
100.00	13.3	37.0	1.7	2.9	1.7	0.7	21.8	15.8	4.1
200.00	21.0	28.9	7.7	9.6	1.2	0.8	30.0	18.2	1.9
300.00	22.2	27.5	13.5	12.8	1.1	0.7	28.9	19.3	1.5
400.00	22.5	27.1	15.9	13.3	1.1	0.6	27.6	19.6	1.3
500.00	22.6	27.0	16.2	13.3	1.1	0.6	28.3	19.7	1.3
600.00	22.6	26.9	16.0	13.5	1.1	0.6	29.0	19.7	1.2
700.00	22.6	26.9	15.9	13.6	1.1	0.6	31.4	20.0	1.2
800.00	22.5	26.8	15.8	13.9	1.1	0.6	32.2	20.0	1.2
900.00	22.5	26.8	15.7	14.3	1.1	0.6	28.7	19.8	1.2
1000.00	22.5	26.8	15.7	14.7	1.1	0.6	30.4	19.5	1.2
1200.00	22.4	26.7	15.7	15.9	1.1	0.6	29.3	19.7	1.3
1400.00	22.2	26.7	15.5	17.5	1.1	0.7	31.3	19.7	1.2
1600.00	22.1	26.7	15.2	19.6	1.1	0.7	27.3	19.5	1.2
1800.00	21.9	26.7	14.8	21.7	1.1	0.7	29.3	19.3	1.2
2000.00	21.7	26.7	14.1	23.2	1.1	0.7	28.3	19.1	1.2
2200.00	21.5	26.7	13.4	22.1	1.1	0.8	28.3	18.9	1.2
2400.00	21.3	26.7	12.8	19.7	1.1	0.8	31.6	18.9	1.2
2600.00	21.1	26.7	12.2	17.4	1.2	0.8	29.1	18.6	1.3
2800.00	20.8	26.8	11.8	15.6	1.2	0.8	28.2	18.7	1.4
3000.00	20.6	26.8	11.4	14.5	1.2	0.8	29.4	18.9	1.3
3200.00	20.4	26.7	11.3	14.0	1.2	0.8	29.1	18.5	1.3
3400.00	20.2	26.6	11.3	13.6	1.2	0.8	28.1	19.0	1.3
3600.00	20.0	26.6	11.3	13.1	1.2	0.8	31.2	19.0	1.3
3800.00	19.8	26.5	11.6	12.8	1.2	0.8	31.3	19.1	1.3
4000.00	19.6	26.5	11.7	12.9	1.2	0.8	29.0	19.3	1.3
4200.00	19.4	26.5	12.4	12.5	1.3	0.8	29.4	18.7	1.3
4400.00	19.2	26.5	13.2	12.3	1.3	0.8	29.9	19.3	1.3
4600.00	19.0	26.5	13.8	11.9	1.3	0.8	26.0	19.1	1.3
4800.00	18.8	26.5	14.6	11.4	1.3	0.8	26.1	18.4	1.3
5000.00	18.6	26.7	15.1	10.8	1.4	0.8	24.9	18.3	1.3
5200.00	18.3	26.9	15.4	10.0	1.4	0.8	25.6	18.0	1.4
5400.00	18.0	27.1	15.3	9.1	1.4	0.8	26.3	17.9	1.4
5600.00	17.5	27.2	14.5	8.3	1.4	0.8	24.2	17.4	1.5
5800.00	17.2	27.3	14.0	7.8	1.4	0.8	23.3	17.1	1.5
6000.00	16.8	27.5	13.1	7.3	1.5	0.8	22.8	16.7	1.7

Typical Performance Data

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: $V_{DD} = 5.0V$, $V_{EN} = 5.0V$, $I_{DD} = 83mA$ @ Temperature = $-45^{\circ}C$

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)			(dBm)	(dBm)	(dB)
100.00	12.6	36.8	1.6	2.2	1.5	0.6	22.9	15.6	3.5
200.00	20.6	28.4	8.2	7.5	1.2	0.7	29.6	17.9	1.5
300.00	21.6	27.1	13.1	9.1	1.1	0.6	28.8	19.3	1.2
400.00	21.9	26.8	13.3	9.2	1.1	0.5	26.6	19.6	1.2
500.00	21.9	26.6	12.7	9.1	1.1	0.5	29.2	19.9	1.1
600.00	21.9	26.6	12.3	9.2	1.1	0.5	31.2	19.9	1.1
700.00	21.9	26.5	12.2	9.2	1.1	0.5	28.7	20.1	1.1
800.00	21.9	26.5	12.1	9.4	1.1	0.5	33.1	20.1	1.0
900.00	21.9	26.4	12.2	9.6	1.1	0.5	32.7	20.1	1.0
1000.00	21.9	26.4	12.4	9.8	1.1	0.5	29.4	20.0	1.0
1200.00	21.9	26.3	12.9	10.5	1.1	0.5	31.8	19.9	1.1
1400.00	21.8	26.2	13.7	11.3	1.1	0.6	30.0	19.8	1.0
1600.00	21.8	26.1	14.7	12.5	1.1	0.6	27.6	19.8	1.0
1800.00	21.7	26.1	15.8	13.9	1.1	0.6	31.2	19.5	1.1
2000.00	21.6	26.0	16.7	15.8	1.1	0.6	29.5	19.3	1.0
2200.00	21.5	26.0	17.5	18.0	1.1	0.7	29.8	19.1	0.9
2400.00	21.4	26.0	17.8	20.4	1.1	0.7	29.2	19.2	1.1
2600.00	21.2	25.9	17.5	22.0	1.1	0.7	28.8	18.7	1.0
2800.00	21.0	25.9	17.1	21.2	1.1	0.7	28.5	18.6	1.1
3000.00	20.9	25.9	16.4	19.6	1.1	0.7	30.3	19.0	1.0
3200.00	20.7	25.8	16.2	18.6	1.2	0.7	30.0	18.5	0.9
3400.00	20.5	25.8	16.0	17.8	1.2	0.7	30.0	19.0	1.0
3600.00	20.4	25.8	15.9	17.0	1.2	0.7	29.7	19.1	0.9
3800.00	20.2	25.8	16.2	16.3	1.2	0.7	28.8	19.0	0.9
4000.00	19.9	25.9	16.2	16.2	1.2	0.8	30.5	19.4	1.0
4200.00	19.9	25.7	17.2	15.4	1.2	0.7	28.3	18.7	1.0
4400.00	19.7	25.7	18.3	14.8	1.2	0.7	28.2	19.3	1.0
4600.00	19.5	25.8	19.3	13.9	1.2	0.7	28.9	19.2	1.0
4800.00	19.3	25.9	20.5	13.2	1.3	0.7	29.1	18.6	1.0
5000.00	19.1	25.9	21.5	12.2	1.3	0.7	28.8	18.7	1.0
5200.00	18.9	26.1	22.2	11.2	1.3	0.7	28.1	18.2	1.0
5400.00	18.6	26.3	22.3	10.1	1.3	0.7	26.6	18.0	1.1
5600.00	18.3	26.5	20.7	8.9	1.3	0.7	26.4	17.3	1.1
5800.00	18.1	26.6	20.4	8.5	1.3	0.7	25.0	17.0	1.1
6000.00	17.7	26.7	18.7	7.9	1.4	0.7	23.7	16.4	1.2

Typical Performance Data

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: $V_{DD} = 4.75V$, $V_{EN} = 5.0V$, $I_{DD} = 81mA$ @ Temperature = $-45^{\circ}C$

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)			(dBm)	(dBm)	(dB)
100.00	12.6	36.7	1.6	2.2	1.5	0.6	23.2	15.2	3.5
200.00	20.5	28.4	8.2	7.5	1.2	0.7	28.9	17.2	1.5
300.00	21.6	27.1	13.1	9.1	1.1	0.6	26.3	18.7	1.2
400.00	21.8	26.8	13.4	9.2	1.1	0.5	28.0	19.2	1.1
500.00	21.9	26.6	12.8	9.1	1.1	0.5	30.5	19.5	1.1
600.00	21.9	26.5	12.4	9.2	1.1	0.5	31.3	19.4	1.0
700.00	21.9	26.5	12.2	9.2	1.1	0.5	29.3	19.6	1.1
800.00	21.9	26.4	12.2	9.4	1.1	0.5	30.2	19.6	1.0
900.00	21.9	26.4	12.3	9.6	1.1	0.5	30.6	19.6	1.1
1000.00	21.9	26.3	12.5	9.8	1.1	0.5	31.6	19.4	1.0
1200.00	21.8	26.3	13.0	10.5	1.1	0.5	30.8	19.4	1.0
1400.00	21.8	26.2	13.7	11.4	1.1	0.6	31.4	19.4	0.9
1600.00	21.7	26.1	14.7	12.5	1.1	0.6	33.0	19.3	1.0
1800.00	21.7	26.0	15.7	13.9	1.1	0.6	28.1	19.1	1.0
2000.00	21.6	26.0	16.6	15.8	1.1	0.6	29.7	19.0	0.9
2200.00	21.5	25.9	17.3	18.0	1.1	0.7	28.7	18.9	0.9
2400.00	21.3	25.9	17.6	20.3	1.1	0.7	29.9	18.8	1.3
2600.00	21.2	25.9	17.3	21.8	1.1	0.7	28.9	18.5	0.9
2800.00	21.0	25.9	16.9	20.8	1.1	0.7	28.9	18.4	1.1
3000.00	20.8	25.9	16.3	19.3	1.1	0.7	28.5	18.8	1.0
3200.00	20.7	25.8	16.1	18.4	1.2	0.7	30.4	18.3	0.8
3400.00	20.5	25.8	15.9	17.5	1.2	0.7	32.4	18.8	1.0
3600.00	20.4	25.7	15.9	16.8	1.2	0.7	29.9	18.9	0.9
3800.00	20.2	25.7	16.2	16.1	1.2	0.7	29.1	18.8	0.9
4000.00	19.9	25.8	16.2	16.0	1.2	0.8	29.5	19.2	1.0
4200.00	19.9	25.7	17.3	15.2	1.2	0.7	28.6	18.7	1.0
4400.00	19.7	25.7	18.4	14.6	1.2	0.7	28.1	19.1	1.0
4600.00	19.5	25.8	19.4	13.8	1.2	0.7	27.5	19.1	1.0
4800.00	19.3	25.8	20.7	13.0	1.2	0.7	28.5	18.6	1.0
5000.00	19.1	26.0	21.7	12.1	1.3	0.7	29.6	18.6	1.0
5200.00	18.9	26.1	22.4	11.1	1.3	0.7	28.7	18.2	1.1
5400.00	18.6	26.2	22.5	10.0	1.3	0.7	26.6	18.0	1.0
5600.00	18.2	26.5	20.9	8.8	1.3	0.7	24.8	17.5	1.1
5800.00	18.0	26.5	20.6	8.4	1.3	0.7	24.1	17.1	1.7
6000.00	17.7	26.7	18.9	7.8	1.4	0.7	22.6	16.4	1.2

Typical Performance Data

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: $V_{DD} = 5.25V$, $V_{EN} = 5.0V$, $I_{DD} = 84mA$ @ Temperature = $-45^{\circ}C$

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)			(dBm)	(dBm)	(dB)
100.00	12.7	36.8	1.6	2.3	1.5	0.6	21.3	16.0	3.5
200.00	20.6	28.6	8.1	7.7	1.2	0.7	31.7	18.2	1.6
300.00	21.7	27.2	13.1	9.4	1.1	0.6	27.6	19.6	1.2
400.00	21.9	26.9	13.4	9.4	1.1	0.5	27.6	20.0	1.2
500.00	22.0	26.8	12.8	9.4	1.1	0.5	30.5	20.2	1.1
600.00	22.0	26.7	12.4	9.4	1.1	0.5	29.1	20.2	1.1
700.00	22.0	26.6	12.2	9.5	1.1	0.5	31.5	20.4	1.0
800.00	22.0	26.6	12.2	9.7	1.1	0.5	31.1	20.4	1.0
900.00	22.0	26.6	12.3	9.9	1.1	0.5	30.3	20.3	1.5
1000.00	22.0	26.5	12.4	10.1	1.1	0.5	29.8	20.1	1.0
1200.00	21.9	26.4	13.0	10.8	1.1	0.5	29.3	20.2	1.1
1400.00	21.9	26.4	13.8	11.6	1.1	0.6	30.4	20.0	1.0
1600.00	21.8	26.3	14.7	12.8	1.1	0.6	28.9	19.9	1.0
1800.00	21.8	26.2	15.8	14.3	1.1	0.6	29.9	19.7	1.0
2000.00	21.7	26.1	16.8	16.2	1.1	0.6	28.3	19.6	1.0
2200.00	21.6	26.1	17.4	18.6	1.1	0.7	29.2	19.2	1.0
2400.00	21.4	26.1	17.7	21.0	1.1	0.7	29.9	19.3	1.9
2600.00	21.3	26.1	17.4	22.4	1.1	0.7	30.5	18.8	1.0
2800.00	21.1	26.1	17.0	21.2	1.1	0.7	30.6	18.8	1.1
3000.00	20.9	26.0	16.3	19.6	1.2	0.7	29.0	19.2	1.0
3200.00	20.8	26.0	16.1	18.6	1.2	0.7	29.8	18.6	0.9
3400.00	20.6	25.9	16.0	17.8	1.2	0.7	30.8	19.2	1.0
3600.00	20.4	25.9	15.9	17.0	1.2	0.7	29.5	19.1	0.8
3800.00	20.2	25.8	16.1	16.4	1.2	0.7	27.7	19.1	0.9
4000.00	20.0	25.9	16.1	16.2	1.2	0.8	30.8	19.4	1.0
4200.00	19.9	25.8	17.2	15.5	1.2	0.7	32.8	18.7	0.9
4400.00	19.7	25.8	18.3	14.9	1.2	0.7	29.0	19.4	1.0
4600.00	19.6	25.9	19.2	14.0	1.2	0.7	28.2	19.3	0.9
4800.00	19.4	26.0	20.4	13.3	1.3	0.7	30.6	18.4	1.0
5000.00	19.2	26.0	21.4	12.3	1.3	0.7	27.7	18.5	1.0
5200.00	18.9	26.2	22.0	11.3	1.3	0.7	27.3	17.8	1.0
5400.00	18.7	26.3	22.2	10.2	1.3	0.7	26.2	17.5	1.0
5600.00	18.3	26.6	20.6	9.0	1.3	0.7	23.9	16.6	1.1
5800.00	18.1	26.7	20.4	8.5	1.4	0.7	23.3	16.6	1.5
6000.00	17.7	26.9	18.6	8.0	1.4	0.7	22.4	15.8	1.2

Typical Performance Data

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: $V_{DD} = 5.0V$, $V_{EN} = 5.0V$, $I_{DD} = 74mA$ @ Temperature = +85°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)			(dBm)	(dBm)	(dB)
100.00	13.7	37.1	1.8	3.1	1.7	0.8	21.9	15.2	4.6
200.00	21.2	29.2	7.0	10.6	1.2	0.9	27.8	17.7	2.2
300.00	22.5	27.8	12.1	16.0	1.1	0.7	26.6	19.0	1.7
400.00	22.9	27.3	15.1	17.6	1.1	0.7	27.7	19.3	1.5
500.00	23.0	27.1	16.3	17.9	1.1	0.6	27.1	19.4	1.5
600.00	23.0	27.1	16.5	18.2	1.1	0.6	27.7	19.4	1.4
700.00	22.9	27.0	16.4	18.4	1.1	0.6	27.6	19.6	1.4
800.00	22.9	27.0	16.2	18.9	1.1	0.6	32.5	19.6	1.4
900.00	22.8	27.0	15.8	19.4	1.1	0.6	30.5	19.6	1.5
1000.00	22.8	27.0	15.4	20.1	1.1	0.7	30.7	19.5	1.3
1200.00	22.6	27.0	14.5	21.8	1.1	0.7	28.2	19.3	1.4
1400.00	22.4	27.0	13.6	23.3	1.1	0.7	30.9	19.4	1.4
1600.00	22.1	27.0	12.7	23.1	1.1	0.7	29.6	19.2	1.5
1800.00	21.9	27.0	12.0	21.4	1.1	0.8	31.0	19.2	1.5
2000.00	21.6	27.0	11.2	19.1	1.1	0.8	28.6	19.0	1.5
2200.00	21.4	27.1	10.6	17.0	1.1	0.8	30.2	19.0	1.5
2400.00	21.1	27.1	10.0	15.1	1.1	0.8	32.2	18.8	1.6
2600.00	20.8	27.2	9.6	13.6	1.2	0.8	28.2	18.6	1.5
2800.00	20.5	27.2	9.4	12.6	1.2	0.8	29.6	18.6	1.6
3000.00	20.2	27.1	9.1	11.9	1.2	0.8	28.3	18.8	1.6
3200.00	20.0	27.0	9.1	11.6	1.2	0.8	31.6	18.6	1.5
3400.00	19.8	26.9	9.2	11.3	1.2	0.8	28.0	19.0	1.6
3600.00	19.6	26.8	9.3	11.0	1.2	0.8	26.2	18.9	1.5
3800.00	19.4	26.8	9.5	10.9	1.2	0.8	26.1	18.9	1.6
4000.00	19.1	26.8	9.7	11.0	1.3	0.8	27.1	19.0	1.6
4200.00	19.0	26.7	10.3	10.7	1.3	0.8	26.4	18.6	1.5
4400.00	18.8	26.7	10.9	10.7	1.3	0.8	28.6	18.9	1.6
4600.00	18.6	26.7	11.5	10.4	1.3	0.8	24.9	18.6	1.6
4800.00	18.4	26.8	12.1	10.1	1.3	0.8	23.0	17.9	1.6
5000.00	18.1	26.9	12.5	9.6	1.4	0.8	27.4	17.7	1.6
5200.00	17.7	27.1	12.7	9.0	1.4	0.8	24.4	17.4	1.7
5400.00	17.3	27.3	12.5	8.2	1.4	0.8	26.7	17.2	1.7
5600.00	16.9	27.4	12.1	7.7	1.4	0.8	20.4	16.8	1.8
5800.00	16.5	27.5	11.5	7.2	1.5	0.8	19.2	16.4	2.0
6000.00	16.0	27.8	10.8	6.8	1.5	0.8	18.2	15.8	2.0

Typical Performance Data

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: $V_{DD} = 4.75V$, $V_{EN} = 5.0V$, $I_{DD} = 72mA$ @ Temperature = +85°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)			(dBm)	(dBm)	(dB)
100.00	13.7	37.0	1.8	3.0	1.7	0.8	22.5	14.8	4.6
200.00	21.2	29.2	7.0	10.5	1.2	0.9	27.5	17.3	2.1
300.00	22.5	27.7	12.0	15.8	1.1	0.7	28.5	18.6	1.6
400.00	22.8	27.2	15.0	17.5	1.1	0.7	31.3	18.9	1.5
500.00	22.9	27.1	16.2	17.9	1.1	0.6	29.2	19.2	1.4
600.00	22.9	27.0	16.4	18.1	1.1	0.6	31.4	19.2	1.4
700.00	22.9	26.9	16.3	18.4	1.1	0.6	29.7	19.4	1.4
800.00	22.9	26.9	16.0	18.8	1.1	0.6	29.4	19.2	1.3
900.00	22.8	26.9	15.6	19.4	1.1	0.6	30.9	19.3	1.4
1000.00	22.7	26.9	15.2	20.1	1.1	0.7	31.3	19.3	1.4
1200.00	22.5	26.9	14.3	21.7	1.1	0.7	30.9	19.1	1.4
1400.00	22.3	26.9	13.4	23.1	1.1	0.7	30.0	19.1	1.4
1600.00	22.1	26.9	12.5	22.9	1.1	0.7	29.0	19.0	1.4
1800.00	21.8	26.9	11.8	21.1	1.1	0.8	27.8	19.0	1.4
2000.00	21.6	26.9	11.0	18.8	1.1	0.8	29.9	18.8	1.5
2200.00	21.3	27.0	10.4	16.8	1.1	0.8	29.7	18.7	1.4
2400.00	21.0	27.1	9.9	14.9	1.1	0.8	28.9	18.6	1.6
2600.00	20.7	27.1	9.5	13.5	1.1	0.8	29.7	18.4	1.5
2800.00	20.4	27.1	9.2	12.4	1.2	0.8	28.4	18.5	1.7
3000.00	20.2	27.1	9.0	11.7	1.2	0.8	30.5	18.6	1.6
3200.00	19.9	26.9	9.0	11.4	1.2	0.8	28.1	18.3	1.5
3400.00	19.7	26.8	9.1	11.2	1.2	0.8	29.1	18.8	1.6
3600.00	19.5	26.8	9.2	10.9	1.2	0.8	27.9	18.7	1.5
3800.00	19.3	26.7	9.4	10.7	1.2	0.8	27.6	18.7	1.5
4000.00	19.1	26.7	9.6	10.8	1.2	0.8	27.4	18.8	1.6
4200.00	18.9	26.6	10.2	10.5	1.3	0.8	26.9	18.4	1.5
4400.00	18.7	26.6	10.9	10.5	1.3	0.8	27.1	18.7	1.5
4600.00	18.5	26.6	11.4	10.2	1.3	0.8	25.1	18.4	1.6
4800.00	18.3	26.7	12.0	9.9	1.3	0.8	23.4	17.8	1.6
5000.00	18.0	26.8	12.4	9.4	1.4	0.8	26.4	17.6	1.6
5200.00	17.7	27.0	12.6	8.8	1.4	0.8	23.2	17.3	1.7
5400.00	17.3	27.1	12.4	8.0	1.4	0.8	23.5	17.2	1.7
5600.00	16.8	27.3	11.9	7.5	1.4	0.8	22.3	16.6	1.8
5800.00	16.4	27.4	11.4	7.1	1.5	0.8	18.6	16.4	1.8
6000.00	15.9	27.7	10.7	6.6	1.5	0.8	18.6	15.6	2.0

Typical Performance Data

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: $V_{DD} = 5.25V$, $V_{EN} = 5.0V$, $I_{DD} = 74mA$ @ Temperature = +85°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)			(dBm)	(dBm)	(dB)
100.00	13.6	37.3	1.8	3.6	1.9	0.9	22.6	15.5	4.7
200.00	21.1	29.6	6.9	11.5	1.2	0.9	29.0	18.0	2.3
300.00	22.4	28.0	11.9	17.6	1.2	0.8	28.1	19.1	1.7
400.00	22.8	27.6	14.8	19.6	1.1	0.7	27.6	19.4	1.6
500.00	22.9	27.4	16.1	20.1	1.1	0.7	29.8	19.7	1.5
600.00	22.9	27.3	16.4	20.3	1.1	0.7	30.1	19.7	1.4
700.00	22.9	27.3	16.4	20.6	1.1	0.7	28.5	19.7	1.5
800.00	22.8	27.2	16.1	21.2	1.1	0.7	28.9	19.7	1.4
900.00	22.7	27.2	15.7	21.8	1.1	0.7	29.0	19.7	1.4
1000.00	22.7	27.2	15.3	22.5	1.1	0.7	30.2	19.6	1.4
1200.00	22.5	27.2	14.4	24.1	1.1	0.7	31.1	19.4	1.4
1400.00	22.3	27.2	13.5	24.7	1.1	0.7	28.8	19.4	1.5
1600.00	22.0	27.2	12.6	23.1	1.1	0.8	29.0	19.3	1.5
1800.00	21.8	27.3	11.8	20.7	1.1	0.8	29.6	19.3	1.5
2000.00	21.5	27.3	11.1	18.4	1.1	0.8	27.6	19.1	1.5
2200.00	21.2	27.3	10.5	16.4	1.2	0.8	27.2	18.9	1.5
2400.00	20.9	27.4	9.9	14.7	1.2	0.8	29.6	18.8	1.7
2600.00	20.7	27.5	9.5	13.3	1.2	0.9	27.9	18.7	1.7
2800.00	20.3	27.5	9.3	12.4	1.2	0.9	28.9	18.7	1.7
3000.00	20.1	27.4	9.0	11.8	1.2	0.9	29.8	18.9	1.7
3200.00	19.8	27.3	9.0	11.5	1.2	0.9	30.1	18.6	1.6
3400.00	19.6	27.2	9.0	11.4	1.2	0.9	29.3	19.0	1.7
3600.00	19.4	27.1	9.1	11.1	1.3	0.8	26.7	19.0	1.6
3800.00	19.2	27.1	9.4	11.0	1.3	0.8	27.1	19.0	1.7
4000.00	19.0	27.1	9.6	11.2	1.3	0.9	27.1	19.0	1.7
4200.00	18.8	27.0	10.1	11.0	1.3	0.8	27.6	18.5	1.6
4400.00	18.6	26.9	10.8	11.0	1.3	0.8	28.5	18.9	1.7
4600.00	18.4	27.0	11.3	10.9	1.4	0.8	27.5	18.6	1.7
4800.00	18.1	27.0	11.9	10.6	1.4	0.8	23.3	17.9	1.7
5000.00	17.8	27.2	12.3	10.1	1.4	0.8	24.1	17.6	1.7
5200.00	17.5	27.4	12.5	9.4	1.5	0.8	23.2	17.2	1.9
5400.00	17.1	27.5	12.4	8.7	1.5	0.8	23.4	17.0	1.8
5600.00	16.7	27.6	12.0	8.1	1.6	0.8	20.5	16.6	2.0
5800.00	16.2	27.8	11.4	7.7	1.6	0.8	19.6	16.4	2.1
6000.00	15.7	28.1	10.8	7.2	1.7	0.8	18.0	15.8	2.1

MMIC Amplifier

Typical Performance Data

NOTE: Use PDF Bookmarks to view DATA at required conditions

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: $V_{DD}=5.0\text{ V}$, $V_{EN}=0\text{ V}$, $I_{DD}=2\text{ mA}$ @ Temperature = +25°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	IP-3 Output	1dB Comp. Input
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(dBm)
100.00	-5.5	5.5	2.9	2.5		
200.00	-1.3	1.3	10.8	11.4		
300.00	-0.8	0.8	17.9	19.5		
400.00	-0.7	0.7	22.9	22.5		
500.00	-0.7	0.7	23.7	21.2	47.0	34.4
600.00	-0.7	0.8	22.5	20.2		
700.00	-0.7	0.7	20.8	19.0		
800.00	-0.7	0.7	19.0	17.7		
900.00	-0.7	0.7	17.6	16.6		
1000.00	-0.7	0.8	16.4	15.7	46.8	34.5
1200.00	-0.7	0.8	14.6	14.3		
1400.00	-0.8	0.9	13.3	13.3		
1600.00	-0.8	1.0	12.4	12.5		
1800.00	-0.9	1.0	11.7	12.0		
2000.00	-0.9	1.1	11.2	11.6	42.6	29.1
2200.00	-1.0	1.2	10.9	11.3		
2400.00	-1.0	1.2	10.7	11.3		
2600.00	-1.0	1.2	10.7	11.4		
2800.00	-1.0	1.3	10.8	11.7		
3000.00	-1.0	1.3	11.1	12.1	38.3	29.9
3200.00	-1.0	1.2	11.5	12.6		
3400.00	-0.9	1.2	12.0	13.4		
3600.00	-0.9	1.2	12.7	14.3		
3800.00	-0.9	1.2	13.5	15.4		
4000.00	-1.0	1.2	13.9	16.0	39.4	29.8
4200.00	-0.9	1.2	15.0	16.9		
4400.00	-0.9	1.1	16.1	17.8		
4600.00	-0.9	1.1	16.9	18.6		
4800.00	-0.9	1.1	17.7	18.7		
5000.00	-0.9	1.2	18.2	18.4	39.1	30.1
5200.00	-0.9	1.2	18.2	17.7		
5400.00	-0.9	1.2	17.7	16.6		
5600.00	-1.0	1.3	16.7	15.4		
5800.00	-1.0	1.4	15.5	14.2		
6000.00	-1.1	1.5	14.6	13.0	43.2	29.5

MMIC Amplifier

Typical Performance Data

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: $V_{DD}=5.0$ V, $V_{EN}=0$ V, $I_{DD} = 2$ mA @ Temperature = -45°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	IP-3 Output	1dB Comp. Input
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(dBm)
100.00	-5.5	5.5	2.7	2.4		
200.00	-1.2	1.2	10.8	11.2		
300.00	-0.7	0.7	18.1	19.2		
400.00	-0.7	0.7	23.3	22.6		
500.00	-0.7	0.7	24.1	21.5	46.6	34.4
600.00	-0.7	0.7	22.9	20.7		
700.00	-0.6	0.7	20.9	19.3		
800.00	-0.6	0.7	19.1	17.9		
900.00	-0.6	0.7	17.7	16.8		
1000.00	-0.6	0.7	16.5	15.9	46.9	34.5
1200.00	-0.7	0.8	14.7	14.4		
1400.00	-0.7	0.8	13.4	13.4		
1600.00	-0.8	0.9	12.4	12.6		
1800.00	-0.8	1.0	11.7	12.0		
2000.00	-0.9	1.0	11.2	11.6	41.7	29.4
2200.00	-0.9	1.1	10.9	11.3		
2400.00	-0.9	1.1	10.7	11.3		
2600.00	-0.9	1.2	10.7	11.4		
2800.00	-0.9	1.2	10.9	11.7		
3000.00	-0.9	1.2	11.2	12.1	37.7	30.2
3200.00	-0.9	1.1	11.7	12.7		
3400.00	-0.9	1.1	12.3	13.4		
3600.00	-0.8	1.1	12.9	14.3		
3800.00	-0.8	1.1	13.7	15.3		
4000.00	-0.9	1.2	14.0	16.1	40.8	30.1
4200.00	-0.8	1.1	15.1	16.7		
4400.00	-0.8	1.0	16.0	17.4		
4600.00	-0.8	1.0	16.8	18.0		
4800.00	-0.8	1.0	17.4	18.1		
5000.00	-0.8	1.1	17.7	17.8	38.9	30.3
5200.00	-0.8	1.1	17.5	17.0		
5400.00	-0.9	1.1	17.1	16.1		
5600.00	-0.9	1.2	16.2	15.1		
5800.00	-1.0	1.3	15.1	14.0		
6000.00	-1.1	1.4	14.2	12.9	42.9	28.9

MMIC Amplifier

Typical Performance Data

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: $V_{DD}=5.0$ V, $V_{EN}=0$ V, $I_{DD} = 2$ mA @ Temperature = +85°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	IP-3 Output	1dB Comp. Input
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(dBm)
100.00	-5.6	5.6	3.0	2.7		
200.00	-1.4	1.4	10.8	11.7		
300.00	-0.9	0.9	17.7	20.0		
400.00	-0.8	0.8	22.3	22.3		
500.00	-0.8	0.8	23.1	20.7	43.2	34.4
600.00	-0.8	0.9	22.2	19.8		
700.00	-0.8	0.8	20.7	18.8		
800.00	-0.7	0.8	18.9	17.5		
900.00	-0.7	0.8	17.5	16.4		
1000.00	-0.8	0.8	16.3	15.5	44.1	34.5
1200.00	-0.8	0.9	14.5	14.2		
1400.00	-0.9	1.0	13.3	13.2		
1600.00	-0.9	1.1	12.3	12.5		
1800.00	-1.0	1.1	11.6	12.0		
2000.00	-1.0	1.2	11.1	11.6	41.4	29.1
2200.00	-1.1	1.3	10.8	11.4		
2400.00	-1.1	1.3	10.6	11.3		
2600.00	-1.1	1.4	10.6	11.4		
2800.00	-1.1	1.4	10.7	11.7		
3000.00	-1.1	1.4	10.9	12.1	37.4	30.0
3200.00	-1.1	1.4	11.3	12.6		
3400.00	-1.1	1.4	11.8	13.3		
3600.00	-1.0	1.4	12.4	14.3		
3800.00	-1.0	1.3	13.2	15.5		
4000.00	-1.1	1.4	13.8	16.1	41.4	29.8
4200.00	-1.0	1.3	14.9	17.2		
4400.00	-1.0	1.3	16.0	18.2		
4600.00	-1.0	1.3	16.9	19.0		
4800.00	-1.0	1.3	17.9	19.3		
5000.00	-1.0	1.3	18.7	19.0	40.0	30.1
5200.00	-1.0	1.3	18.8	18.2		
5400.00	-1.1	1.4	18.3	17.0		
5600.00	-1.1	1.5	17.3	15.7		
5800.00	-1.2	1.6	15.9	14.4		
6000.00	-1.3	1.7	14.9	13.0	43.5	29.5