

Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.01	12.03	1.18
0.02	12.03	1.18
0.04	12.04	1.18
0.06	12.05	1.18
0.08	12.05	1.18
0.10	12.05	1.18
0.20	12.05	1.18
0.40	12.05	1.18
0.60	12.05	1.18
0.80	12.05	1.18
1.00	12.05	1.18
1.20	12.05	1.18
1.40	12.05	1.18
1.60	12.05	1.18
1.80	12.05	1.18
2.00	12.06	1.18
3.00	12.05	1.18
4.00	12.05	1.18
5.00	12.05	1.18
6.00	12.04	1.17
7.00	12.04	1.17
8.00	12.04	1.17
9.00	12.04	1.17
10.0	12.04	1.17
11.0	12.05	1.16
12.0	12.08	1.16
13.0	12.12	1.15
14.0	12.10	1.14
15.0	12.08	1.14
16.0	12.08	1.14
17.0	12.09	1.13
18.0	12.12	1.12
19.0	12.10	1.12
20.0	12.08	1.11
21.0	12.06	1.11
22.0	12.04	1.11
23.0	12.03	1.10
24.0	12.02	1.09
25.0	12.00	1.09
26.0	12.03	1.09
27.0	12.05	1.08
28.0	12.05	1.08
29.0	12.03	1.08
30.0	12.00	1.07
31.0	12.05	1.07
32.0	12.05	1.06
33.0	11.97	1.06
34.0	11.90	1.06
35.0	11.84	1.06
36.0	11.86	1.06
37.0	11.77	1.07
38.0	11.72	1.08
39.0	11.65	1.09
40.0	11.57	1.10
41.0	11.65	1.10
42.0	11.56	1.11
43.0	11.53	1.11
43.5	11.50	1.12