

Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.01	8.02	1.13
0.02	8.02	1.13
0.04	8.02	1.13
0.06	8.02	1.13
0.08	8.02	1.13
0.10	8.02	1.13
0.20	8.02	1.13
0.40	8.02	1.13
0.60	8.02	1.13
0.80	8.02	1.13
1.00	8.02	1.13
1.20	8.02	1.13
1.40	8.02	1.13
1.60	8.03	1.13
1.80	8.03	1.13
2.00	8.03	1.13
3.00	8.02	1.13
4.00	8.02	1.13
5.00	8.03	1.12
6.00	8.02	1.12
7.00	8.02	1.12
8.00	8.03	1.12
9.00	8.03	1.12
10.0	8.03	1.11
11.0	8.04	1.11
12.0	8.07	1.10
13.0	8.12	1.09
14.0	8.10	1.09
15.0	8.08	1.09
16.0	8.08	1.08
17.0	8.10	1.08
18.0	8.13	1.07
19.0	8.12	1.06
20.0	8.08	1.06
21.0	8.06	1.05
22.0	8.06	1.05
23.0	8.04	1.05
24.0	8.02	1.04
25.0	8.03	1.04
26.0	8.05	1.04
27.0	8.07	1.03
28.0	8.06	1.04
29.0	8.05	1.03
30.0	8.05	1.04
31.0	8.09	1.04
32.0	8.08	1.04
33.0	8.03	1.04
34.0	7.99	1.04
35.0	7.95	1.04
36.0	7.94	1.06
37.0	7.87	1.07
38.0	7.83	1.07
39.0	7.78	1.08
40.0	7.70	1.09
41.0	7.79	1.10
42.0	7.76	1.10
43.0	7.76	1.11
43.5	7.70	1.12