






### Typical Performance Graphs

Test Conditions: Input Power = +5 dbm, Configuration A.






### Typical Performance Graphs

Test Conditions: Input Power = +5 dbm, Configuration A.





### Typical Performance Graphs

Test Conditions: Input Power = +5 dbm, Configuration B.






### Typical Performance Graphs

Test Conditions: Input Power = +5 dbm, Configuration B.





### Typical Performance Graphs

Test Conditions: Input Power = +5 dbm, Configuration C.






### Typical Performance Graphs

Test Conditions: Input Power = +5 dbm, Configuration C.





### Typical Performance Graphs

Test Conditions: Input Power = +5 dbm, Configuration D.



### Typical Performance Graphs




Test Conditions: Input Power = +5 dbm, Configuration D.





### Typical Performance Graphs

Test Conditions: Input Power = +5 dbm, Configuration A.





**NOTES:**

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at <https://www.minicircuits.com/terms/viewterm.html>



### Typical Performance Graphs

Test Conditions: Input Power = +5 dbm, Configuration A.



**NOTES:**

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at <https://www.minicircuits.com/terms/viewterm.html>

