

X2 Frequency Multiplier

50Ω Output 20 to 2000 MHz

Maximum Ratings

Operating Temperature -55°C to 100°C

Storage Temperature -55°C to 100°C

RF Input Power 200mW

Permanent damage may occur if any of these limits are exceeded.

Features

- wideband, 20 to 2000 MHz
- low insertion loss, 13 dB typ.
- rugged shielded case

Applications

- synthesizers
- local oscillators

MK-5




Generic photo used for illustration purposes only

CASE STYLE: L19

Connectors Model
SMA MK-5
BRACKET (OPTION "B")
BRACKET (OPTION "BR")

Outline Drawing



Outline Dimensions (inch)

A	B	C	D	E	F	G	H
1.50	1.13	1.00	.50	.155	2.345	.138	.987
38.10	28.70	25.40	12.70	3.94	59.56	3.51	25.07
J	K	L	M	N	P	S	wt
2.50	.10	.31	1.19	--	.66	.150	grams
63.50	2.54	7.87	30.23	--	16.76	3.81	37.0

Electrical Specifications





MULTIPLICATION FACTOR	FREQUENCY (MHz)		INPUT POWER (dBm)		CONVERSION LOSS (dB)		*HARMONIC OUTPUT (dBc)					
	F1 Input	F2 Output	Min.	Max.	Typ.	Max.	F1 Typ.	F1 Min.	F3 Typ.	F3 Min.	F4 Typ.	F4 Min.
2	10-600	20-1200	10**	20	13.0	15.0	20	10	26	20	15	10
	600-1000	1200-2000	10**	20	14.0	17.0	20	10	25	20	25	15

* Harmonics of input frequency below the power level of F2

** Minimum input power +13 dBm above 700 MHz.

Typical Performance Data

Input Frequency (MHz)	Conversion Loss (dB) F2	F1	Harmonic Output (-dBc) F3	F4
10.00	12.28	20.30	26.20	15.60
25.00	12.35	21.40	27.00	13.60
50.00	12.31	22.00	27.30	14.30
75.00	12.35	22.00	26.00	14.60
100.00	12.27	21.80	25.20	14.40
200.00	12.27	24.80	28.30	15.00
400.00	13.42	20.00	33.40	15.20
600.00	12.09	16.20	26.80	23.20
800.00	12.92	15.60	28.70	24.20
1000.00	14.71	15.30	30.70	26.70



Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

REV. A
M151107
MK-5
AD/CP/AM
200821
Page 1 of 1

Frequency Multiplier (Doubler)

MK-5

Typical Performance Data

FREQUENCY (MHz)				CONVERSION LOSS (dB)	HARMONIC OUTPUT* (-dBc)		
X 1 OUTPUT	X 2 OUTPUT	X 3 OUTPUT	X 4 OUTPUT	X 2 OUTPUT	X 1 OUTPUT	X 3 OUTPUT	X 4 OUTPUT
10	20	30	40	12.28	20.30	26.20	15.60
25	50	75	100	12.35	21.40	27.00	13.60
50	100	150	200	12.31	22.00	27.30	14.30
75	150	225	300	12.35	22.00	26.00	14.60
100	200	300	400	12.27	21.80	25.20	14.40
200	400	600	800	12.27	24.80	28.30	15.00
400	800	1200	1600	13.42	20.00	33.40	15.20
600	1200	1800	2400	12.09	16.20	26.80	23.20
800	1600	2400	3200	12.92	15.60	28.70	24.20
1000	2000	3000	4000	14.71	15.30	30.70	26.70


*Harmonic Output below power level of X 2 Output .

Frequency Multiplier (Doubler)


MK-5

Typical Performance Curves


Conversion Loss X 2 Output




Harmonic X 1 Output



Harmonic X 3 Output



Harmonic X 4 Output




Case Style

L

L19

L20

Outline Dimensions



CASE#	A	B	C	D	E	F	G	H	J	K	L	M	N
L19	1.50 (38.10)	1.13 (28.70)	1.00 (25.40)	.50 (12.70)	.155 (3.94)	2.345 (59.56)	.138 (3.51)	.987 (25.07)	2.50 (63.50)	.10 (2.54)	.31 (7.87)	1.19 (30.23)	--
L20	2.25 (57.15)	1.38 (35.05)	1.24 (31.50)		.150 (3.81)	3.100 (78.74)		1.238 (31.45)	3.25 (82.55)		.40 (10.16)	1.86 (47.24)	--

CASE#	P	Q	R	S	WT. GRAMS
L19	.66 (16.76)	--	--	.150 (3.81)	37.0
L20	.64 (16.26)	--	--		74.0

Dimensions are in inches (mm). Tolerances: 2 Pl. $\pm .03$; 3 Pl. $\pm .015$

Notes:

- Case material: Aluminum alloy.
- Case finish:
 - For RoHS Case Styles: Clear chemical conversion coating, non-chrome or trivalent chrome based.
 - For Non-RoHS Case Styles: Yellow hexavalent chrome based conversion coating.
- Mounting bracket available on request. For bracket mounted on connector end add suffix B to part number and add \$5.00 to unit cost. For bracket mounted on the rear, add suffix BR to part number and add \$1.50 to unit cost.



INTERNET <http://www.minicircuits.com>

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010

Mini-Circuits ISO 9001 & ISO 14001 Certified



All Mini-Circuits products are manufactured under exacting quality assurance and control standards, and are capable of meeting published specifications after being subjected to any or all of the following physical and environmental test.

Specification	Test/Inspection Condition	Reference/Spec
Operating Temperature	-55° to 100°C Ambient Environment	Individual Model Data Sheet
Storage Temperature	-55° to 100° C Ambient Environment	Individual Model Data Sheet
Barometric Pressure	100,000 Feet	MIL-STD-202, Method 105, Condition D
Humidity	90% RH, 65°C Units may require bake-out after humidity to restore full performance.	MIL-STD-202, Method 103
Thermal Shock	-65° to 125°C, 5 cycles	MIL-STD-202, Method 107, Condition B
Vibration (High Frequency)	20g peak, 10-2000 Hz, 12 times in each of three perpendicular directions (total 36)	MIL-STD-202, Method 204, Condition D
Mechanical Shock	100g, 6ms sawtooth, 3 shocks each direction 3 axes (total 18)	MIL-STD-202, Method 213, Condition I