

Power Splitter/Combiner

3 Way-0° 50Ω 700 to 3000 MHz

SEPS-3-33+



Generic photo used for illustration purposes only

CASE STYLE: JF1258

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications



Available Tape and Reel
at no extra cost

Reel Size 13" Devices/Reel 125

Maximum Ratings

Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
Power Input (as a splitter)	4W max.
Internal Dissipation	0.5W max.
DC Current	2.25 A(750mA for each port)

Permanent damage may occur if any of these limits are exceeded.

Pin Connections

SUM PORT	17
PORT 1	4
PORT 2	6
PORT 3	8
GROUND	all others

Features

- wide frequency band, 700-3000 MHz
- good isolation, 18 dB typ.
- good output matching, VSWR 1.1 typ.
- good coplanarity
- low unbalance
- shielded case
- aqueous washable


Applications

- cellular
- GPS
- PCS
- L Band


Electrical Specifications at 25°C

Parameter	Frequency (MHz)	Min.	Typ.	Max.	Unit
Frequency Range		700		3000	MHz
Insertion Loss Above 4.8 dB	700 - 800	—	0.5	1.0	dB
	800 - 2200	—	0.9	1.5	
	2200 - 2700	—	1.1	1.6	
	2700 - 3000	—	1.2	1.7	
Isolation	700 - 800	14	17	—	dB
	800 - 2200	16	20	—	
	2200 - 2700	14	18	—	
	2700 - 3000	14	18	—	
Phase Unbalance	700 - 800	—	1.0	3.0	Degree
	800 - 2200	—	2.0	5.0	
	2200 - 2700	—	2.5	7.0	
	2700 - 3000	—	4.0	9.0	
Amplitude Unbalance	700 - 800	—	0.2	0.5	dB
	800 - 2200	—	0.2	0.5	
	2200 - 2700	—	0.1	0.5	
	2700 - 3000	—	0.3	0.8	
VSWR (Port S)	700 - 800	—	1.5	1.8	:1
	800 - 2200	—	1.2	1.8	
	2200 - 2700	—	1.6	2.0	
	2700 - 3000	—	1.5	2.0	
VSWR (Port 1-3)	700 - 800	—	1.3	1.5	:1
	800 - 2200	—	1.3	1.5	
	2200 - 2700	—	1.4	1.65	
	2700 - 3000	—	1.4	1.65	

Outline Drawing



PCB Land Pattern




Suggested Layout,
Tolerance to be within ±.002

Outline Dimensions (inch/mm)

A	B	C	D	E	F	G
1.250	1.000	.200	.125	.100	.060	.040
31.75	25.40	5.08	3.18	2.54	1.52	1.02
H	J	K	L	M	wt	
—	—	.050	.060	.920	grams	
—	—	1.27	1.52	23.37	4.4	


Demo Board MCL P/N: TB-513+

Suggested PCB Layout (PL-309)



NOTES: 1. TRACE WIDTH IS SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS .030" ± .002"; COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.

Electrical Schematic



Notes




- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



Typical Performance Data

Freq. (MHz)	Total Loss ¹ (dB)			Amp. Unbal. (dB)	Isolation (dB)			Phase Unbal. (deg.)	VSWR S	VSWR 1	VSWR 2	VSWR 3
	S-1	S-2	S-3		1-2	1-3	2-3					
700.00	5.27	5.11	5.32	0.22	21.17	16.82	20.80	0.61	1.56	1.29	1.18	1.28
800.00	5.17	5.03	5.23	0.20	26.47	18.13	25.50	0.76	1.34	1.29	1.16	1.28
1000.00	5.11	5.00	5.19	0.19	29.79	20.42	29.11	1.11	1.03	1.25	1.09	1.26
1100.00	5.14	5.03	5.23	0.20	25.96	21.37	26.05	1.24	1.08	1.22	1.08	1.24
1200.00	5.19	5.08	5.29	0.21	23.83	22.20	24.15	1.36	1.16	1.18	1.09	1.20
1400.00	5.32	5.19	5.40	0.22	22.04	23.70	22.49	1.40	1.25	1.08	1.13	1.11
1500.00	5.37	5.23	5.45	0.22	21.87	24.43	22.32	1.37	1.26	1.03	1.13	1.06
1600.00	5.42	5.29	5.49	0.21	22.12	25.13	22.58	1.29	1.24	1.01	1.13	1.02
1800.00	5.43	5.33	5.50	0.16	24.40	25.89	25.06	1.20	1.14	1.04	1.11	1.00
1900.00	5.45	5.39	5.52	0.13	25.68	25.82	26.98	1.19	1.05	1.03	1.10	1.01
2000.00	5.48	5.46	5.56	0.11	25.17	25.35	27.38	1.21	1.09	1.05	1.10	1.05
2200.00	5.68	5.70	5.76	0.08	20.54	23.74	22.65	1.21	1.41	1.17	1.13	1.15
2500.00	5.99	6.01	6.01	0.02	17.07	22.04	18.94	0.92	1.66	1.34	1.09	1.30
2700.00	5.91	5.93	5.88	0.06	17.62	21.67	19.83	1.16	1.45	1.36	1.06	1.33
3000.00	5.78	6.01	5.76	0.25	18.75	19.52	20.18	3.61	1.26	1.26	1.36	1.26

1. Total Loss = Insertion Loss + 4.8dB splitter theoretical loss.



Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuits' applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



3 Way-0° Power Splitter/Combiner

SEPS-3-33+

Typical Performance Data

FREQ. (MHz)	TOTAL LOSS ¹			AMP UNBAL. (dB)	ISOLATION			PHASE UNBAL. (Deg)	FREQ. (MHz)	VSWR			
	S1	S2	S3		1-2	1-3	2-3			S	1	2	3
50	6.05	6.01	6.07	0.06	6.56	6.28	6.58	0.80	50	2.94	2.75	2.62	2.74
75	6.06	5.98	6.08	0.11	7.05	6.52	7.07	1.00	75	2.92	2.57	2.36	2.56
100	6.07	5.95	6.09	0.15	7.59	6.84	7.61	1.07	100	2.89	2.38	2.13	2.38
200	6.04	5.82	6.07	0.25	9.59	8.66	9.62	0.92	200	2.74	1.79	1.54	1.79
300	5.93	5.69	5.97	0.28	11.25	10.60	11.28	0.65	300	2.55	1.48	1.29	1.48
400	5.79	5.55	5.83	0.28	12.95	12.35	12.94	0.47	400	2.32	1.34	1.20	1.33
500	5.64	5.42	5.68	0.26	15.08	13.97	15.01	0.44	500	2.07	1.29	1.19	1.28
600	5.44	5.25	5.49	0.23	17.56	15.49	17.40	0.47	600	1.81	1.29	1.19	1.28
700	5.27	5.11	5.32	0.22	21.17	16.82	20.80	0.61	700	1.56	1.29	1.18	1.28
750	5.21	5.06	5.27	0.21	23.56	17.48	22.98	0.68	750	1.45	1.29	1.17	1.28
800	5.17	5.03	5.23	0.20	26.47	18.13	25.50	0.76	800	1.34	1.29	1.16	1.28
900	5.11	4.99	5.19	0.20	32.78	19.35	30.36	0.93	900	1.17	1.27	1.12	1.28
1000	5.11	5.00	5.19	0.19	29.79	20.42	29.11	1.11	1000	1.03	1.25	1.09	1.26
1100	5.14	5.03	5.23	0.20	25.96	21.37	26.05	1.24	1100	1.08	1.22	1.08	1.24
1200	5.19	5.08	5.29	0.21	23.83	22.20	24.15	1.36	1200	1.16	1.18	1.09	1.20
1300	5.25	5.13	5.35	0.21	22.63	22.95	23.05	1.40	1300	1.22	1.13	1.11	1.16
1400	5.32	5.19	5.40	0.22	22.04	23.70	22.49	1.40	1400	1.25	1.08	1.13	1.11
1500	5.37	5.23	5.45	0.22	21.87	24.43	22.32	1.37	1500	1.26	1.03	1.13	1.06
1600	5.42	5.29	5.49	0.21	22.12	25.13	22.58	1.29	1600	1.24	1.01	1.13	1.02
1700	5.43	5.31	5.50	0.19	22.98	25.61	23.46	1.23	1700	1.21	1.03	1.12	1.00
1800	5.43	5.33	5.50	0.16	24.40	25.89	25.06	1.20	1800	1.14	1.04	1.11	1.00
1900	5.45	5.39	5.52	0.13	25.68	25.82	26.98	1.19	1900	1.05	1.03	1.10	1.01
2000	5.48	5.46	5.56	0.11	25.17	25.35	27.38	1.21	2000	1.09	1.05	1.10	1.05
2100	5.55	5.56	5.64	0.09	22.90	24.58	25.22	1.24	2100	1.24	1.10	1.11	1.09
2200	5.68	5.70	5.76	0.08	20.54	23.74	22.65	1.21	2200	1.41	1.17	1.13	1.15
2300	5.82	5.85	5.89	0.07	18.77	22.99	20.71	1.20	2300	1.55	1.23	1.14	1.21
2400	5.93	5.96	5.98	0.05	17.63	22.41	19.49	1.10	2400	1.65	1.29	1.13	1.26
2500	5.99	6.01	6.01	0.02	17.07	22.04	18.94	0.92	2500	1.66	1.34	1.09	1.30
2600	5.98	5.99	5.97	0.02	17.08	21.84	19.04	0.89	2600	1.59	1.36	1.03	1.33
2700	5.91	5.93	5.88	0.06	17.62	21.67	19.83	1.16	2700	1.45	1.36	1.06	1.33
2800	5.83	5.88	5.78	0.10	18.55	21.38	21.10	1.72	2800	1.28	1.34	1.16	1.32
2900	5.77	5.89	5.73	0.16	19.25	20.71	21.71	2.64	2900	1.17	1.30	1.26	1.29
3000	5.78	6.01	5.76	0.25	18.75	19.52	20.18	3.61	3000	1.26	1.26	1.36	1.26
3100	5.85	6.23	5.86	0.38	17.00	17.96	17.56	4.64	3100	1.44	1.22	1.42	1.24
3200	5.97	6.54	6.01	0.57	15.06	16.12	15.21	5.65	3200	1.63	1.23	1.44	1.25
3300	6.09	6.91	6.17	0.82	13.41	14.14	13.38	6.55	3300	1.79	1.31	1.41	1.31
3400	6.19	7.30	6.32	1.12	12.10	12.10	12.00	7.26	3400	1.91	1.48	1.35	1.46
3500	6.28	7.74	6.40	1.46	11.07	10.19	10.98	7.77	3500	1.99	1.73	1.27	1.69

¹Total Loss = Insertion Loss + 4.8dB Splitter Loss



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 • Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site
The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com








IF/RF MICROWAVE COMPONENTS




REV. OR
SEPS-3-33+
6/11/2015
Page 1 of 1


Typical Performance Curves



Outline Dimensions



PCB Land Pattern



Suggested Layout,
Tolerance to be within $\pm .002$

CASE #	A	B	C	D	E	F	G	H	J	K	L	M	WT. GRAM
JF1258	1.250 (31.75)	1.000 (25.40)	.200 (5.08)	.125 (3.17)	.100 (2.54)	.060 (1.52)	.040 (1.02)	-	-	.050 (1.27)	.060 (1.52)	.920 (23.37)	4.4

Dimensions are in inches (mm). Tolerances: 2 Pl. $\pm .03$; 3Pl. $\pm .015$


Notes:

- Case material: Nickel-Silver alloy.
- Base: Printed wiring laminate.
- Termination finish:
For RoHS Case Styles: 3-5 μ inch (.08-.13 μ m) Gold over 120-240 μ inch (3-6 μ m) Nickel plate.
All models, (+) suffix.



INTERNET <http://www.minicircuits.com>
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661
Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010
Mini-Circuits ISO 9001 & ISO 14001 Certified

Tape & Reel Packaging TR-F27



Tape Width, mm	Device Cavity Pitch, mm	Reel Size, inches	Devices per Reel
44	32	13	125

Mini-Circuits carrier tape materials provide protection from ESD (Electro-Static Discharge) during handling and transportation. Tapes are static dissipative and comply with industry standards EIA-481/EIA-541.

Go to: www.minicircuits.com/pages/pdfs/tape.pdf




INTERNET <http://www.minicircuits.com>

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661


Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010

Mini-Circuits ISO 9001 & ISO 14001 Certified



REVISIONS					
REV OR	ECN No.	DESCRIPTION	DATE	DR	AUTH
	M123526	NEW RELEASE	07/09/09	MMG	ABD

SUGGESTED MOUNTING CONFIGURATION FOR
JF1258 CASE STYLE, "22SP02" PIN CODE



- NOTES: 1. TRACE WIDTH IS SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS .030" $\pm$.002"; COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.



DENOTES PCB COPPER LAYOUT WITH SMOBC
 (SOLDER MASK OVER BARE COPPER)



DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

UNLESS OTHERWISE SPECIFIED	INITIALS		DATE
DIMENSIONS ARE IN INCHES TOLERANCES ON: 2 PL DECIMALS $\pm$ 3 PL DECIMALS $\pm$.005 ANGLES $\pm$ FRACTIONS $\pm$	DRAWN	MMG	07/06/09
	CHECKED	AY	07/09/09
	APPROVED	ABD	07/09/09





Mini-Circuits® 13 Neptune Avenue
 Brooklyn NY 11235

PL, 22SP02, JF1258, SEPS-3, TB-513+

Mini-Circuits® THIS DOCUMENT AND ITS CONTENTS ARE THE PROPERTY OF MINI-CIRCUITS. EXCEPT FOR USE EXPRESSLY GRANTED, IN WRITING, TO ITS VENDORS, VENDEE AND THE UNITED STATES GOVERNMENT, MINI-CIRCUITS RESERVES ALL PROPRIETARY DESIGN, USE, MANUFACTURING AND REPRODUCTION RIGHTS THERETO. THESE CONTENTS SHALL NOT BE USED, DUPLICATED OR DISCLOSED TO ANY OUTSIDE PARTY, IN WHOLE OR IN PART, WITHOUT WRITTEN PERMISSION OF MINI-CIRCUITS.	
ASHEETA1.DWG REV:A	DATE:01/12/95

SIZE A	CODE IDENT 15542	DRAWING NO: 98-PL-309	REV: OR
FILE: 98PL309	SCALE: 3:1	SHEET: 1 OF 1	

Evaluation Board and Circuit



Schematic Diagram

Notes:

1. 50 Ohm SMA Female connectors.
2. PCB Material: Rogers R04350 or equivalent,
Dielectric Constant=3.5, Thickness=.030 inch.

Mini-Circuits®



All Mini-Circuits products are manufactured under exacting quality assurance and control standards, and are capable of meeting published specifications after being subjected to any or all of the following physical and environmental test.

Specification	Test/Inspection Condition	Reference/Spec
Operating Temperature	-40° to 85°C Ambient Environment	Individual Model Data Sheet
Storage Temperature	-55° to 100° C Ambient Environment	Individual Model Data Sheet
Humidity	90 to 95% RH, 240 hours, 50°C	MIL-STD-202, Method 103, Condition A, Except 50°C and end-point electrical test done within 12 hours
Thermal Shock	-55° to 100°C, 100 cycles	MIL-STD-202, Method 107, Condition A-3, except +100°C
Solder Reflow Heat	Sn-Pb Eutetic Process: 225°C peak Pb-Free Process 245° - 250°C peak	J-STD-020, Table 4-1, 4-2 and 5-2, Figure 5-1
Solderability	10X Magnification	J-STD-002, 95% Coverage
Vibration (High Frequency)	20g peak, 10-2000 Hz, 12 times in each of three perpendicular directions (total 36)	MIL-STD-202, Method 204, Condition D
Mechanical Shock	50g, 11 ms, 1/2-sine, 18 shocks: 3 each direction, each of 3 axes	MIL-STD-202, Method 213, Condition A
Marking Resistance to Solvents	Isopropyl alcohol + mineral spirits at 25°C; terpene defluxer at 25°C; distilled water + proylene glycol monomethyl ether + monoethanolamine at 63°C to 70°C	MIL-STD-202, Method 215