

Coaxial

Bandpass Filter

50Ω Constant Impedance 50 to 70 MHz

Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
RF Power Input	0.5W max.
Permanent damage may occur if any of these limits are exceeded.	

Features

- rugged shielded case
- wide selection of cut-off frequencies
- custom fco models available

Applications

- harmonic rejection
- lab use

SIF-60+


Generic photo used for illustration purposes only


CASE STYLE: FF99

Connectors	Model
SMA	SIF-60+

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications


Outline Drawing




Outline Dimensions (inch/mm)

B	D	E	wt
.67	1.98	.312	grams
17.02	50.29	7.92	42.0

typical frequency response






electrical schematic



Typical Performance Data

Frequency (MHz)	Insertion Loss (dB)	Return Loss (dB)	Frequency (MHz)	Group Delay (nsec)
$\bar{x}$	σ			
1.0	35.25	0.1	1.0	0.036
1.6	31.45	0.1	1.6	0.385
2.1	28.84	0.1	2.1	2.704
2.7	26.81	0.1	2.7	2.564
3.2	25.18	0.1	3.2	1.978
3.8	23.80	0.1	3.8	3.449
4.0	23.37	0.1	3.9	2.820
10.7	14.83	0.1	7.3	2.963
14.0	12.40	0.1	10.7	3.244
20.0	9.15	0.1	14.0	3.331
26.0	6.66	0.1	15.0	3.511
32.0	4.65	0.1	22.8	3.863
38.0	3.00	0.1	30.5	4.455
50.0	0.75	0.1	38.2	5.190
56.4	0.27	0.1	39.9	5.236
61.9	0.26	0.1	50.4	6.121
67.3	0.54	0.0	51.3	6.127
92.0	3.08	0.1	54.0	6.168
94.0	3.30	0.1	56.9	6.165
142.7	7.76	0.1	58.9	6.001
191.3	11.04	0.1	62.0	5.775
240.0	13.71	0.2	64.2	5.461
260.0	14.71	0.2	67.6	5.045
306.7	17.09	0.2	70.0	4.715
353.3	19.45	0.3	71.2	4.566
400.0	22.02	0.5	90.7	2.549
425.0	23.50	0.6	92.3	2.464
450.0	25.09	0.6	142.1	1.039
475.0	26.76	0.8	190.5	0.715
500.0	28.43	0.9	238.5	0.552



Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

REV. C
M151107
SIF-60+
200522

Coaxial Band Pass Filter(Constant Impedance) SIF-60+

Typical Performance Data

FREQUENCY (MHz)	INSERTION LOSS (dB)	RETURN LOSS (dB)	FREQUENCY (MHz)	GROUP DELAY (nsec)
1.00	35.25	50.90	1.00	0.036
1.60	31.45	46.70	1.60	0.385
2.10	28.84	43.80	2.10	2.704
2.70	26.81	41.80	2.70	2.564
3.20	25.18	40.00	3.20	1.978
3.80	23.80	38.60	3.80	3.449
4.00	23.37	37.90	3.90	2.820
10.70	14.83	29.00	7.30	2.963
14.00	12.40	26.60	10.70	3.244
20.00	9.15	23.60	14.00	3.331
26.00	6.66	21.40	15.00	3.511
32.00	4.65	20.20	22.80	3.863
38.00	3.00	19.90	30.50	4.455
50.00	0.75	24.50	38.20	5.190
56.40	0.27	31.00	38.90	5.236
61.90	0.26	31.00	50.40	6.121
67.30	0.54	23.70	51.30	6.127
92.00	3.08	18.00	54.00	6.168
94.00	3.30	17.90	56.90	6.165
142.70	7.76	20.30	58.90	6.001
191.30	11.04	21.40	62.00	5.775
240.00	13.71	22.50	64.20	5.461
260.00	14.71	22.90	67.60	5.045
306.70	17.09	23.50	70.00	4.715
353.30	19.45	23.60	71.20	4.566
400.00	22.02	23.70	90.70	2.549
425.00	23.50	23.70	92.30	2.464
450.00	25.09	23.50	142.10	1.039
475.00	26.76	23.40	190.50	0.715
500.00	28.43	23.10	238.50	0.552

REV. X1
SIF-60+
070530

Page 1 of 1






Mini-Circuits®
IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED • RoHS compliant
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661
The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



Coaxial Band Pass Filter(Constant Impedance) SIF-60+

Typical Performance Curves



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS 9100 CERTIFIED RoHS compliant
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661



The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



REV. X1
SIF-60+
070530
Page 1 of 1

FF56
FF99

Outline Dimensions



CASE #.	A	B	C	D	E	WT GRAMS
FF56	--	.46 (11.68)	--	1.70 (43.18)	.312 (7.92)	18.0
FF99	--	.70 (17.78)	--	1.98 (50.29)		42.0

Dimensions are in inches (mm). Tolerances: 2Pl. ± .03; 3Pl. ± .015

Notes:

1. Case material: Brass.
2. Case finish: Nickel plate.



All Mini-Circuits products are manufactured under exacting quality assurance and control standards, and are capable of meeting published specifications after being subjected to any or all of the following physical and environmental test.

Specification	Test/Inspection Condition	Reference/Spec
Operating Temperature	-55° to 100°C Ambient Environment	Individual Model Data Sheet
Storage Temperature	-55° to 100° C Ambient Environment	Individual Model Data Sheet
Barometric Pressure	100,000 Feet	MIL-STD-202, Method 105, Condition D
Humidity	90% RH, 65°C Units may require bake-out after humidity to restore full performance.	MIL-STD-202, Method 103
Thermal Shock	-65° to 125°C, 5 cycles	MIL-STD-202, Method 107, Condition B
Vibration (High Frequency)	20g peak, 10-2000 Hz, 12 times in each of three perpendicular directions (total 36)	MIL-STD-202, Method 204, Condition D
Mechanical Shock	100g, 6ms sawtooth, 3 shocks each direction 3 axes (total 18)	MIL-STD-202, Method 213, Condition I