

## REPLACEMENT PART REFERENCE GUIDE, ZN4PD1-50-S+    **AN-10-008**

ORIGINAL PART: ZN4PD1-50-S+  
 REPLACEMENT PART: ZN4PD1-63HP-S+

*Replacement Part has been judged by Mini-Circuits Engineering as a suitable replacement to Original Part.*

### MECHANICAL DIMENSIONS

ORIGINAL PART: ZN4PD1-50-S+

REPLACEMENT PART: ZN4PD1-63HP-S+


Case Style Change from

UU846 to


UU846-4



FROM :



TO:



**ORIGINAL PART: ZN4PD1-50-S+**

**REPLACEMENT PART: ZN4PD1-63HP-S+**

In new outline UU846-4, connectors at location 1 and 2 are moved on left side by .250" (6.35mm) and 4 and 5 are moved on right side by .25" (6.35 mm).

**Internally, PCB material is change from OAK to TLP.**

## CONCLUSION:

### 1) FUNCTIONAL COMPATIBLE<sub>a</sub>:


Following is a summary of changes/improvements:



Typical performance: See paragraphs 2 and 3

Min/Max Specifications - see below:

Parameter	Original Part ZN4PD1-50-S+	Replacement Part ZN4PD1-63HP-S+
Insertion Loss(max) @ 5000 MHz	1.8	1.5 typ
Isolation (Min) @ 5000 MHz	13	18
Phase unbalance (max)	8	6
Amplitude unbalance (max)	0.6	0.6
VSWR (Max)@ (typ)	1.3:1	1.25:1

### 2) PERFORMANCE COMPARISON CURVES<sub>a</sub> (TYPICAL),





**IMPORTANT NOTICE**

© 2015 Mini-Circuits

This document is provided as an accommodation to Mini-Circuits customers in connection with Mini-Circuits parts only. In that regard, this document is for informational and guideline purposes only. Mini-Circuits assumes no responsibility for errors or omissions in this document or for any information contained herein.

Mini-Circuits may change this document or the Mini-Circuits parts referenced herein (collectively, the "Materials") from time to time, without notice. Mini-Circuits makes no commitment to update or correct any of the Materials, and Mini-Circuits shall have no responsibility whatsoever on account of any updates or corrections to the Materials or Mini-Circuits' failure to do so.

Mini-Circuits customers are solely responsible for the products, systems, and applications in which Mini-Circuits parts are incorporated or used. In that regard, customers are responsible for consulting with their own engineers and other appropriate professionals who are familiar with the specific products and systems into which Mini-Circuits' parts are to be incorporated or used so that the proper selection, installation/integration, use and safeguards are made. Accordingly, Mini-Circuits assumes no liability therefore.

In addition, your use of this document and the information contained herein is subject to Mini-Circuits' standard terms of use, which are available at Mini-Circuits' website at [www.minicircuits.com/homepage/terms\\_of\\_use.html](http://www.minicircuits.com/homepage/terms_of_use.html).

Mini-Circuits and the Mini-Circuits logo are registered trademarks of Scientific Components Corporation d/b/a Mini-Circuits. All other third-party trademarks are the property of their respective owners. A reference to any third-party trademark does not constitute or imply any endorsement, affiliation, sponsorship, or recommendation: (i) by Mini-Circuits of such third-party's products, services, processes, or other information; or (ii) by any such third-party of Mini-Circuits or its products, services, processes, or other information.