Case Style




DB714

Outline Dimensions

SEE NOTE 3 D TYP→ SEE NOTE 3 COMPONENT AREA +.005 Ε -.009.000 .008 5 G TYP C MAX→ ^LPLASTIC SHAPE ADJACENT TO LEADS PICK & PLACE MAY VARY SURFACE AREA (.03X.075)MIN.

PCB Land Pattern



Suggested Layout, Tolerance to be within ±.002

CASE #	A	В	С	D	Е	F	G	Н	J	K	WT. GRAM
DB714	.160	.150	.160	.050	.040	.025	.028	.065	.190	.030	.15
	(4.06)	(3.81)	(4.06)	(1.27)	(1.02)	(0.64)	(0.71)	(1.65)	(4.83)	(0.76)	

Dimensions are in inches (mm). Tolerances: 2 Pl. \pm .01; 3Pl. \pm .005

Notes:

- 1. Case material: Plastic.
- 2. Termination finish:

For RoHS Case Styles: Tin plate over Nickel plate. All models, (+) suffix. For RoHS-5 Case Styles: Tin-Lead plate. All models, no (+) suffix.

3. Lead #1 identifier shall be located in the cross-hatched area shown. Identifier may be either a molded or marked feature.





P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site

The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com