

RRR137-1

## **Outline Dimensions**



## **PCB Land Pattern**



Suggested Layout, Tolerance to be within ±.002

CASE #	A	В	С	D	Е	F	G	Н	J	K	L	M	N
RRR137-1	.28 (7.11)	.14 (3.56)	.030 (.76)	.020 (0.51)	.145 (3.68)	.110 (2.79)	.007 (0.18)	.020 (0.51)	.03 (0.76)	.040 (1.02)	.072 (1.83)	.310 (7.87)	.310 (7.87)

CASE #	P	Q	R	S	WT. GRAM
RRR137-1	.084 (2.13)	.167 (4.24)	.084 (2.13)	.167 (4.24)	.015

Dimensions are in inches (mm). Tolerances: 2 Pl. ± .02; 3 Pl. ± .015

## **Notes:**

- 1. Case material: Plastic.
- 2. Termination finish:

For RoHS Case Styles: Tin plate. All models, (+) suffix.

J TYP

- 3. RF output is identified by index mark, model dash number by alphanumeric code.
- 4. Special Tolerances: Termination width  $\pm$  .005 inch, termination thickness  $\pm$  .003 inch.



INTERNET http://www.minicircuits.com

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010

Mini-Circuits ISO 9001 & ISO 14001 Certified