

## Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.01	19.96	1.00
0.05	20.03	1.00
0.1	19.99	1.00
0.2	20.01	1.00
0.3	20.02	1.00
0.4	20.05	1.00
0.5	20.06	1.00
0.6	20.06	1.00
0.7	20.05	1.00
0.8	20.05	1.01
0.9	20.06	1.01
1.0	20.06	1.01
1.4	20.08	1.03
1.8	20.09	1.04
2.0	20.09	1.05
2.4	20.07	1.06
2.8	20.10	1.07
3.0	20.08	1.08
3.4	20.08	1.08
3.8	20.09	1.07
4.0	20.07	1.07
4.4	20.07	1.05
4.8	20.05	1.04
5.0	20.05	1.03
5.4	20.06	1.03
5.8	20.06	1.04
6.0	20.03	1.06
6.4	20.03	1.07
6.8	20.04	1.10
7.0	20.06	1.11
7.4	20.08	1.13
7.8	20.12	1.14
8.0	20.07	1.14
8.4	19.94	1.14
8.8	19.86	1.14
9.0	19.86	1.11
9.4	19.84	1.10
9.8	19.85	1.13
10.0	19.86	1.07
10.4	19.84	1.08
10.8	19.86	1.10
11.0	19.84	1.03
11.4	19.94	1.07
11.8	20.01	1.07
12.0	20.05	1.05
12.4	20.03	1.06
12.8	19.91	1.09
13.0	19.86	1.09
13.4	19.77	1.09
13.8	19.69	1.09
14.0	19.66	1.10
14.4	19.67	1.12
14.8	19.63	1.13
15.0	19.57	1.13
15.4	19.56	1.11
15.8	19.53	1.10
16.0	19.48	1.12
16.4	19.49	1.10
16.8	19.49	1.10
17.0	19.46	1.10
17.4	19.58	1.10
17.8	19.54	1.08
18.0	19.55	1.13