

## Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.01	20.22	1.01
0.05	20.30	1.00
0.1	20.29	1.00
0.2	20.31	1.00
0.3	20.33	1.01
0.4	20.35	1.01
0.5	20.36	1.01
0.6	20.37	1.02
0.7	20.37	1.02
0.8	20.38	1.03
0.9	20.38	1.03
1.0	20.39	1.04
1.4	20.41	1.05
1.8	20.43	1.06
2.0	20.43	1.06
2.4	20.44	1.07
2.8	20.44	1.08
3.0	20.44	1.08
3.4	20.43	1.10
3.8	20.43	1.12
4.0	20.42	1.13
4.4	20.41	1.14
4.8	20.39	1.13
5.0	20.39	1.12
5.4	20.37	1.09
5.8	20.36	1.06
6.0	20.35	1.05
6.4	20.34	1.02
6.8	20.31	1.01
7.0	20.29	1.03
7.4	20.28	1.07
7.8	20.25	1.11
8.0	20.23	1.12
8.4	20.21	1.16
8.8	20.13	1.21
9.0	20.10	1.23
9.4	20.05	1.26
9.8	19.99	1.24
10.0	19.99	1.22
10.4	19.98	1.14
10.8	20.04	1.08
11.0	20.07	1.11
11.4	20.13	1.19
11.8	20.08	1.26
12.0	20.09	1.28
12.4	20.03	1.29
12.8	19.92	1.30
13.0	19.90	1.30
13.4	19.86	1.33
13.8	19.81	1.37
14.0	19.81	1.39
14.4	19.71	1.39
14.8	19.58	1.34
15.0	19.52	1.29
15.4	19.49	1.18
15.8	19.52	1.13
16.0	19.55	1.15
16.4	19.61	1.20
16.8	19.58	1.20
17.0	19.54	1.19
17.4	19.41	1.15
17.8	19.37	1.11
18.0	19.36	1.10