

Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.01	30.05	1.01
0.05	30.15	1.01
0.1	30.11	1.01
0.2	30.16	1.01
0.3	30.18	1.01
0.4	30.19	1.01
0.5	30.19	1.01
0.6	30.17	1.01
0.7	30.16	1.01
0.8	30.21	1.01
0.9	30.23	1.01
1.0	30.21	1.02
1.4	30.22	1.03
1.8	30.21	1.04
2.0	30.23	1.05
2.4	30.24	1.06
2.8	30.26	1.08
3.0	30.24	1.09
3.4	30.22	1.10
3.8	30.24	1.10
4.0	30.26	1.10
4.4	30.25	1.10
4.8	30.24	1.09
5.0	30.19	1.07
5.4	30.21	1.06
5.8	30.17	1.04
6.0	30.19	1.04
6.4	30.19	1.04
6.8	30.18	1.06
7.0	30.17	1.08
7.4	30.15	1.09
7.8	30.15	1.11
8.0	30.13	1.11
8.4	30.12	1.11
8.8	30.09	1.13
9.0	30.07	1.11
9.4	30.11	1.09
9.8	30.05	1.10
10.0	30.06	1.08
10.4	29.98	1.07
10.8	30.02	1.08
11.0	29.94	1.05
11.4	29.98	1.08
11.8	30.07	1.11
12.0	30.02	1.07
12.4	30.00	1.11
12.8	30.00	1.13
13.0	29.93	1.11
13.4	29.90	1.13
13.8	29.90	1.11
14.0	29.89	1.11
14.4	29.82	1.12
14.8	29.79	1.10
15.0	29.81	1.13
15.4	29.71	1.11
15.8	29.75	1.12
16.0	29.73	1.15
16.4	29.87	1.12
16.8	29.80	1.15
17.0	29.72	1.13
17.4	29.77	1.18
17.8	29.71	1.18
18.0	29.66	1.19