

Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.01	30.17	1.00
0.05	30.16	1.00
0.1	30.22	1.01
0.2	30.24	1.01
0.3	30.26	1.01
0.4	30.28	1.01
0.5	30.29	1.02
0.6	30.30	1.02
0.7	30.29	1.02
0.8	30.30	1.03
0.9	30.31	1.03
1.0	30.31	1.04
1.4	30.34	1.05
1.8	30.35	1.07
2.0	30.36	1.07
2.4	30.36	1.08
2.8	30.36	1.10
3.0	30.37	1.11
3.4	30.37	1.14
3.8	30.37	1.16
4.0	30.37	1.16
4.4	30.36	1.16
4.8	30.34	1.15
5.0	30.34	1.15
5.4	30.31	1.14
5.8	30.28	1.14
6.0	30.27	1.13
6.4	30.25	1.12
6.8	30.22	1.10
7.0	30.21	1.09
7.4	30.18	1.10
7.8	30.15	1.14
8.0	30.12	1.16
8.4	30.09	1.19
8.8	30.08	1.23
9.0	30.08	1.24
9.4	30.07	1.25
9.8	30.03	1.23
10.0	30.03	1.23
10.4	29.97	1.21
10.8	29.92	1.20
11.0	29.89	1.18
11.4	29.86	1.15
11.8	29.82	1.13
12.0	29.81	1.13
12.4	29.78	1.17
12.8	29.72	1.21
13.0	29.71	1.22
13.4	29.66	1.25
13.8	29.61	1.28
14.0	29.61	1.29
14.4	29.52	1.29
14.8	29.43	1.26
15.0	29.40	1.23
15.4	29.38	1.18
15.8	29.36	1.14
16.0	29.35	1.12
16.4	29.36	1.08
16.8	29.34	1.06
17.0	29.34	1.06
17.4	29.31	1.05
17.8	29.29	1.03
18.0	29.26	1.02