

Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.01	19.90	1.01
0.05	19.91	1.01
0.1	19.91	1.01
0.2	19.93	1.01
0.3	19.94	1.01
0.4	19.94	1.01
0.5	19.95	1.02
0.6	19.95	1.02
0.7	19.95	1.02
0.8	19.96	1.02
0.9	19.96	1.02
1.0	19.96	1.03
1.4	19.97	1.03
1.8	19.98	1.04
2.0	19.98	1.05
2.4	19.98	1.05
2.8	19.99	1.06
3.0	19.98	1.06
3.4	19.98	1.07
3.8	19.98	1.08
4.0	19.98	1.08
4.4	19.99	1.09
4.8	19.97	1.10
5.0	19.98	1.11
5.4	19.98	1.12
5.8	19.98	1.14
6.0	19.98	1.15
6.4	19.98	1.17
6.8	19.98	1.19
7.0	19.98	1.20
7.4	19.99	1.21
7.8	19.99	1.22
8.0	19.99	1.22
8.4	19.99	1.21
8.8	19.97	1.19
9.0	19.96	1.18
9.2	19.96	1.17
9.4	19.96	1.16
9.8	19.93	1.14
10.0	19.93	1.13
10.4	19.92	1.11
10.8	19.91	1.10
11.0	19.91	1.10
11.4	19.89	1.09
11.8	19.89	1.11
12.0	19.89	1.11
12.4	19.87	1.12
12.8	19.92	1.13
13.0	19.92	1.13
13.4	19.88	1.14
13.8	19.90	1.14
14.0	19.91	1.14
14.4	19.84	1.15
14.8	19.92	1.14
15.0	19.86	1.14
15.4	19.84	1.12
15.8	19.83	1.12
16.0	19.82	1.11
16.4	19.77	1.09
16.8	19.85	1.10
17.0	19.81	1.11
17.4	19.78	1.14
17.8	19.77	1.19
18.0	19.78	1.23