

## Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.01	39.78	1.00
0.02	39.85	1.00
0.03	39.86	1.00
0.04	39.86	1.00
0.05	39.87	1.00
0.06	39.84	1.00
0.07	39.83	1.00
0.08	39.83	1.00
0.09	39.84	1.00
0.10	39.84	1.00
0.20	39.87	1.00
0.30	39.88	1.01
0.40	39.88	1.01
0.50	39.88	1.01
0.60	39.88	1.01
0.70	39.88	1.01
0.80	39.89	1.01
0.90	39.88	1.01
1.00	39.89	1.01
1.20	39.90	1.02
1.40	39.89	1.03
1.60	39.90	1.03
1.80	39.90	1.02
2.00	39.91	1.02
2.20	39.91	1.04
2.40	39.89	1.04
2.60	39.89	1.05
2.80	39.88	1.03
3.00	39.88	1.02
3.20	39.87	1.05
3.40	39.87	1.05
3.60	39.86	1.06
3.80	39.85	1.03
4.00	39.84	1.04
4.20	39.84	1.04
4.40	39.83	1.06
4.60	39.81	1.05
5.00	39.78	1.04
6.00	39.73	1.05
7.00	39.62	1.03
8.00	39.56	1.09
9.00	39.41	1.07
10.00	39.36	1.09
11.00	39.23	1.09
12.00	39.14	1.19
12.20	39.13	1.09
12.40	39.08	1.11
12.60	39.09	1.11
12.80	39.06	1.01
13.00	39.07	1.11
14.00	38.94	1.03
15.00	38.88	1.04
16.00	38.81	1.08
17.00	38.68	1.07
18.00	38.59	1.19