

Fixed Attenuator

FW-1+

Typical Performance Data

FREQUENCY (MHz)	ATTENUATION (dB)	VSWR (:1)
10.0	1.03	1.00
50.0	1.03	1.00
100.0	1.04	1.01
500.0	1.09	1.01
1000.0	1.12	1.03
1200.0	1.14	1.03
1400.0	1.15	1.03
1600.0	1.15	1.04
1800.0	1.17	1.04
2000.0	1.18	1.04
2200.0	1.18	1.04
2400.0	1.19	1.03
2600.0	1.20	1.03
2800.0	1.21	1.02
3000.0	1.22	1.02
3200.0	1.23	1.02
3400.0	1.24	1.03
3600.0	1.24	1.05
3800.0	1.26	1.07
4000.0	1.27	1.08
4200.0	1.28	1.10
4400.0	1.28	1.12
4600.0	1.30	1.14
4800.0	1.31	1.16
5000.0	1.32	1.16
5200.0	1.33	1.17
5500.0	1.33	1.17
6000.0	1.34	1.14
6500.0	1.34	1.08
7000.0	1.37	1.04
7500.0	1.39	1.10
8000.0	1.42	1.18
8500.0	1.47	1.25
9000.0	1.51	1.29
9500.0	1.55	1.31
10000.0	1.59	1.33
10500.0	1.56	1.34
11000.0	1.56	1.34
11500.0	1.55	1.34
12000.0	1.64	1.35
12500.0	1.55	1.31
13000.0	1.52	1.26
13500.0	1.51	1.20
14000.0	1.50	1.13
14500.0	1.48	1.04
15000.0	1.51	1.04



P.O. Box 350166, Brooklyn, New York 11235-0003 • (718) 934-4500 • Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site
The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com



IF/RF MICROWAVE COMPONENTS

REV. OR
FW-1+
5/1/2014
Page 1 of 1