

Fixed Attenuator

FW-2+

Typical Performance Data

FREQUENCY (MHz)	ATTENUATION (dB)	VSWR (:1)
10.0	2.01	1.00
50.0	2.02	1.00
100.0	2.02	1.01
500.0	2.08	1.01
1000.0	2.11	1.01
1200.0	2.13	1.01
1400.0	2.14	1.01
1600.0	2.14	1.01
1800.0	2.16	1.00
2000.0	2.17	1.01
2200.0	2.18	1.02
2400.0	2.19	1.02
2600.0	2.20	1.03
2800.0	2.21	1.05
3000.0	2.22	1.06
3200.0	2.23	1.07
3400.0	2.24	1.08
3600.0	2.25	1.10
3800.0	2.26	1.11
4000.0	2.27	1.12
4200.0	2.29	1.13
4400.0	2.29	1.14
4600.0	2.30	1.15
4800.0	2.31	1.16
5000.0	2.32	1.16
5200.0	2.33	1.15
5500.0	2.34	1.14
6000.0	2.35	1.12
6500.0	2.36	1.08
7000.0	2.38	1.06
7500.0	2.40	1.09
8000.0	2.45	1.14
8500.0	2.55	1.20
9000.0	2.51	1.24
9500.0	2.51	1.27
10000.0	2.52	1.29
10500.0	2.51	1.30
11000.0	2.52	1.28
11500.0	2.51	1.26
12000.0	2.53	1.26
12500.0	2.52	1.27
13000.0	2.53	1.29
13500.0	2.54	1.30
14000.0	2.56	1.29
14500.0	2.54	1.24
15000.0	2.55	1.18



P.O. Box 350166, Brooklyn, New York 11235-0003 • Fax (718) 934-4500 • Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site
The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com



IF/RF MICROWAVE COMPONENTS

REV. OR
FW-2+
5/1/2014
Page 1 of 1