

# RF Transformer

# T16-1T+

## Typical Performance Data

FREQUENCY (MHz)	INSERTION LOSS (dB)	RETURN LOSS (dB)
0.30	1.52	7.57
0.40	1.30	8.82
0.50	1.19	9.76
0.60	1.13	10.47
0.70	1.09	11.06
0.80	1.05	11.57
0.90	1.02	12.03
1.00	1.00	12.43
2.00	0.81	15.38
4.00	0.72	18.43
5.00	0.71	19.30
10.00	0.71	20.53
15.00	0.73	19.63
20.00	0.75	18.25
30.00	0.80	15.67
40.00	0.84	13.62
50.00	0.87	11.99
60.00	0.89	10.66
70.00	0.93	9.53
80.00	0.99	8.57
90.00	1.07	7.76
100.00	1.17	7.04
110.00	1.29	6.44
120.00	1.41	5.90



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site



The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: [www.minicircuits.com](http://www.minicircuits.com)

RF/IF MICROWAVE COMPONENTS

REV. X1  
T16-1T+  
2/27/2008  
Page 1 of 1