

2WAY-90° POWER SPLITTER/COMBINERS Designer's Kit K1-QCN+

MINI-CIRCUITS DESIGNER'S KITS
SPEED UP
THE SOLUTION!



220 to 4500 MHz

QCN+ Features

- Wideband, 50 Ω
- Low insertion loss, 0.4 dB typical
- High isolation up to 32 dB typical
- Wrap-around terminals for excellent solderability
- Ultra small ceramic cases, (L) 0.12" x (W) 0.60" x (H) 0.35"



All models are
RoHS compliant

\$79⁹⁵
only *ea. kit (10 models, 2 of each, 20 total)*

Kit K1-QCN+ Electrical specifications of each model

Model	Frequency Range (MHz)		Isolation (dB)		Insertion Loss (dB) Above 3 dB		Phase Unbalance (Degrees) Max.	Amplitude Unbalance	Power Input (W) (as a splitter) Max.
	Low	High	Typ.	Min.	Typ.	Max.			
QCN-3+	220	470	24	18	0.6	0.8	8	1.3	15
QCN-5+	330	580	20	14	0.3	0.6	8	1.3	15
QCN-7+	425	675	17	11	0.4	0.7	8	1.0	15
QCN-12+	800	1375	19	14	0.4	0.8	12	0.9	15
QCN-12A+	800	1250	17	13	0.3	0.7	5	0.8	15
QCN-19+	1100	1925	25	19	0.4	0.9	4	1.1	15
QCN-25+	1350	2450	25	18	0.4	0.9	5	1.1	15
QCN-27+	1700	2700	26	18	0.4	0.9	6	1.0	15
QCN-34+	2500	3400	32	20	0.4	0.7	4	1.2	15
QCN-45+	2500	4500	19	15	0.5	0.8	6	2.5	15

Patent pending

Mini-Circuits®
ISO 9001 ISO 14001 CERTIFIED

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 For quick access to product information see MINI-CIRCUITS CATALOG & WEB SITE

IF RF MICROWAVE COMPONENTS

REV. 0R
M111563
K1-QCN+