



DESIGNER'S KIT K3-DBTC-L+

Directional Couplers

50Ω 5 to 2000MHz

FEATURES

- Very flat 9 to 20dB coupling
- Very broadband, multi-octave, 50Ω
- Temperature stable LTCC base
- All welded construction
- Micro-miniature package with leads (L).166" x (W).150" x (H).155

MINI-CIRCUITS DESIGNER'S KITS
SPEED UP
THE SOLUTION



K3-DBTC-L+ ELECTRICAL SPECIFICATIONS

(kit includes 5 models, 5 of each, 25 total)

Model	Freq. (MHz) f_L - f_U	Coupling (dB) Nom. Max Flatness		Mainline Loss ¹ (dB)						Directivity (dB)						VSWR (:1) Typ.	Power Input (W)	
				L		M		U		L		M		U			L	MU
				Typ.	Max.	Typ.	Max.	Typ.	Max.	Typ.	Min.	Typ.	Min.	Typ.	Min.		Max.	Max.
DBTC-9-4L+	5-1000	9.0±0.5	±0.5	1.2	2.0	1.2	1.8	1.5	2.0	21	17	18	13	15	—	1.20	0.5	1.0
DBTC-12-4L+	5-1000	12.2±0.5	±0.9	0.9	1.8	0.7	1.3	1.1	1.6	33	22	21	14	15	—	1.20	0.5	1.0
DBTC-13-4L+	5-1000	13.0±0.5	±0.6	0.7	1.3	0.7	1.3	1.1	1.6	21	17	18	13	13	—	1.20	0.5	1.0
DBTC-17-5L+	50-1000	17.7±0.9	±1.0	0.9	1.4	0.9	1.4	1.1	1.6	20	13	20	13	14	—	1.20	—	2.0
DBTC-20-4L+	20-1000	20.4±0.6	±0.8	0.3	1.0	0.4	1.0	0.7	1.3	21	13	21	14	16	—	1.20	1.0	1.0

Protected under U.S. Patents 6,140,887 & 6,784,521
1. Includes theoretical power loss due to coupling.

L = low range [f_L to $10f_L$]

M = mid range [$10f_L$ to $f_U/2$]

U = upper range [$f_U/2$ to f_U]

