



Mini-Circuits

ULTRA-HIGH DYNAMIC RANGE

Monolithic Amplifier

PGA-102+

50Ω 0.05 to 6 GHz

THE BIG DEAL

- +3.3 V, 83 mA Operation
- High IP3, +33 dBm Typ. at 2 GHz
- Gain, 14.0 dB Typ. at 2 GHz
- P1dB +17.5 dBm Typ. at 2 GHz
- Low Noise Figure, 2.3 dB at 0.8 GHz
- No External Matching Components Required



Generic photo used for illustration purposes only

CASE STYLE: DF782

+RoHS Compliant

The +Suffix identifies RoHS Compliance.
See our website for methodologies and qualifications

APPLICATIONS

- Base Station Infrastructure
- Portable Wireless
- CATV & DBS
- MMDS & Wireless LAN
- LTE CATV, DOCSIS 3.1 WLAN

PRODUCT OVERVIEW

PGA-102+ (RoHS compliant) is an advanced wideband amplifier fabricated using E-pHEMT technology and offers extremely high dynamic range over a broad frequency range and with low noise figure. In addition, the PGA-102+ has good input and output return loss over a broad frequency range without the need for external matching components and has demonstrated excellent reliability. It has repeatable performance from lot to lot and is enclosed in a SOT-89 package for very good thermal performance.

KEY FEATURES

Feature	Advantages
Broad Band: 0.05 to 6.0 GHz	Broadband covering primary wireless communications bands: Cellular, PCS, LTE, WiMAX
High IP3 Versus DC Power Consumption: +33 dBm Typical at 2 GHz at +3.3 V Supply Voltage and Only 83 mA	The PGA-102+ provides good IP3 performance relative to device size and power consumption. The combination of the design and E-pHEMT Structure provides enhanced linearity over a broad frequency range as evidenced in the IP3 being typically 15 dB above the P1dB point. This feature makes this amplifier ideal for use in: <ul style="list-style-type: none"> • Driver amplifiers for complex waveform up converter paths • Drivers in linearized transmit systems • Secondary amplifiers in ultra High Dynamic range receivers
No External Matching Components Required	Unlike competing products, Mini-Circuits PGA-102+ provides Input and Output Return Loss of 16-19 dB up to 4 GHz without the need for any external matching components.
Low Noise Figure: 2.3 dB at 0.8 GHz	A unique feature of the PGA-102+ which separates this design from all competitors is the low noise figure performance in combination with the high dynamic range.

REV. E
ECO-024506
PGA-102+
MCL NY
250212

Mini-Circuits

www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

PAGE 1 OF 5



ULTRA-HIGH DYNAMIC RANGE

Monolithic Amplifier

PGA-102+

50Ω 0.05 to 6 GHz

ELECTRICAL SPECIFICATIONS AT +25°C, 50Ω, UNLESS NOTED OTHERWISE

Parameter	Condition (GHz)	Min.	Typ.	Max.	Units
Frequency Range		0.05		6	GHz
Gain	0.05	14.4	17.7	17.4	dB
	0.8		15.9		
	2.0		14.0		
	3.0		12.5		
	4.0		11.5		
	6.0		10.4		
Input Return Loss	0.05	15	14.0	9.4	dB
	0.8		18.4		
	2.0		12.4		
	3.0		10.5		
	4.0		9.4		
	6.0		6.7		
Output Return Loss	0.05	15	18.3	11.0	dB
	0.8		18.6		
	2.0		17.6		
	3.0		17.1		
	4.0		15.3		
	6.0		11.0		
Reverse Isolation	2.0		21.9		dB
Output Power @ 1 dB Compression	0.05	+16.0	+17.6	+17.5	dBm
	0.8		+17.4		
	2.0		+17.5		
	3.0		+17.5		
	4.0		+17.3		
	6.0		+16.5		
Output IP3	0.05		+30.8	+33.0	dBm
	0.8		+32.7		
	2.0		+33.0		
	3.0		+33.0		
	4.0		+33.4		
	6.0		+33.2		
Noise Figure	0.05		2.1	2.4	dB
	0.8		2.3		
	2.0		2.4		
	3.0		2.8		
	4.0		3.0		
	6.0		3.9		
Device Operating Voltage		+3.1	+3.3	+3.5	V
Device Operating Current		60	83	120	mA
Device Current Variation vs. Temperature			49		µA/°C
Device Current Variation vs. Voltage			0.066		mA/mV
Thermal Resistance, Junction-to-Ground Lead			73		°C/W

1. Measured on Mini-Circuits Characterization test board TB-313. See Characterization Test Circuit (Fig. 1).



ULTRA-HIGH DYNAMIC RANGE

Monolithic Amplifier

PGA-102+

50Ω 0.05 to 6 GHz

ABSOLUTE MAXIMUM RATINGS²

Parameter	Ratings
Operating Temperature (Ground Lead)	-40°C to +85°C
Storage Temperature	-65°C to +150°C
Operating Current at +3.3 V	300 mA
Power Dissipation	1 W
Input Power (CW)	+28 dBm
DC Voltage on Pin 3	+5.5 V

2. Permanent damage may occur if any of these limits are exceeded.

Electrical maximum ratings are not intended for continuous normal operation.

SIMPLIFIED SCHEMATIC AND PAD DESCRIPTION



Function	Pin Number	Description
RF-IN	1	RF input pin. This pin requires the use of an external DC blocking capacitor chosen for the frequency of operation.
RF-OUT and DC-IN	3	RF output and bias pin. DC voltage is present on this pin; therefore a DC blocking capacitor is necessary for proper operation. An RF choke is needed to feed DC bias without loss of RF signal due to the bias connection, as shown in "Recommended Application Circuit", Fig. 2.
GND	2,4	Connections to ground. Use via holes as shown in "Suggested Layout for PCB Design" to reduce ground path inductance for best performance.



ULTRA-HIGH DYNAMIC RANGE

Monolithic Amplifier

PGA-102+

50Ω 0.05 to 6 GHz

CHARACTERIZATION TEST CIRCUIT





Fig 1. Block Diagram of Test Circuit used for characterization. (DUT tested on Mini-Circuits Characterization test board TB-313)
 Gain, Return Loss, Output Power at 1 dB Compression (P1 dB), Output IP3 (OIP3) and Noise Figure measured using Agilent's N5242A PNA-X microwave network analyzer.

Conditions:

1. Gain and Return loss: $P_{IN} = -25$ dBm
2. Output IP3 (OIP3): Two tones, spaced 10 MHz apart, 2.5 dBm/tone at output.

RECOMMENDED APPLICATION CIRCUIT



$C_{block}=0.001$ μ F, Bias-Tee=TCBT-14+, $C_{bypass}=0.1$ μ F

Fig 2. Evaluation board includes case, connectors, and components soldered to PCB

PRODUCT MARKING



Marking may contain other features or characters for internal lot control.

Mini-Circuits®



Mini-Circuits

ULTRA-HIGH DYNAMIC RANGE

Monolithic Amplifier

PGA-102+

50Ω 0.05 to 6 GHz

ADDITIONAL DETAILED TECHNICAL INFORMATION IS AVAILABLE ON OUR DASHBOARD. [CLICK HERE](#)

Performance Data	Data Table Swept Graphs S-Parameter (S2P Files) Data Set (.zip file)
Case Style	DF782 (SOT 89) Plastic package, exposed paddle lead finish: matte-tin
Tape & Reel Standard Quantities Available on Reel	F55 7" Reels with 20, 50, 100, 200, 500 or 1K devices
Suggested Layout for PCB Design	PL-313
Evaluation Board	TB-596-1+
Environmental Ratings	ENV08T1

ESD RATING

Human Body Model (HBM): Class 1B (500 to <1000 V) in accordance with ANSI/ESD STM 5.1 - 2001

Machine Model (MM): Class M1 (50 V) in accordance with ANSI/ESD STM5.2-1999



Attention
Observe precautions
for handling electrostatic
sensitive devices

MSL RATING

Moisture Sensitivity: MSL1 in accordance with IPC/JEDEC J-STD-020D

NOTES

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the standard terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/terms/viewterm.html

Mini-Circuits®

www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

PAGE 5 OF 5