

Frequency Synthesizer

SSN-3352A-119+

50Ω 3132 to 3352 MHz

The Big Deal

- Fractional N synthesizer
- Low phase noise and spurious
- Very small size 0.60" x 0.60" x 0.138"



CASE STYLE: KJ1367

Product Overview

The SSN-3352A-119+ is a Frequency Synthesizer, designed to operate from 3132 to 3352 MHz for WiMAX application. The SSN-3352A-119+ is packaged in a metal case (size of 0.60" x 0.60" x 0.138") to shield against unwanted signals and noise.

Key Features

Feature	Advantages
Low phase noise and spurious: <ul style="list-style-type: none">• Phase Noise: -92 dBc/Hz typ. @ 10 kHz offset• Step Size Spurious: -84 dBc typ.• Comparison Spurious: -88 dBc typ.• Reference Spurious: -88 dBc typ.	Low phase noise and spurious improve system EVM (Error Vector Magnitude).
Robust design and construction	To enhance the robustness of SSN-3352A-119+, each internal component is secured to the substrate with chip bonder, thereby eliminating the risk of tombstoning during subsequent solder reflow operations by the customer.
Small size, 0.60" x 0.60" x 0.138"	The small size enables the SSN-3352A-119+ to be used in compact designs.

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

Frequency Synthesizer

SSN-3352A-119+

50Ω 3132 to 3352 MHz

Features

- Fractional N synthesizer
- Integrated VCO + PLL
- Low phase noise and spurious
- Robust design and construction
- Low operating voltage (VCC VCO=+4.85V, VCC PLL=+3.2V)
- Small size 0.60" x 0.60" x 0.138"



CASE STYLE: KJ1367

+RoHS Compliant
The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications


Applications

- WiMAX

General Description

The SSN-3352A-119+ is a Frequency Synthesizer, designed to operate from 3132 to 3352 MHz for WiMAX application. The SSN-3352A-119+ is packaged in a metal case (size of 0.60" x 0.60" x 0.138") to shield against unwanted signals and noise. To enhance the robustness of SSN-3352A-119+, each internal component is secured to the substrate with chip bonder, thereby eliminating the risk of tombstoning during subsequent solder reflow operations by the customer.

Simplified Schematic



Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

REV. A
M151108
EDR-10128F1
SSN-3352A-119+
Category-A1
RAV
151012
Page 2 of 13

Electrical Specifications (over operating temperature -40°C to +85°C)

Parameters	Test Conditions	Min.	Typ.	Max.	Units	
Frequency Range	-	3132	-	3352	MHz	
Step Size	-	-	125	-	kHz	
Comparison Frequency	-	-	26	-	MHz	
Settling Time	Within ± 1 kHz	-	5	-	mSec	
Output Power	-	0	+3	+6	dBm	
SSB Phase Noise	@ 100 Hz offset	-	-75	-	dBc/Hz	
	@ 1 kHz offset	-	-90	-83		
	@ 10 kHz offset	-	-92	-87		
	@ 100 kHz offset	-	-116	-109		
	@ 1 MHz offset	-	-137	-129		
Integrated SSB Phase Noise	@1kHz to 10MHz	-	-49	-45	dBc	
Step Size Spurious Suppression	Step Size 125 kHz	-	-84	-54	dBc	
0.5 Step Size Spurious Suppression	0.5 Step Size 62.5 kHz	-	-70	-54		
Reference Spurious Suppression	Ref. Freq. 52 MHz	-	-88	-80		
Comparison Spurious Suppression	Comp. Freq. 26 MHz	-	-88	-80		
Non - Harmonic Spurious Suppression	-	-	-90	-		
Harmonic Suppression	-	-	-30	-20		
VCO Supply Voltage	+4.85	+4.75	+4.85	+5.25	V	
PLL Supply Voltage	+3.20	+3.10	+3.20	+3.30	V	
VCO Supply Current	-	-	44	55	mA	
PLL Supply Current	-	-	17	26		
Reference Input (External)	Frequency	52 (square wave)	-	52	MHz	
	Amplitude	1	-	1	V _{P-P}	
	Input impedance	-	-	100	KΩ	
	Phase Noise @ 1 kHz offset	-	-	-135	dBc/Hz	
RF Output port Impedance	-	-	50	-	Ω	
Input Logic Level	Input high voltage	-	2.65	-	V	
	Input low voltage	-	-	0.60	V	
Digital Lock Detect	Locked	-	2.70	-	3.30	V
	Unlocked	-	-	-	0.40	V
Frequency Synthesizer PLL	-	ADF4153				
PLL Programming	-	3-wire serial 3.2V CMOS				
Register Map @ 3352 MHz	R0_Register	-	(MSB) 00100000000001100000000 (LSB)			
	R1_Register	-	(MSB) 000101001000001101000001 (LSB)			
	R2_Register	-	(MSB) 000000000000001111000011 (LSB)			
	R3_Register	-	(MSB) 000000000000001111000111 (LSB)			

Absolute Maximum Ratings

Parameters	Ratings
VCO Supply Voltage	5.8V
PLL Supply Voltage	4.0V
VCO Supply Voltage to PLL Supply Voltage	-0.3V to +5.8V
Reference Frequency Voltage	-0.3Vmin, VCC PLL +0.3Vmax
Data, Clock, LE Levels	-0.3Vmin, VCC PLL +0.3Vmax
Operating Temperature	-40°C to +85°C
Storage Temperature	-55°C to +100°C

Permanent damage may occur if any of these limits are exceeded

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



Typical Performance Data

FREQUENCY (MHz)	POWER OUTPUT (dBm)			VCO CURRENT (mA)			PLL CURENT (mA)		
	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
3132	2.88	2.95	2.95	41.81	43.57	44.88	14.90	16.82	19.05
3144	2.91	2.95	2.93	41.84	43.61	44.90	14.47	16.37	18.64
3169	2.95	3.00	2.98	41.91	43.65	44.95	14.67	16.57	18.91
3193	2.92	2.99	3.00	41.91	43.65	44.96	14.73	16.64	19.01
3218	2.71	2.76	2.79	41.98	43.72	45.00	14.80	16.72	19.13
3242	2.85	2.84	2.83	42.02	43.76	45.06	14.75	16.66	19.09
3267	2.87	2.94	2.98	42.09	43.79	45.10	14.90	16.82	19.27
3291	2.70	2.75	2.82	42.17	43.88	45.17	14.92	16.84	19.31
3316	2.86	2.85	2.87	42.22	43.93	45.21	14.99	16.92	19.40
3340	3.00	3.02	3.05	42.29	43.96	45.23	14.89	16.80	19.29
3352	2.94	2.98	3.03	42.33	43.99	45.25	14.46	16.36	18.80

FREQUENCY (MHz)	HARMONICS (dBc)					
	F2			F3		
	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
3132	-34.40	-29.87	-28.05	-47.19	-47.36	-56.19
3144	-32.01	-29.90	-27.58	-47.63	-47.51	-56.63
3169	-30.66	-30.00	-28.92	-46.04	-47.47	-56.90
3193	-30.67	-29.89	-29.63	-45.86	-46.28	-56.50
3218	-28.47	-30.64	-30.18	-43.39	-44.80	-51.86
3242	-30.14	-31.48	-30.24	-42.95	-44.38	-49.40
3267	-30.27	-32.15	-32.53	-48.20	-44.74	-47.98
3291	-31.82	-32.17	-30.75	-45.24	-44.46	-48.84
3316	-33.63	-33.63	-33.99	-45.95	-44.36	-48.70
3340	-33.36	-33.49	-33.51	-43.63	-44.50	-47.86
3352	-31.82	-32.90	-32.98	-41.81	-44.48	-47.32

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



FREQUENCY (MHz)	PHASE NOISE (dBc/Hz) @OFFSETS				
	+25°C				
	100Hz	1kHz	10kHz	100kHz	1MHz
3132	-74.73	-88.13	-92.40	-116.98	-137.51
3144	-75.12	-90.71	-92.38	-116.97	-137.41
3169	-76.00	-88.04	-92.46	-116.80	-137.35
3193	-75.70	-89.95	-91.63	-116.68	-137.09
3218	-79.23	-88.69	-91.35	-116.56	-137.13
3242	-74.23	-90.15	-91.96	-116.28	-136.89
3267	-77.39	-89.16	-91.56	-115.88	-136.68
3291	-74.40	-91.72	-91.71	-115.80	-136.43
3316	-73.57	-88.13	-91.49	-115.81	-136.29
3340	-74.90	-89.54	-91.29	-116.22	-136.87
3352	-75.00	-89.75	-91.43	-116.56	-137.23

FREQUENCY (MHz)	PHASE NOISE (dBc/Hz) @OFFSETS				
	-45°C				
	100Hz	1kHz	10kHz	100kHz	1MHz
3132	-80.39	-89.98	-94.58	-117.94	-138.87
3144	-76.54	-92.17	-93.87	-117.96	-138.74
3169	-77.83	-93.28	-92.89	-117.84	-138.60
3193	-80.72	-90.75	-92.92	-117.52	-138.35
3218	-80.81	-92.71	-93.10	-117.35	-138.18
3242	-79.34	-92.46	-92.82	-117.10	-138.03
3267	-78.51	-92.42	-92.72	-116.80	-137.64
3291	-79.44	-90.33	-92.99	-116.62	-137.52
3316	-77.29	-91.06	-92.79	-116.13	-137.05
3340	-77.30	-89.08	-91.87	-116.79	-137.99
3352	-77.79	-90.23	-93.11	-117.20	-137.96

FREQUENCY (MHz)	PHASE NOISE (dBc/Hz) @OFFSETS				
	+85°C				
	100Hz	1kHz	10kHz	100kHz	1MHz
3132	-75.10	-89.87	-91.29	-115.23	-135.54
3144	-78.20	-90.91	-90.82	-115.13	-135.69
3169	-75.11	-89.39	-91.13	-115.23	-135.65
3193	-76.35	-86.55	-91.36	-115.16	-135.64
3218	-79.76	-90.17	-91.20	-115.13	-135.66
3242	-78.50	-90.26	-90.68	-114.92	-135.44
3267	-76.10	-90.26	-91.14	-114.66	-135.36
3291	-76.95	-91.62	-90.43	-114.70	-135.11
3316	-76.67	-88.56	-91.20	-114.94	-135.26
3340	-76.59	-86.97	-90.60	-115.39	-135.87
3352	-78.70	-86.22	-90.96	-115.49	-135.97

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



COMPARISON SPURIOUS ORDER	COMPARISON SPURIOUS @Fcarrier 3132MHz+(n*Fcomparison) (dBc) note 1			COMPARISON SPURIOUS @Fcarrier 3242MHz+(n*Fcomparison) (dBc) note 1			COMPARISON SPURIOUS @Fcarrier 3352MHz+(n*Fcomparison) (dBc) note 1			
	n	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
	-5	-98.77	-98.08	-99.60	-98.78	-100.34	-99.45	-102.00	-101.72	-102.85
-4	-92.09	-94.93	-94.82	-96.97	-99.18	-97.49	-101.23	-101.34	-98.46	
-3	-99.42	-97.58	-99.91	-99.60	-98.31	-99.69	-99.75	-98.95	-101.20	
-2	-87.40	-87.16	-87.54	-90.00	-89.65	-89.04	-90.29	-90.45	-89.56	
-1	-95.96	-101.48	-110.44	-102.57	-105.89	-108.85	-96.61	-102.25	-109.06	
0 ^{note 2}	-	-	-	-	-	-	-	-	-	
+1	-95.67	-95.93	-95.39	-95.45	-95.17	-93.99	-92.49	-93.44	-95.54	
+2	-98.31	-94.69	-95.83	-102.40	-100.84	-99.56	-100.34	-100.54	-98.23	
+3	-95.44	-100.77	-97.59	-98.93	-99.78	-99.09	-99.37	-100.02	-103.07	
+4	-94.34	-95.30	-95.50	-100.00	-98.56	-99.00	-103.42	-100.54	-99.29	
+5	-109.16	-108.84	-115.21	-113.38	-114.06	-117.35	-110.90	-118.47	-112.14	

Note 1: Comparison frequency 26 MHz
 Note 2: All spurs are referenced to carrier signal (n=0).

REFERENCE SPURIOUS ORDER	REFERENCE SPURIOUS @Fcarrier 3132MHz+(n*Freference) (dBc) note 3			REFERENCE SPURIOUS @Fcarrier 3242MHz+(n*Freference) (dBc) note 3			REFERENCE SPURIOUS @Fcarrier 3352MHz+(n*Freference) (dBc) note 3			
	n	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
	-5	-89.81	-94.14	-100.25	-97.45	-100.10	-112.72	-97.30	-100.01	-104.94
-4	-92.32	-93.81	-93.82	-105.08	-104.46	-101.41	-108.13	-110.02	-102.20	
-3	-98.54	-99.03	-96.59	-112.88	-104.08	-99.73	-114.89	-105.11	-98.92	
-2	-92.09	-94.93	-94.82	-96.97	-99.18	-97.49	-101.23	-101.34	-98.46	
-1	-87.40	-87.16	-87.54	-90.00	-89.65	-89.04	-90.29	-90.45	-89.56	
0 ^{note 4}	-	-	-	-	-	-	-	-	-	
+1	-98.31	-94.69	-95.83	-102.40	-100.84	-99.56	-100.34	-100.54	-98.23	
+2	-94.34	-95.30	-95.50	-100.00	-98.56	-99.00	-103.42	-100.54	-99.29	
+3	-107.64	-114.42	-109.44	-108.96	-109.57	-106.28	-110.58	-110.57	-105.60	
+4	-96.40	-96.98	-95.29	-111.64	-103.51	-98.63	-111.85	-104.83	-96.69	
+5	-90.48	-92.12	-95.48	-97.49	-96.21	-99.02	-97.96	-97.68	-99.85	

Note 3: Reference frequency 52 MHz
 Note 4: All spurs are referenced to carrier signal (n=0).

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



STEP SIZE SPURIOUS ORDER n	0.5 STEP SIZE & STEP SIZE SPURIOUS @Fcarrier 3132MHz+(n*Fstep size) (dBc) note 5			0.5 STEP SIZE & STEP SIZE SPURIOUS @Fcarrier 3242MHz+(n*Fstep size) (dBc) note 5			0.5 STEP SIZE & STEP SIZE SPURIOUS @Fcarrier 3352MHz+(n*Fstep size) (dBc) note 5		
	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
-5.0	-111.93	-113.04	-110.36	-105.92	-110.68	-109.48	-108.42	-112.27	-110.64
-4.5	-107.27	-107.49	-106.03	-111.50	-107.11	-107.54	-109.96	-106.13	-111.21
-4.0	-108.37	-111.14	-108.38	-107.28	-110.31	-106.80	-109.76	-111.47	-108.32
-3.5	-108.49	-106.43	-109.05	-104.00	-106.71	-104.02	-109.20	-106.26	-107.45
-3.0	-106.56	-106.92	-104.90	-104.50	-104.71	-105.17	-106.35	-100.04	-104.20
-2.5	-101.13	-101.25	-102.25	-100.34	-99.57	-101.68	-101.57	-104.20	-102.96
-2.0	-99.41	-98.89	-100.60	-97.05	-99.33	-98.27	-96.27	-97.27	-95.11
-1.5	-95.66	-96.21	-90.83	-90.08	-94.46	-90.65	-93.95	-94.07	-89.97
-1.0	-83.93	-85.44	-85.72	-86.19	-83.61	-87.75	-80.11	-77.06	-87.40
-0.5	-73.51	-71.36	-68.07	-75.00	-72.24	-70.79	-80.12	-72.14	-82.79
0 ^{note 6}	-	-	-	-	-	-	-	-	-
+0.5	-75.10	-70.48	-69.13	-74.45	-73.58	-72.57	-77.88	-69.59	-81.44
+1.0	-83.60	-88.33	-86.23	-83.65	-82.60	-84.95	-82.63	-78.41	-85.02
+1.5	-96.00	-96.43	-94.64	-90.18	-93.16	-90.09	-93.67	-93.34	-91.20
+2.0	-97.97	-99.68	-100.76	-96.39	-96.85	-100.37	-94.79	-97.71	-97.24
+2.5	-104.71	-103.85	-100.68	-104.36	-99.60	-102.44	-99.67	-105.20	-100.91
+3.0	-106.51	-104.37	-104.43	-107.67	-102.28	-103.35	-106.99	-100.91	-105.50
+3.5	-105.92	-105.19	-108.43	-107.20	-106.57	-105.13	-107.61	-108.44	-104.03
+4.0	-108.39	-110.56	-110.11	-105.93	-110.84	-105.06	-108.64	-104.34	-108.96
+4.5	-110.20	-109.42	-107.86	-109.07	-105.69	-107.78	-110.19	-106.48	-110.15
+5.0	-113.85	-110.57	-110.70	-108.21	-113.39	-110.89	-110.17	-109.51	-112.90

Note 5: Step size 125 kHz




Note 6: All spurs are referenced to carrier signal (n=0).

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp








Typical Performance Curves



Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp











Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp






Notes


- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp




0.5 STEP SIZE & STEP SIZE SPURIOUS
Vs FREQ. OFFSET @ Fcar = 3132MHz



0.5 STEP SIZE & STEP SIZE SPURIOUS
Vs FREQ. OFFSET @ Fcar = 3242MHz



0.5 STEP SIZE & STEP SIZE SPURIOUS
Vs FREQ. OFFSET @ Fcar = 3352MHz




Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



Pin Configuration




Pin Connection

Pin Number	Function
1	CLOCK
2	DATA
3	ENABLED
4	REF IN
5	GND
6	GND
7	VCC VCO
8	GND
9	RF OUT
10	GND
11	LOCK DET
12	VCC PLL

Recommended Application Circuit

Note: REF IN and RF OUT ports are internally AC coupled.




Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuits' applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



Device Marking



Additional Detailed Technical Information

Additional information is available on our web site. To access this information enter the model number on our web site home page.

Case Style: KJ1367

Tape & Reel: TR-F95

Suggested Layout for PCB Design: PL-317

Evaluation Board: TB-552+

Environment Ratings: ENV65T2

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

