


Frequency Synthesizer **SSND-1014N-119+**

50Ω Dual Frequency 1000 and 1440 MHz (fixed)

The Big Deal

- Dual frequency
- Low phase noise and spurious
- Very small size 0.60" x 0.60" x 0.138"



CASE STYLE: KJ1373

Product Overview

The SSND-1014N-119+ is a Dual Frequency Synthesizer, designed to operate at two discrete, single frequency synthesizers 1000 and 1440 MHz for GPS receiver application. The SSND-1014N-119+ is packaged in a very small metal case (size of 0.60" x 0.60" x 0.138") to shield against unwanted signals and noise.

Key Features

Feature	Advantages
Dual frequency	For saving in cost and system real estate.
Low phase noise and spurious	Low phase noise and spurious improve system EVM (Error Vector Magnitude).
Very small size, 0.60" x 0.60" x 0.138"	The small size enables the SSND-1014N-119+ to be used in compact designs.
Low current consumptions	Can be used in a portable system.

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

Surface Mount

Frequency Synthesizer

SSND-1014N-119+

50Ω Dual Frequency 1000 and 1440 MHz (fixed)

Features

- Dual frequency
- Integrated VCO + PLL
- Low phase noise and spurious
- Robust design and construction
- Low operating voltage (VCC RF-IF=+2.5V, VCC VCO RF=+3.0V, VCC VCO IF=+3.0V)
- Small size 0.60" x 0.60" x 0.138"



CASE STYLE: KJ1373

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications


Applications

- GPS receiver

General Description

The SSND-1014N-119+ is a Frequency Synthesizer, designed to operate at 1000 and 1440 MHz for GPS receiver application. The SSND-1014N-119+ is packaged in a metal case (size of 0.60" x 0.60" x 0.138") to shield against unwanted signals and noise. To enhance the robustness of SSND-1014N-119+, each internal component is secured to the substrate with chip bonder, thereby eliminating the risk of tombstoning during subsequent solder reflow operations by the customer.

Simplified Schematic



Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuit's website at www.minicircuits.com/MCLStore/terms.jsp



www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

REV. B
M151108
EDR-9422/4F1
SSND-1014N-119+
Category-A2
RAV
151013
Page 2 of 11

Electrical Specifications (over operating temperature -40°C to +85°C)

Parameters	Test Conditions	Min.	Typ.	Max.	Units	
IF Frequency Range (Fixed)	-	1000	-	1000	MHz	
RF Frequency Range (Fixed)	-	1440	-	1440		
Comparison Frequency	-	-	2000	-	kHz	
Settling Time	Within ± 1 kHz	-	0.4	-	mSec	
IF Output Power	-	-12.0	-9.7	-8.0	dBm	
RF Output Power	-	+1.0	+2.9	+5.0		
IF SSB Phase Noise	@ 100 Hz offset	-	-84	-	dBc/Hz	
	@ 1 kHz offset	-	-92	-87		
	@ 10 kHz offset	-	-90	-86		
	@ 100 kHz offset	-	-118	-114		
	@ 1 MHz offset	-	-145	-140		
RF SSB Phase Noise	@ 100 Hz offset	-	-82	-		
	@ 1 kHz offset	-	-89	-84		
	@ 10 kHz offset	-	-89	-85		
	@ 100 kHz offset	-	-119	-115		
	@ 1 MHz offset	-	-143	-135		
IF Reference Spurious Suppression	Ref. Freq. 10 MHz	-	-80	-70	dBc	
RF Reference Spurious Suppression		-	-106	-76		
IF Comparison Spurious Suppression	Comp Freq. 2000 kHz	-	-96	-80		
RF Comparison Spurious Suppression		-	-97	-78		
Non - Harmonic Spurious Suppression	-	-	-90	-		
IF Harmonic Suppression	-	-	-30	-19		
RF Harmonic Suppression	-	-	-31	-26		
VCC RF-IF Supply Voltage	+2.50	+2.25	+2.50	+2.75	V	
VCC VCO IF Supply Voltage	+3.00	+2.95	+3.00	+3.05		
VCC VCO RF Supply Voltage	+3.00	+2.95	+3.00	+3.05		
VCC RF-IF Supply Current	-	-	6	12	mA	
VCO IF Supply Current	-	-	7	13		
VCO RF Supply Current	-	-	10	16		
Reference Input (External)	Frequency	10 (square wave)	-	10	-	MHz
	Amplitude	1	-	1	-	V _{P-P}
	Input impedance	-	-	100	-	KΩ
	Phase Noise @ 1 kHz offset	-	-	-145	-	dBc/Hz
RF Output port Impedance	-	-	50	-	Ω	
Input Logic Level	Input high voltage	-	2.20	-	-	V
	Input low voltage	-	-	-	0.45	V
Digital Lock Detect	Locked	-	1.90	-	2.70	V
	Unlocked	-	-	-	0.40	V
Frequency Synthesizer PLL	-	LMX2433				
PLL Programming	-	3-wire serial 2.5V CMOS				
Register Map @ IF+RF Freq.	R0_Register	-	(MSB) 00001000000000000101000 (LSB)			
	R1_Register	-	(MSB) 010000000001011010000001 (LSB)			
	R2_Register	-	(MSB) 00000000000000000000010 (LSB)			
	R3_Register	-	(MSB) 1100010000000000000101011 (LSB)			
	R4_Register	-	(MSB) 010000000000111110100100 (LSB)			
	R5_Register	-	(MSB) 000000000000000000000101 (LSB)			

Absolute Maximum Ratings

Parameters	Ratings
VCO Supply Voltage	4V
PLL Supply Voltage	3V
VCO Supply Voltage to PLL Supply Voltage	N.A
Reference Frequency Voltage	-0.5Vmin, VCC RF-IF +0.3Vmax
Data, Clock, LE Levels	-0.3Vmin, VCC RF-IF +0.3Vmax
Operating Temperature	-40°C to +85°C
Storage Temperature	-55°C to +100°C

Permanent damage may occur if any of these limits are exceeded

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



Typical Performance Data

FREQUENCY		POWER OUTPUT (dBm)			VCO CURRENT (mA)			PLL CURENT (mA)		
		-45°C	+25°C	+85°C	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
IF	1000	-10.29	-9.72	-9.94	6.86	7.90	8.65	6.47	6.66	6.82
RF	1440	1.93	2.95	3.68	8.86	10.46	11.57	6.47	6.66	6.82

FREQUENCY		HARMONICS (dBc)					
		F2			F3		
		-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
IF	1000	-24.83	-31.22	-43.66	-49.04	-44.89	-36.17
RF	1440	-29.89	-30.87	-32.32	-57.39	-63.55	-67.75

FREQUENCY		@TEMP.	PHASE NOISE (dBc/Hz)				
			@OFFSETS				
			100Hz	1kHz	10kHz	100kHz	1MHz
IF	1000	-45°C	-82.37	-92.65	-91.73	-118.91	-146.75
		+25°C	-83.35	-90.41	-91.46	-118.35	-145.98
		+85°C	-86.92	-92.44	-91.14	-117.31	-144.69
RF	1440	-45°C	-80.87	-90.97	-89.77	-120.14	-143.76
		+25°C	-82.69	-91.08	-89.51	-119.8	-143.09
		+85°C	-82.90	-89.83	-89.92	-119.21	-142.57

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



COMPARISON SPURIOUS ORDER n	(IF) COMPARISON SPURIOUS @Fcarrier 1000MHz+(n*Fcomparison) (dBc) note 1			(RF) COMPARISON SPURIOUS @Fcarrier 1440MHz+(n*Fcomparison) (dBc) note 1		
	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
-4	-101.21	-104.36	-102.09	-96.99	-122.86	-104.97
-3	-98.72	-105.65	-102.13	-98.11	-114.62	-96.87
-2	-93.83	-106.00	-96.70	-92.74	-116.44	-92.69
-1	-90.41	-96.24	-90.61	-85.19	-103.99	-88.86
0 note 2	-	-	-	-	-	-
+1	-87.18	-90.94	-90.61	-85.35	-104.64	-88.89
+2	-89.40	-103.62	-101.95	-92.89	-117.51	-92.77
+3	-93.28	-98.88	-108.19	-98.86	-117.27	-96.70
+4	-97.85	-100.78	-105.91	-97.13	-124.83	-104.39

Note 1: Comparison frequency 2000 kHz

Note 2: All spurs are referenced to carrier signal (n=0).

REFERENCE SPURIOUS ORDER n	(IF) REFERENCE SPURIOUS @Fcarrier 1000MHz+(n*Freference) (dBc) note 3			(RF) REFERENCE SPURIOUS @Fcarrier 1440MHz+(n*Freference) (dBc) note 3		
	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
-5	-107.54	-105.37	-105.57	-115.59	-103.43	-110.01
-4	-93.75	-97.17	-96.16	-117.59	-110.24	-110.38
-3	-84.36	-86.05	-86.28	-114.38	-110.76	-112.91
-2	-78.28	-78.97	-79.06	-124.24	-104.56	-119.42
-1	-75.49	-76.34	-76.07	-119.55	-107.94	-100.63
0 note 4	-	-	-	-	-	-
+1	-82.30	-82.04	-81.92	-105.29	-104.57	-110.55
+2	-83.79	-83.41	-83.57	-111.78	-110.73	-114.76
+3	-89.47	-90.36	-90.65	-123.06	-112.23	-115.98
+4	-98.90	-99.89	-101.31	-117.19	-120.43	-115.81
+5	-108.33	-112.67	-117.95	-113.26	-113.11	-112.92

Note 3: Reference frequency 10 MHz


Note 4: All spurs are referenced to carrier signal (n=0).

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp









Typical Performance Curves







Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp









Notes
 A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
 B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuits' applicable established test performance criteria and measurement instructions.
 C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp






Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



Pin Configuration




Pin Connection

Pin Number	Function
1	IF OUT
2	GND
3	VCC RF-IF
4	VCC VCO IF
5	REF IN
6	LOCK DET
7	RF OUT
8	GND
9	VCC VCO RF
10	CLOCK
11	DATA
12	LE

Recommended Application Circuit

Note: REF IN and RF OUT ports are internally AC coupled.




Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



Device Marking



Additional Detailed Technical Information

Additional information is available on our web site. To access this information enter the model number on our web site home page.

Case Style: KJ1373

Tape & Reel: TR-F95

Suggested Layout for PCB Design: PL-325

Evaluation Board: TB-571+

Environment Ratings: ENV65T2

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

