# Directional Coupler

# TCD-9-1W-75

CASE STYLE: DB714

PRICE: Contact Sales Dept.

# $75\Omega$

## 5 to 2000 MHz

## **Maximum Ratings**

Operating Temperature	-40°C to 85°C
Storogo Tomporoturo	EE°C to 100°C


Storage Temperature -55°C to 100°C

\* Case temperature is defined as temperature on ground leads. Permanent damage may occur if any of these limits are exceeded.


#### Pin Connections

INPUT	3
OUTPUT	4
COUPLED	1
GROUND	2
75Ω TERM EXTERNAL	6
NOT USED	5

#### **Outline Drawing**



#### PCB Land Pattern




Suggested Layout Tolerance to be within ±.002

## Outline Dimensions (inch)

III /	<b>\</b> 111				
F	Е	D	С	В	Α
.025	.040	.050	.160	.150	.160
0.64	1.02	1.27	4.06	3.81	4.06
wt		K	J	Н	G
grams		.030	.190	.065	.028
0.15		0.76	4 83	1 65	0.71

#### Demo Board MCL P/N: TB-72 Suggested PCB Layout (PL-010)



RESISTOR R1: 75 ± 1% Ohm, 0805 SIZE

- NOTES: 1. TRACE WIDTH IS SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS 0.030" ± 0.002"; COPPER: 1/2 0Z. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.

  2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.
  - DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)
  - DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

#### **Features**

- wideband, 5 to 2000 MHz
- low mainline loss, 1.3 dB typ. (5-1000 MHz)
- · aqueous washable
- leads for excellent solderability
- protected by US Patent 6,140,887

## **Applications**

- GPS
- cellular
- satellite distribution
- CATV

## **Electrical Specifications**

FREQ. RANGE (MHz)		PLING IB)	MAINLINE LOSS (dB)			SS <sup>1</sup>			DIRECTIVITY (dB)				VSWR (:1)	POV			
`				L	1	M	ι	J	l	L	1	M	l	J		L	MU
f <sub>L</sub> -f <sub>U</sub>	Nom.	Flatness	Тур.	Max.	Тур.	Max.	Тур.	Max.	Тур.	Min.	Тур.	Min.	Тур.	Min.	Тур.	Max.	Max.
5-1000	8.9±0.5	±0.6	1.3	2.1	1.3	2.0	1.8	2.4	21	17	15	_	10	_	1.30	0.5	1.0
1000-2000	8.9±0.5	±0.6	_	_	2.5		_	_	_	_	10	_	_	_	1.60	_	1.0

 $M = mid range [10 f_L to f_U/2]$ U= upper range [f<sub>U</sub>/2 to f<sub>U</sub>]


## **Typical Performance Data**


Frequency (MHz)	Mainline Loss (dB)	Coupling (dB)	Directivity (dB)	Return Loss (dB)				
. ,	In-Oút	In-Cpl		In	Ouť	Cpl		
5.00	1.29	8.99	21.24	16.92	25.24	16.42		
200.00	1.28	8.94	17.61	17.17	24.67	16.49		
600.00	1.46	8.84	11.06	12.00	15.49	12.84		
800.00	1.63	8.81	9.49	11.14	14.69	11.57		
1000.00	1.87	8.78	8.59	11.05	14.44	10.62		
1200.00	2.06	8.67	8.12	11.15	14.53	9.81		
1400.00	2.27	8.65	7.88	11.16	14.51	9.22		
1600.00	2.50	8.89	7.63	11.20	15.36	8.91		
1800.00	2.71	8.90	7.19	11.56	15.46	8.40		
2000.00	2.73	8.41	6.49	11.81	14.35	8.53		

# MAINLINE LOSS ලි <sup>2.5</sup> WAINLINE LOSS (2.0 1.5 1.0 0.5 0.0 1000 FREQUENCY (MHz) 2000 0



## **COUPLING & DIRECTIVITY**





For detailed performance speci



<sup>1.</sup> Mainline loss includes theoretical power loss at coupled port.