
# Coaxial **SMA Fixed Attenuator**

#### 15dB 50Ω 2W

#### **Maximum Ratings**

Operating Temperature	-45°C to 100°C
Storage Temperature	-55°C to 100°C
Permanent damage may occur if any	of these limits are exceeded.

#### **Outline Drawing**



#### Outline Dimensions (inch )

wt	Е	D	В
grams	.312	1.43	.74
11.4	7.92	36.32	18.80

Notes

# DC to 6000 MHz

#### Features

- wideband coverage, DC to 6000 MHz
- 2 watt rating
- rugged unibody construction
- off-the-shelf availability
- · very low cost

#### **Applications**

- impedance matching
- signal level adjustment





Generic photo used for illustration purposes only CASE STYLE: DC1066

Connectors Model VAT-15W2(+) SMA

#### +RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications


### **Electrical Specifications**


FREQ. RANGE (MHz)	ATTENUATION * (dB) Flatness **		VSWR (:1)			MAX. INPUT POWER			
		DC-3 GHz	3-5 GHz	5-6 GHz	DC-6 GHz	DC-3 GHz	3-5 GHz	5-6 GHz	(W)
f <sub>L</sub> -f <sub>U</sub>	Nom.	Тур.	Тур.	Тур.	Тур.	Тур. Мах.	Тур. Мах.	Тур.	
DC-6000	15±0.3	0.20	0.30	0.30	0.80	1.30 1.50	1.60 1.80	1.75	2.0

\* Attenuation varies by 0.3 dB max. over temperature.

\*\* Flatness= variation over band divided by 2.

Frequency (MHz)	Attenuation (dB)	VSWR (:1)	
(	()	()	
10.00	15.01	1.00	
100.00	15.03	1.00	
1000.00	15.05	1.04	
2000.00	14.91	1.10	
3000.00	14.68	1.17	
4000.00	14.43	1.26	
4500.00	14.32	1.32	
5000.00	14.22	1.40	
5500.00	14.14	1.49	
6000.00	14.06	1.61	





A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document. B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement ins C. The parts covered by this specification document are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part

Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable stabilished test performance orteria and measurement instructions. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuit's website at www.minicircuits.com/MCLStore/terms.jsp



## Mini-Circuits

www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com