

# Surface Mount Directional Coupler

## ADC-20-13+

50Ω 450 to 1000 MHz


### Maximum Ratings

Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C


### Pin Connections

INPUT	1
OUTPUT	6
COUPLED	3
GROUND	2
50Ω TERM EXTERNAL	4
ISOLATE (DO NOT USE)	5

### Outline Drawing



### PCB Land Pattern



Suggested Layout,  
Tolerance to be within ±.002


### Outline Dimensions (inch/mm)

A	B	C	D	E	F	G
.272	.310	.220	.100	.112	.055	.100
6.91	7.87	5.59	2.54	2.84	1.40	2.54

H	J	K	L	wt
.030	.026	.065	.300	grams
0.76	0.66	1.65	7.62	0.20

### Demo Board MCL P/N: TB-05 Suggested PCB Layout (PL-095)



- NOTES: 1. TRACE WIDTH IS SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS .030" ± .002"; COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.  
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.
- DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)
  - DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

### Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.  
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuits' applicable established test performance criteria and measurement instructions.  
C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at [www.minicircuits.com/MCLStore/terms.jsp](http://www.minicircuits.com/MCLStore/terms.jsp)

### Features

- power handling up to 4 Watt.
- low mainline loss, 0.20 dB typ.
- high directivity, 25 dB typ.
- excellent VSWR, 1.2:1 typ.
- aqueous washable

### Applications

- cable tv
- VHF/UHF receivers
- cellular



Generic photo used for illustration purposes only  
CASE STYLE: CD542

### +RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Available Tape and Reel at no extra cost

Reel Size	Devices/Reel
7"	20, 50, 100, 200
13"	500, 1000




### Electrical Specifications at 25°C

Parameter	Condition (MHz)	Min.	Typ.	Max.	Unit
<b>Frequency Range</b>		450	—	1000	MHz
<b>Mainline Loss</b> (above theoretical 0.05 dB)	450 700 1000	— — —	0.2 0.2 0.3	0.3 0.4 0.5	dB
<b>Coupling</b>	450-1000 450 700 1000	— 19.0 18.4 17.0	19.7 20.7 20.0 19.0	22.2 21.6 21.0	dB
<b>Coupling Flatness(±)</b>	450-700 700-1000	— —	0.4 0.5	0.6 0.7	dB
<b>Directivity</b>	450 700 1000	18 16 13	22 20 18	— — —	dB
<b>Return Loss (Input)</b>	450 700 1000	20 19 16	24 25 23	— — —	dB
<b>Return Loss (Output)</b>	450 700 100	20 18 15	24 25 23	— — —	dB
<b>Return Loss (Coupling)</b>	450 700 1000	18 17 14	21 20 18	— — —	dB
<b>Input Power<sup>1</sup></b>	450-1000			4.0	W


1. Maximum input power with 2:1 VSWR (maximum) load at output port.

### Typical Performance Data

Frequency (MHz)	Mainline Loss (dB)		Coupling (dB) In-Cpl	Directivity (dB)	Return Loss (dB)		
	In-Out				In	Out	Cpl
450.00	0.18		20.98	27.72	23.85	23.86	20.98
500.00	0.19		20.87	27.19	24.06	24.14	20.94
560.00	0.20		20.72	26.86	24.11	24.24	20.73
600.00	0.21		20.63	26.88	24.09	24.19	20.61
700.00	0.22		20.38	26.45	23.71	23.87	20.01
760.00	0.24		20.23	25.91	23.35	23.52	19.59
800.00	0.25		20.10	25.41	23.09	23.23	19.26
900.00	0.27		19.81	24.46	22.21	22.40	18.51
950.00	0.29		19.67	23.94	21.81	21.94	18.11
1000.00	0.30		19.52	23.40	21.25	21.43	17.82



### Electrical Schematic



REV. A  
M151107  
ED-13396/2  
ADC-20-13+  
HL/CP/AM  
200414

# Directional Coupler

# ADC-20-13+

## Typical Performance Data

FREQUENCY (MHz)	INSERTION LOSS (dB)	COUPLING (dB)	DIRECTIVITY (dB)	RETURN LOSS (dB)		
				IN	OUT	CPL
100.0	0.28	21.64	25.28	14.06	14.07	14.01
150.0	0.20	21.49	26.96	17.21	17.22	16.89
200.0	0.17	21.41	27.78	19.38	19.37	18.64
250.0	0.17	21.34	28.02	20.88	20.84	19.72
300.0	0.17	21.26	27.89	21.95	21.91	20.36
350.0	0.17	21.18	28.16	22.82	22.79	20.75
400.0	0.17	21.09	27.92	23.48	23.42	20.92
410.0	0.18	21.07	27.86	23.59	23.50	20.93
420.0	0.18	21.05	27.78	23.67	23.61	20.95
430.0	0.18	21.03	27.76	23.74	23.69	20.96
440.0	0.18	21.01	27.72	23.79	23.78	20.97
450.0	0.18	20.98	27.72	23.85	23.86	20.98
460.0	0.18	20.96	27.58	23.90	23.92	20.99
470.0	0.19	20.94	27.51	23.95	23.99	20.99
480.0	0.19	20.92	27.41	24.00	24.05	20.99
490.0	0.19	20.89	27.30	24.02	24.09	20.97
500.0	0.19	20.87	27.19	24.06	24.14	20.94
520.0	0.19	20.82	26.99	24.10	24.20	20.87
540.0	0.20	20.77	26.91	24.12	24.23	20.80
560.0	0.20	20.72	26.86	24.11	24.24	20.73
580.0	0.20	20.67	26.89	24.10	24.23	20.67
600.0	0.21	20.63	26.88	24.09	24.19	20.61
620.0	0.21	20.58	26.81	24.03	24.17	20.51
640.0	0.21	20.53	26.75	23.94	24.11	20.38
660.0	0.22	20.48	26.72	23.86	24.03	20.25
680.0	0.22	20.43	26.61	23.79	23.95	20.12
700.0	0.22	20.38	26.45	23.71	23.87	20.01
720.0	0.23	20.33	26.33	23.61	23.79	19.89
740.0	0.23	20.28	26.15	23.47	23.67	19.75
760.0	0.24	20.23	25.91	23.35	23.52	19.59
780.0	0.24	20.16	25.71	23.22	23.36	19.42
800.0	0.25	20.10	25.41	23.09	23.23	19.26
850.0	0.26	19.95	24.85	22.67	22.87	18.92
900.0	0.27	19.81	24.46	22.21	22.40	18.51
950.0	0.29	19.67	23.94	21.81	21.94	18.11
1000.0	0.30	19.52	23.40	21.25	21.43	17.82
1050.0	0.32	19.38	22.79	20.75	20.89	17.39
1100.0	0.33	19.24	22.16	20.20	20.31	17.07
1150.0	0.35	19.09	21.46	19.63	19.72	16.72
1200.0	0.38	18.95	20.73	19.09	19.15	16.29



P.O. Box 350166, Brooklyn, New York 11235-0003 • (718) 934-4500 • Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site  
The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: [www.minicircuits.com](http://www.minicircuits.com)






IF/RF MICROWAVE COMPONENTS

REV. OR  
ADC-20-13+  
1/31/2013  
Page 1 of 1

# Directional Coupler

## Typical Performance Curves

ADC-20-13+



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 • Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site  
The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: [www.minicircuits.com](http://www.minicircuits.com)



IF/RF MICROWAVE COMPONENTS



REV. OR  
ADC-20-13+  
1/31/2013  
Page 1 of 1

# Case Style


# CD

CD541  
CD542  
CD636  
CD637

## Outline Dimensions



## PCB Land Pattern



Suggested Layout,  
Tolerance to be within  $\pm .002$

CASE#	A	B	C	D	E	F	G	H	J	K	L	WT, GRAM
CD541					.082 (2.08)							.15
CD542	.272 (6.91)	.310 (7.87)	.220 (5.58)	.100 (2.54)	.112 (2.84)	.055 (1.40)	.100 (2.54)	.030 (0.76)	.026 (0.66)	.065 (1.65)	.300 (7.62)	.20
CD636					.162 (4.11)							.25
CD637					.206 (5.23)							.40

Dimensions are in inches (mm). Tolerances: 2 Pl.  $\pm .01$ ; 3 Pl.  $\pm .005$

### Notes:

- Case material: Plastic.
- Termination finish:
  - For RoHS Case Styles: Tin plate over Nickel plate. All models, (+) suffix.
  - For RoHS-5 Case Styles: Tin-Lead plate. All models, no (+) suffix.

**Mini-Circuits**

INTERNET <http://www.minicircuits.com>

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010

Mini-Circuits ISO 9001 & ISO 14001 Certified

# Tape & Reel Packaging TR-F34



Tape Width, mm	Device Cavity Pitch, mm	Reel Size, inches	Devices per Reel see note	
16	12	7	Small quantity standard (see note)	20
				50
				100
				200
		13	Standard	500
				1000

Note: Availability of small reel quantity varies by model.  
Refer to pricing and availability on individual model dashboard.

Mini-Circuits carrier tape materials provide protection from ESD (Electro-Static Discharge) during handling and transportation. Tapes are static dissipative and comply with industry standards EIA-481/EIA-541.

Go to: [www.minicircuits.com/pages/pdfs/tape.pdf](http://www.minicircuits.com/pages/pdfs/tape.pdf)




INTERNET <http://www.minicircuits.com>

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010

Mini-Circuits ISO 9001 & ISO 14001 Certified


THIRD ANGLE PROJECTION



REVISIONS

REV	ECN No.	DESCRIPTION	DATE	DR	AUTH
OR	M82272	NEW RELEASE	08/05/02	MMG	DJ
A	M102713	ADDED NOTE 2 & "...WITH SMOBC"	01/17/06	MMG	IL

SUGGESTED MOUNTING CONFIGURATION  
FOR CD542 CASE STYLE "kd" PIN CONNECTION



RESISTOR R1: 49.9 Ohm, 0805 SIZE.

- NOTES: 1. TRACE WIDTH IS SHOWN FOR ROGERS R04350B WITH DIELECTRIC THICKNESS .030" ± .002"; COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.  
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.



DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)



DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

UNLESS OTHERWISE SPECIFIED	INITIALS	DATE
DIMENSIONS ARE IN INCHES	DRAWN MMG	07/23/02
TOLERANCES ON:	CHECKED IC	08/01/02
2 PL DECIMALS ±	APPROVED DJ	08/05/02
3 PL DECIMALS ± .005		
ANGLES ±		
FRACTIONS ±		



Mini-Circuits®


13 Neptune Avenue  
Brooklyn NY 11235

PL, kd, CD542, ADC, TB-05


Mini-Circuits®
THIS DOCUMENT AND ITS CONTENTS ARE THE PROPERTY OF MINI-CIRCUITS. EXCEPT FOR USE EXPRESSLY GRANTED, IN WRITING, TO ITS VENDORS, VENDEE AND THE UNITED STATES GOVERNMENT, MINI-CIRCUITS RESERVES ALL PROPRIETARY DESIGN, USE, MANUFACTURING AND REPRODUCTION RIGHTS THERETO. THESE CONTENTS SHALL NOT BE USED, DUPLICATED OR DISCLOSED TO ANY OUTSIDE PARTY, IN WHOLE OR IN PART, WITHOUT WRITTEN PERMISSION OF MINI-CIRCUITS.
ASHEETA1.DWG REV:A DATE:01/12/95

SIZE	CODE IDENT	DRAWING NO:	REV:
A	15542	98-PL-095	A
FILE:	98PL095	SCALE:	8:1
		SHEET:	1 OF 1

# Evaluation Board and Circuit




TB-05



Schematic Diagram

## Notes:

1. SMA Female connectors.
2. PCB Material: Rogers R04350 or equivalent, Dielectric Constant=3.5, Thickness=.030 inch.

 Mini-Circuits®

All Mini-Circuits products are manufactured under exacting quality assurance and control standards, and are capable of meeting published specifications after being subjected to any or all of the following physical and environmental test.

Specification	Test/Inspection Condition	Reference/Spec
Operating Temperature	-40° to 85°C Ambient Environment	Individual Model Data Sheet
Storage Temperature	-55° to 100° C Ambient Environment	Individual Model Data Sheet
Humidity	90 to 95% RH, 240 hours, 50°C	MIL-STD-202, Method 103, Condition A, Except 50°C and end-point electrical test done within 12 hours
Thermal Shock	-55° to 100°C, 100 cycles	MIL-STD-202, Method 107, Condition A-3, except +100°C
Solder Reflow Heat	Sn-Pb Eutetic Process: 225°C peak Pb-Free Process 245° - 250°C peak	J-STD-020, Table 4-1, 4-2 and 5-2, Figure 5-1
Solderability	10X Magnification	J-STD-002, 95% Coverage
Vibration (High Frequency)	20g peak, 10-2000 Hz, 12 times in each of three perpendicular directions (total 36)	MIL-STD-202, Method 204, Condition D
Mechanical Shock	50g, 11 ms, 1/2-sine, 18 shocks: 3 each direction, each of 3 axes	MIL-STD-202, Method 213, Condition A
Marking Resistance to Solvents	Isopropyl alcohol + mineral spirits at 25°C; terpene defluxer at 25°C; distilled water + proylene glycol monomethyl ether + monoethanolamine at 63°C to 70°C	MIL-STD-202, Method 215