

Engineering Development Model

Power Splitter/Combiner
2 Way-0°

ADP-ED9774

Important Note

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.



Please click "Back", and then click "Contact Us" for Applications support.

CASE STYLE : CD636

ELECTRICAL SPECIFICATIONS 75Ω @ +25°C					
Parameter		Min.	Typ.	Max.	Units
Frequency		0.55		1400	MHz
Isolation	0.55 - 5.5 MHz		15		dB
	5.5 - 700 MHz		31		dB
	700 - 1400 MHz		30		dB
Total Loss Above 3.0 dB	0.55 - 5.5 MHz		0.28		dB
	5.5 - 700 MHz		0.29		dB
	700 - 1400 MHz		0.83		dB
Phase Unbalance	0.55 - 5.5 MHz		0.013		deg.
	5.5 - 700 MHz		0.436		deg.
	700 - 1400 MHz		1.628		deg.
Amplitude Unbalance	0.55 - 5.5 MHz		0.003		dB
	5.5 - 700 MHz		0.006		dB
	700 - 1400 MHz		0.135		dB
VSWR	SUM Port		1.11		(:1)
	OUT Ports		1.19		(:1)

Note: Denotes 75 ohm model.

MAXIMUM RATINGS	
Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C

PIN CONNECTIONS	
SUM PORT	1
PORT 1	3
PORT 2	4
GND EXT	2, 5, 6

Functional Diagram



Notes
A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

2 Way-0° Power Splitter/Combiner

ADP-ED9774

Typical Performance Data

FREQ. (MHz)	TOTAL LOSS ¹ (dB)		AMP. UNBAL. (dB)	ISOLATION (dB)	PHASE UNBAL. (deg.)	FREQ. (MHz)	VSWR (:1)		
	S-1	S-2					S	1	2
0.6	3.30	3.30	0.00	11.76	0.01	0.6	1.20	1.95	1.95
0.8	3.30	3.30	0.00	12.96	0.00	0.8	1.16	1.76	1.76
1.0	3.30	3.30	0.01	13.96	0.01	1.0	1.14	1.65	1.65
5.0	3.21	3.21	0.00	22.12	0.03	5.0	1.07	1.21	1.21
10.8	3.20	3.20	0.00	26.18	0.00	10.8	1.06	1.12	1.12
16.7	3.19	3.20	0.01	27.77	0.02	16.7	1.06	1.10	1.10
22.5	3.21	3.21	0.00	28.44	0.05	22.5	1.06	1.09	1.09
28.3	3.21	3.21	0.00	28.68	0.02	28.3	1.06	1.09	1.09
34.2	3.21	3.21	0.00	28.81	0.08	34.2	1.06	1.09	1.09
40.0	3.22	3.22	0.01	28.84	0.09	40.0	1.06	1.09	1.09
109.2	3.25	3.25	0.00	29.19	0.24	109.2	1.06	1.09	1.08
178.3	3.28	3.28	0.00	29.68	0.30	178.3	1.06	1.09	1.08
247.5	3.30	3.29	0.01	30.28	0.46	247.5	1.07	1.09	1.07
316.7	3.32	3.32	0.00	31.21	0.56	316.7	1.08	1.10	1.07
385.8	3.34	3.33	0.00	32.25	0.74	385.8	1.09	1.11	1.07
455.0	3.37	3.36	0.01	33.49	0.84	455.0	1.10	1.11	1.07
524.2	3.40	3.38	0.02	34.84	0.91	524.2	1.11	1.12	1.07
593.3	3.43	3.42	0.01	35.82	1.05	593.3	1.11	1.12	1.08
662.5	3.46	3.44	0.02	36.48	1.18	662.5	1.12	1.13	1.09
731.7	3.51	3.49	0.02	36.37	1.20	731.7	1.12	1.13	1.09
800.8	3.56	3.52	0.04	35.77	1.28	800.8	1.12	1.13	1.10
870.0	3.62	3.55	0.06	35.00	1.39	870.0	1.12	1.13	1.12
907.9	3.64	3.59	0.06	34.55	1.45	907.9	1.12	1.13	1.13
945.7	3.66	3.59	0.07	34.08	1.44	945.7	1.12	1.13	1.13
983.6	3.71	3.64	0.08	33.58	1.49	983.6	1.12	1.14	1.15
1021.4	3.74	3.65	0.09	33.06	1.49	1021.4	1.12	1.14	1.16
1059.3	3.79	3.69	0.10	32.43	1.54	1059.3	1.12	1.14	1.17
1097.1	3.84	3.72	0.12	31.71	1.61	1097.1	1.12	1.14	1.18
1135.0	3.88	3.75	0.13	30.85	1.53	1135.0	1.12	1.15	1.19
1172.9	3.94	3.79	0.15	29.79	1.70	1172.9	1.13	1.15	1.21
1210.7	4.01	3.83	0.18	28.55	1.71	1210.7	1.13	1.16	1.22
1248.6	4.07	3.87	0.20	27.19	1.76	1248.6	1.14	1.16	1.24
1286.4	4.17	3.96	0.21	25.77	1.91	1286.4	1.16	1.17	1.26
1324.3	4.24	4.00	0.24	24.27	1.85	1324.3	1.17	1.18	1.28
1362.1	4.36	4.09	0.27	22.75	2.17	1362.1	1.20	1.19	1.30
1400.0	4.49	4.21	0.28	21.29	2.16	1400.0	1.24	1.20	1.32






¹ Total Loss = Insertion Loss + 3dB Splitter Loss

REV. X2
ADP-ED9774
100707
Page 1 of 1

2 Way-0° Power Splitter/Combiner

ADP-ED9774

Typical Performance Curves



REV. X2
ADP-ED9774
100707
Page 1 of 1



Mini-Circuits®

RF/MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED • RoHS compliant
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

The Design Engineers Search Engine finds the model you need, instantly • For detailed performance specs & shopping online see



CD541
CD542
CD636
CD637

Outline Dimensions



PCB Land Pattern



Suggested Layout,
Tolerance to be within $\pm .002$

CASE#	A	B	C	D	E	F	G	H	J	K	L	WT, GRAM
CD541					.082 (2.08)							.15
CD542	.272 (6.91)	.310 (7.87)	.220 (5.58)	.100 (2.54)	.112 (2.84)	.055 (1.40)	.100 (2.54)	.030 (0.76)	.026 (0.66)	.065 (1.65)	.300 (7.62)	.20
CD636					.162 (4.11)							.25
CD637					.206 (5.23)							.40

Dimensions are in inches (mm). Tolerances: 2 Pl. $\pm .01$; 3 Pl. $\pm .005$

Notes:

- Case material: Plastic.
- Termination finish:
For RoHS Case Styles: Tin plate over Nickel plate. All models, (+) suffix.
For RoHS-5 Case Styles: Tin-Lead plate. All models, no (+) suffix.



INTERNET <http://www.minicircuits.com>

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010

Mini-Circuits ISO 9001 & ISO 14001 Certified

Tape & Reel Packaging TR-F34



Tape Width, mm	Device Cavity Pitch, mm	Reel Size, inches	Devices per Reel see note	
16	12	7	Small quantity standard (see note)	20
				50
				100
				200
		13	Standard	500
				1000

Note: Availability of small reel quantity varies by model.
Refer to pricing and availability on individual model dashboard.

Mini-Circuits carrier tape materials provide protection from ESD (Electro-Static Discharge) during handling and transportation. Tapes are static dissipative and comply with industry standards EIA-481/EIA-541.

Go to: www.minicircuits.com/pages/pdfs/tape.pdf



INTERNET <http://www.minicircuits.com>

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010

Mini-Circuits ISO 9001 & ISO 14001 Certified



All Mini-Circuits products are manufactured under exacting quality assurance and control standards, and are capable of meeting published specifications after being subjected to any or all of the following physical and environmental test.

Specification	Test/Inspection Condition	Reference/Spec
Operating Temperature	-40° to 85°C Ambient Environment	Individual Model Data Sheet
Storage Temperature	-55° to 100° C Ambient Environment	Individual Model Data Sheet
Humidity	90 to 95% RH, 240 hours, 50°C	MIL-STD-202, Method 103, Condition A, Except 50°C and end-point electrical test done within 12 hours
Thermal Shock	-55° to 100°C, 100 cycles	MIL-STD-202, Method 107, Condition A-3, except +100°C
Solder Reflow Heat	Sn-Pb Eutetic Process: 225°C peak Pb-Free Process 245° - 250°C peak	J-STD-020, Table 4-1, 4-2 and 5-2, Figure 5-1
Solderability	10X Magnification	J-STD-002, 95% Coverage
Vibration (High Frequency)	20g peak, 10-2000 Hz, 12 times in each of three perpendicular directions (total 36)	MIL-STD-202, Method 204, Condition D
Mechanical Shock	50g, 11 ms, 1/2-sine, 18 shocks: 3 each direction, each of 3 axes	MIL-STD-202, Method 213, Condition A
Marking Resistance to Solvents	Isopropyl alcohol + mineral spirits at 25°C; terpene defluxer at 25°C; distilled water + proylene glycol monomethyl ether + monoethanolamine at 63°C to 70°C	MIL-STD-202, Method 215