

Engineering Development Model

Power Splitter/Combiner

ADPQ-ED10656

2 Way-90°

Important Note

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.

Please click "Back", and then click "Contact Us" for Applications support.




CASE STYLE : 99-01-775

ELECTRICAL SPECIFICATIONS 50Ω @ +25°C				
Parameter		Min.	Typ.	Max. Units
Frequency		40		100 MHz
Isolation	40 - 100 MHz		21	
Total Loss				
Average of Coupled Outputs	40 - 100 MHz		0.50	
above 3.0 dB				
Phase Unbalance	40 - 100 MHz		2.054	
Amplitude Unbalance	40 - 100 MHz		1.136	
VSWR	SUM Port		1.20	(:1)
	OUT Ports		1.20	(:1)

MAXIMUM RATINGS	
Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C

PIN CONNECTIONS	
SUM PORT	1
PORT 1	6
PORT 2	4
GND EXT	2, 5
50Ω TERMINATION	3

Functional Diagram



2 Way-90° Power Splitter/Combiner

ADPQ-ED10656

Typical Performance Data

FREQ. (MHz)	TOTAL LOSS ¹			AMP. UNBAL. (dB)	ISOLATION (dB) 1-2	PHASE UNBAL. (deg.)	FREQ. (MHz)	VSWR		
	S-1	S-2	AVG.					S	1	2
30.0	5.71	1.46	3.59	4.25	31.80	90.20	30.0	1.10	1.02	1.12
32.0	5.35	1.60	3.48	3.75	31.49	90.28	32.0	1.10	1.03	1.12
34.0	5.03	1.76	3.40	3.28	31.22	90.26	34.0	1.11	1.03	1.12
36.0	4.75	1.90	3.33	2.85	30.93	90.32	36.0	1.11	1.03	1.12
38.0	4.49	2.04	3.27	2.44	30.66	90.32	38.0	1.11	1.03	1.12
40.0	4.26	2.20	3.23	2.06	30.41	90.33	40.0	1.11	1.03	1.12
42.0	4.05	2.34	3.20	1.71	30.15	90.39	42.0	1.11	1.04	1.12
44.0	3.86	2.49	3.18	1.38	29.86	90.51	44.0	1.12	1.04	1.12
46.0	3.70	2.63	3.17	1.07	29.57	90.47	46.0	1.12	1.04	1.12
48.0	3.55	2.76	3.16	0.78	29.25	90.51	48.0	1.12	1.04	1.13
50.0	3.41	2.89	3.15	0.52	28.92	90.62	50.0	1.13	1.04	1.13
55.0	3.11	3.18	3.15	0.07	27.96	90.65	55.0	1.14	1.05	1.14
60.0	2.88	3.41	3.15	0.53	26.88	90.84	60.0	1.16	1.06	1.15
65.0	2.72	3.63	3.18	0.91	25.67	91.10	65.0	1.18	1.06	1.17
70.0	2.61	3.81	3.21	1.20	24.38	91.31	70.0	1.20	1.08	1.19
75.0	2.58	3.96	3.27	1.38	23.08	91.73	75.0	1.23	1.09	1.21
80.0	2.59	4.07	3.33	1.49	21.82	92.08	80.0	1.25	1.12	1.24
85.0	2.61	4.12	3.37	1.51	20.61	92.63	85.0	1.26	1.14	1.27
90.0	2.67	4.08	3.38	1.42	19.36	93.27	90.0	1.29	1.18	1.31
92.0	2.71	4.05	3.38	1.34	18.84	93.60	92.0	1.31	1.20	1.33
94.0	2.76	4.02	3.39	1.26	18.30	94.04	94.0	1.34	1.21	1.35
96.0	2.84	3.97	3.41	1.13	17.78	94.41	96.0	1.37	1.23	1.37
98.0	2.93	3.92	3.43	0.99	17.25	94.95	98.0	1.40	1.26	1.39
100.0	3.05	3.88	3.47	0.83	16.72	95.58	100.0	1.44	1.28	1.42
102.0	3.19	3.84	3.52	0.66	16.20	96.39	102.0	1.48	1.30	1.45
104.0	3.36	3.82	3.59	0.46	15.68	97.22	104.0	1.52	1.33	1.49
106.0	3.55	3.79	3.67	0.24	15.15	98.29	106.0	1.57	1.36	1.52
108.0	3.79	3.79	3.79	0.00	14.60	99.46	108.0	1.62	1.39	1.57
110.0	4.04	3.78	3.91	0.27	14.04	100.71	110.0	1.67	1.43	1.62

¹ Total Loss = Insertion Loss+ 3dB Splitter Loss

REV. X2

ADPQ-ED10656

100705

Page 1 of 1



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED • RoHS compliant
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661




The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



2 Way-90° Power Splitter/Combiner

ADPQ-ED10656

Typical Performance Curves



REV. X2
ADPQ-ED10656
100705
Page 1 of 1




Mini-Circuits®

IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED • RoHS compliant
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see




THIRD ANGLE PROJECTION



REVISIONS

REV	ECN No.	DESCRIPTION	DATE	DR	AUTH
OR	M82476	NEW RELEASE	11/26/02	MMG	HY
A	M102713	ADDED "ay", "lg", "ls" PIN CONNECTIONS, CD636/637 CASE STYLES & "...WITH SMOBC"	01/17/06	MMG	IL

**SUGGESTED MOUNTING CONFIGURATION
FOR BH292, CD636/CD637 CASE STYLES,
"ay", "lg", "ls" PIN CONNECTIONS**



- NOTES: 1. TRACE WIDTH IS SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS .030" $\pm$.002"; COPPER: 1/2 OZ. EACH SIDE.
FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.



DENOTES PCB COPPER LAYOUT WITH SMOBC
(SOLDER MASK OVER BARE COPPER)



DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

UNLESS OTHERWISE SPECIFIED

INITIALS

DATE

DIMENSIONS ARE IN INCHES

TOLERANCES ON:

2 PL DECIMALS $\pm$ 3 PL DECIMALS $\pm$.005ANGLES $\pm$ FRACTIONS $\pm$

DRAWN

MMG

10/30/02

CHECKED

AV

11/26/02

APPROVED

HY

11/26/02



Mini-Circuits®

13 Neptune Avenue
Brooklyn NY 11235

PL, ay/jg/lb, BH292, CD636/637,
ADPQ/AMT/JPS, TB-211

SIZE
A

CODE IDENT
15542

DRAWING NO:
98-PL-097

REV:
A

FILE: 98PL097

SCALE: 8:1

SHEET: 1 OF 1



Mini-Circuits®

THIS DOCUMENT AND ITS CONTENTS ARE THE PROPERTY OF MINI-CIRCUITS. EXCEPT FOR USE EXPRESSLY GRANTED, IN WRITING, TO ITS VENDORS, VENDEE AND THE UNITED STATES GOVERNMENT, MINI-CIRCUITS RESERVES ALL PROPRIETARY DESIGN, USE, MANUFACTURING AND REPRODUCTION RIGHTS THERETO. THESE CONTENTS SHALL NOT BE USED, DUPLICATED OR DISCLOSED TO ANY OUTSIDE PARTY, IN WHOLE OR IN PART, WITHOUT WRITTEN PERMISSION OF MINI-CIRCUITS.

ASHEETA1.DWG REV:A DATE:01/12/95

Evaluation Board and Circuit


For Pin Connections refer to Data Sheet of the DUT



Schematic Diagram

Notes:

1. SMA Female connectors.
2. PCB Material: Rogers R04350 or equivalent,
Dielectric Constant=3.5, Thickness=.030 inch.

 Mini-Circuits®



All Mini-Circuits products are manufactured under exacting quality assurance and control standards, and are capable of meeting published specifications after being subjected to any or all of the following physical and environmental test.

Specification	Test/Inspection Condition	Reference/Spec
Operating Temperature	-40° to 85°C Ambient Environment	Individual Model Data Sheet
Storage Temperature	-55° to 100° C Ambient Environment	Individual Model Data Sheet
Humidity	90 to 95% RH, 240 hours, 50°C	MIL-STD-202, Method 103, Condition A, Except 50°C and end-point electrical test done within 12 hours
Thermal Shock	-55° to 100°C, 100 cycles	MIL-STD-202, Method 107, Condition A-3, except +100°C
Solder Reflow Heat	Sn-Pb Eutetic Process: 225°C peak Pb-Free Process 245° - 250°C peak	J-STD-020, Table 4-1, 4-2 and 5-2, Figure 5-1
Solderability	10X Magnification	J-STD-002, 95% Coverage
Vibration (High Frequency)	20g peak, 10-2000 Hz, 12 times in each of three perpendicular directions (total 36)	MIL-STD-202, Method 204, Condition D
Mechanical Shock	50g, 11 ms, 1/2-sine, 18 shocks: 3 each direction, each of 3 axes	MIL-STD-202, Method 213, Condition A
Marking Resistance to Solvents	Isopropyl alcohol + mineral spirits at 25°C; terpene defluxer at 25°C; distilled water + proylene glycol monomethyl ether + monoethanolamine at 63°C to 70°C	MIL-STD-202, Method 215