

# Engineering Development Model

## RF Transformer

## ADT4-ED14511/1

Impedance Ratio: 4

### Important Note

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.



Please click "Back", and then click "Contact Us" for Applications support.


CASE STYLE : CD541

ELECTRICAL SPECIFICATIONS 50Ω @ +25°C					
Parameter		Min.	Typ.	Max.	Units
Frequency		0.5		700	MHz
Insertion Loss *	3 dB Bandwidth		0.5-700		MHz
	2 dB Bandwidth		0.9-600		MHz
	1 dB Bandwidth		3-500		MHz
Amplitude Unbalance	Over 3 dB Bandwidth		0.5		dB
	Over 1 dB Bandwidth		0.1		dB
Phase Unbalance	Over 3 dB Bandwidth		5.0		Deg.
	Over 1 dB Bandwidth		1.0		Deg.

Note: \* Insertion Loss is referenced to mid-band loss, 0.9 dB typ.

MAXIMUM RATINGS	
Operating Temperature	-20°C to 85°C
Storage Temperature	-55°C to 100°C
RF Power	0.25W
DC Current	30 mA

PIN CONNECTIONS	
PRIMARY DOT	3
PRIMARY	1
SECONDARY DOT	4
SECONDARY	6
SECONDARY CT	5
ISOLATE	2



# RF Transformer

# ADT4-ED14511/1


## Typical Performance Data

FREQUENCY MHz	AVERAGE INSERTION LOSS (dB)	INPUT RETURN LOSS (dB)	AMPLITUDE UNBALANCE (dB)	PHASE UNBALANCE (deg.)
0.5	3.00	7.27	0.01	0.12
0.7	2.45	8.81	0.00	0.08
0.9	2.14	9.98	0.00	0.05
1.0	2.03	10.47	0.00	0.04
3.0	1.30	15.41	0.01	0.02
5.0	1.13	17.33	0.01	0.02
7.0	1.05	18.41	0.01	0.03
9.0	1.02	19.04	0.01	0.03
10.0	1.01	19.28	0.01	0.04
20.0	0.97	20.20	0.01	0.07
30.0	0.97	20.37	0.01	0.09
40.0	0.97	20.43	0.01	0.12
50.0	0.97	20.46	0.01	0.15
60.0	0.97	20.46	0.00	0.18
75.0	0.98	20.41	0.01	0.22
90.0	0.98	20.32	0.01	0.26
100.0	0.98	20.21	0.01	0.29
125.0	0.99	19.87	0.03	0.38
150.0	1.00	19.54	0.05	0.41
200.0	1.03	18.57	0.07	0.60
250.0	1.06	17.59	0.12	0.79
275.0	1.08	17.11	0.14	0.89
300.0	1.09	16.68	0.17	1.00
325.0	1.11	16.22	0.20	1.13
375.0	1.15	15.33	0.27	1.43
400.0	1.17	14.93	0.30	1.60
425.0	1.19	14.51	0.34	1.82
475.0	1.25	13.69	0.44	2.27
500.0	1.28	13.32	0.49	2.52
525.0	1.31	12.96	0.53	2.84
550.0	1.35	12.58	0.58	3.20
600.0	1.43	11.88	0.68	4.10
650.0	1.52	11.22	0.81	5.28
700.0	1.63	10.57	0.93	6.79




## Typical Performance Data


### Average Insertion Loss




### Input Return Loss



### Amplitude Unbalance



### Phase Unbalance



# Case Style

# CD

CD541  
CD542  
CD636  
CD637

## Outline Dimensions



## PCB Land Pattern



Suggested Layout,  
Tolerance to be within  $\pm .002$

CASE#	A	B	C	D	E	F	G	H	J	K	L	WT, GRAM
CD541					.082 (2.08)							.15
CD542	.272 (6.91)	.310 (7.87)	.220 (5.58)	.100 (2.54)	.112 (2.84)	.055 (1.40)	.100 (2.54)	.030 (0.76)	.026 (0.66)	.065 (1.65)	.300 (7.62)	.20
CD636					.162 (4.11)							.25
CD637					.206 (5.23)							.40

Dimensions are in inches (mm). Tolerances: 2 Pl.  $\pm .01$ ; 3 Pl.  $\pm .005$

### Notes:

- Case material: Plastic.
- Termination finish:
  - For RoHS Case Styles: Tin plate over Nickel plate. All models, (+) suffix.
  - For RoHS-5 Case Styles: Tin-Lead plate. All models, no (+) suffix.

**Mini-Circuits®**

INTERNET <http://www.minicircuits.com>

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010

Mini-Circuits ISO 9001 & ISO 14001 Certified

# Tape & Reel Packaging TR-F34



Tape Width, mm	Device Cavity Pitch, mm	Reel Size, inches	Devices per Reel see note	
16	12	7	Small quantity standard (see note)	20
				50
				100
				200
		13	Standard	500
				1000

Note: Availability of small reel quantity varies by model.  
Refer to pricing and availability on individual model dashboard.

Mini-Circuits carrier tape materials provide protection from ESD (Electro-Static Discharge) during handling and transportation. Tapes are static dissipative and comply with industry standards EIA-481/EIA-541.

Go to: [www.minicircuits.com/pages/pdfs/tape.pdf](http://www.minicircuits.com/pages/pdfs/tape.pdf)



INTERNET <http://www.minicircuits.com>

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010

Mini-Circuits ISO 9001 & ISO 14001 Certified

All Mini-Circuits products are manufactured under exacting quality assurance and control standards, and are capable of meeting published specifications after being subjected to any or all of the following physical and environmental test.

Specification	Test/Inspection Condition	Reference/Spec
Operating Temperature	-20° to 85°C Ambient Environment	Individual Model Data Sheet
Storage Temperature	-55° to 100° C Ambient Environment	Individual Model Data Sheet
Humidity	90 to 95% RH, 240 hours, 50°C	MIL-STD-202, Method 103, Condition A, Except 50°C and end-point electrical test done within 12 hours
Thermal Shock	-55° to 100°C, 100 cycles	MIL-STD-202, Method 107, Condition A-3, except +100°C
Solder Reflow Heat	Sn-Pb Eutetic Process: 225°C peak Pb-Free Process 245° - 250°C peak	J-STD-020, Table 4-1, 4-2 and 5-2, Figure 5-1
Solderability	10X Magnification	J-STD-002, 95% Coverage
Vibration (High Frequency)	20g peak, 10-2000 Hz, 12 times in each of three perpendicular directions (total 36)	MIL-STD-202, Method 204, Condition D
Mechanical Shock	50g, 11 ms, 1/2-sine, 18 shocks: 3 each direction, each of 3 axes	MIL-STD-202, Method 213, Condition A
Marking Resistance to Solvents	Isopropyl alcohol + mineral spirits at 25°C; terpene defluxer at 25°C; distilled water + proylene glycol monomethyl ether + monoethanolamine at 63°C to 70°C	MIL-STD-202, Method 215