

Precision Fixed Attenuator

50Ω 2W 3dB DC to 26 GHz

BW-S3-2W263+

Maximum Ratings


Operating Temperature -55°C to 100°C

Storage Temperature -55°C to 100°C**

**With mated connectors. Unmated, 85°C max.

Permanent damage may occur if any of these limits are exceeded.


Outline Drawing



Outline Dimensions (inch/mm)

B	D	E	F	wt
.36	.85	.312	.312	grams
9.14	21.59	7.92	7.92	4.3

Electrical Schematic



Features

- DC to 26 GHz
- precise attenuation
- excellent VSWR, 1.08 typ
- stainless steel SMA male and female connectors

Applications

- matching
- instrumentation
- test set-ups



Generic photo used for illustration purposes only

CASE STYLE: FF659

Connectors Model
SMA-Fem SMA-Male BW-S3-2W263+

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Electrical Specifications at 25°C



Parameter	Condition (GHz)	Min.	Typ.	Max.	Unit
Frequency Range		DC	—	26	GHz
Attenuation¹	DC - 26	—	3	—	
	DC - 12	2.7	—	3.3	dB
	12 - 18	2.7	—	3.3	
	18 - 26	2.7	—	3.7	
VSWR	DC - 12	—	1.07	1.20	
	12 - 18	—	1.08	1.25	:1
	18 - 26	—	1.17	1.40	
Input Power²	DC - 26	—	—	2	W

1. At 25°C, accuracy includes frequency and power variations. Temperature coefficient for attenuation: .0004 dB/dB/°C typ.

2. Max. power at 25°C ambient, derate linearly to 0.5W at 100°. Peak power 125W max. 5μsec. pulse width, 100Hz PRF

Typical Performance Data

Frequency (GHz)	Attenuation (dB)	VSWR (:1)
0.01	2.79	1.00
1.0	2.82	1.01
4.0	2.84	1.03
8.0	2.88	1.05
10.0	2.90	1.03
12.0	2.92	1.05
14.0	2.95	1.06
16.0	2.99	1.02
18.0	3.03	1.05
20.0	3.09	1.11
26.0	3.28	1.07



Notes

A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.

C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



Fixed Attenuator


BW-S3-2W263+

Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.01	2.79	1.00
0.05	2.79	1.00
0.10	2.79	1.01
0.50	2.81	1.01
1.00	2.82	1.01
2.00	2.83	1.01
3.00	2.83	1.02
4.00	2.84	1.03
5.00	2.85	1.03
6.00	2.86	1.04
7.00	2.87	1.06
8.00	2.88	1.05
9.00	2.89	1.04
10.0	2.90	1.03
11.0	2.91	1.03
12.0	2.92	1.05
13.0	2.94	1.07
14.0	2.95	1.06
15.0	2.98	1.03
16.0	2.99	1.02
17.0	3.00	1.00
18.0	3.03	1.05
19.0	3.06	1.09
20.0	3.09	1.11
20.2	3.09	1.11
20.4	3.10	1.11
20.6	3.10	1.11
20.8	3.10	1.11
21.0	3.10	1.11
21.2	3.11	1.10
21.4	3.11	1.10
21.6	3.12	1.11
21.8	3.13	1.11
22.0	3.13	1.11
22.2	3.14	1.11
22.4	3.14	1.11
22.6	3.15	1.11
22.8	3.16	1.11
23.0	3.17	1.11
23.2	3.17	1.10
23.4	3.18	1.10
23.6	3.18	1.09
23.8	3.18	1.09
24.0	3.18	1.08
24.2	3.19	1.07
24.4	3.19	1.07
24.6	3.19	1.06
24.8	3.20	1.05
25.0	3.21	1.05
25.2	3.22	1.05
25.4	3.22	1.05
25.6	3.23	1.06
25.8	3.24	1.06
26.0	3.28	1.07




Typical Performance Curves



Outline Dimensions

FF658

FF659



CASE #.	A	B	C	D	E	F	WT GRAMS
FF658	--	.36 (9.14)	--	.85 (21.59)	.312 (7.92)	.312 (7.92)	4.3
FF659	--		--	.99 (25.15)			5.1

Dimensions are in inches (mm). Tolerances: 2Pl. $\pm .03$; 3Pl. $\pm .015$

Note:

- Case material: Stainless steel.



All Mini-Circuits products are manufactured under exacting quality assurance and control standards, and are capable of meeting published specifications after being subjected to any or all of the following physical and environmental test.

Specification	Test/Inspection Condition	Reference/Spec
Operating Temperature	-55° to 100°C Ambient Environment	Individual Model Data Sheet
Storage Temperature	-55° to 100° C Ambient Environment	Individual Model Data Sheet
Barometric Pressure	100,000 Feet	MIL-STD-202, Method 105, Condition D
Humidity	90% RH, 65°C Units may require bake-out after humidity to restore full performance.	MIL-STD-202, Method 103
Thermal Shock	-65° to 125°C, 5 cycles	MIL-STD-202, Method 107, Condition B
Vibration (High Frequency)	20g peak, 10-2000 Hz, 12 times in each of three perpendicular directions (total 36)	MIL-STD-202, Method 204, Condition D
Mechanical Shock	100g, 6ms sawtooth, 3 shocks each direction 3 axes (total 18)	MIL-STD-202, Method 213, Condition I