

Monolithic Amplifier MAR-4SM+

500 DC to 1 GHz

FEATURES

- · Wideband, DC to 1 GHz
- Exact Footprint Substitute for Avago's MSA-0486
- Internally Matched to 50Ω
- Unconditionally Stable
- Protected by US Patent, 6,943,629



Generic photo used for illustration purposes only

CASE STYLE: WW107

+RoHS Compliant The +Suffix identifies RoHS Compliance our website for methodologies and qualifi


APPLICATIONS


- Cellular
- Instrumentation
- VHF/UHF Receivers/Transmitters

PRODUCT OVERVIEW

MAR-4SM+ (RoHS compliant) is a wideband amplifier offering high dynamic range. It has repeatable performance from lot to lot. It is enclosed in a Micro-X package. MAR-4SM+ uses Darlington configuration and is fabricated using InGaP HBT technology. Expected MTTF is 900 years at +85°C case temperature.

SIMPLIFIED SCHEMATIC AND PIN DESCRIPTION





Function	Pin Number	Description
RF-IN	1	RF input pin. This pin requires the use of an external DC blocking capacitor chosen for the frequency of operation.
RF-OUT and DC-IN	3	RF output and bias pin. DC voltage is present on this pin; therefore a DC blocking capacitor is necessary for proper operation. An RF choke is needed to feed DC bias without loss of RF signal due to the bias connection, as shown in "Recommended Application Circuit".
GND	2,4	Connections to ground. Use via holes as shown in "Suggested Layout for PCB Design" to reduce ground path inductance for best performance.



Monolithic Amplifier MAR-4SM+

50Ω DC to 1 GHz

ELECTRICAL SPECIFICATIONS AT +25°C AND 50 mA UNLESS NOTED OTHERWISE

Parameter	Conditions (GHz)	Min.	Тур.	Max.	Units
Frequency Range ¹		DC		1	GHz
Gain	0.1 1	7.0 ²	8.3 8.0		dB
Input Return Loss	DC - 1		14		dB
Output Return Loss	DC - 1		10		dB
Output Power @ 1 dB Compression	1		+12.5		dBm
Output IP3	1		+25.5		dBm
Noise Figure	1		6.0		dB
Recommended Device Operating Current			50		mA
Device Operating Voltage			+5.25		V
Device Voltage Variation vs. Temperature at 50 mA			-2.2		mV/°C
Device Voltage Variation vs. Current at +25°C			23.0		mV/mA
Thermal Resistance, Junction-to-Case ³			157		°C/W

^{1.} Guaranteed specification DC-1 GHz. Low frequency cut off determined by external coupling capacitors.

ABSOLUTE MAXIMUM RATINGS

Parameter	Ratings				
Operating Temperature	-40°C to +85°C				
Storage Temperature	-55°C to +100°C				
Operating Current	85 mA				
Power Dissipation	500 mW				
Input Power	+13 dBm				

 $Permanent\ damage\ may\ occur\ if\ any\ of\ these\ limits\ are\ exceeded.\ These\ ratings\ are\ not$ intended for continuous normal operation.


Full temperature range.
 Case is defined as ground leads.



Monolithic Amplifier MAR-4SM+

50Ω DC to 1 GHz


RECOMMENDED APPLICATION CIRCUIT



Test Board includes case, connectors, and components (in bold) soldered to PCB

R BIAS					
Vcc	"1%" Res. Values (Ohms) for Optimum Biasing				
7	34.8				
8	54.9				
9	75				
10	95.3				
11	115				
12	133				
13	154				
14	174				
15	196				

PRODUCT MARKING



Markings in addition to model number designation may appear for internal quality control purposes.



Monolithic Amplifier MAR-4SM+

50Ω DC to 1 GHz

ADDITIONAL DETAILED TECHNICAL INFORMATION IS AVAILABLE ON OUR DASHBOARD. CLICK HERE

	Data Table
Performance Data & Graphs	Swept Graphs
	S-Parameter Data Set (.zip file)
Case Style	WW107 Plastic micro-x package, 0.085 body diameter, Lead Finish: Matte-Tin
Tape & Reel Standard Quantities Available on Reel	F4 7" Reels with 20, 50, 100, 200, 500 or 1K devices
Suggested Layout for PCB Design	PL-253
Evaluation Board	TB-411-4+
Environmental Ratings	ENV08T3

ESD RATING


Human Body Model (HBM): Class 1B (500 V to < 1,000 V) in accordance with ANSI/ESD STM 5.1 - 2001 Machine Model (MM): Class M1 (< 100 V) in accordance with ESD STM 5.2 - 1999

MSL RATING

Moisture Sensitivity: MSL1 in accordance with IPC/JEDECJ-STD-020C

No.	Test Required	Condition	Standard	Quantity
1	Visual Inspection	Low Power Microscope Magnification 40x	MIP-IN-0003 (MCT spec)	45 units
2	Electrical Test	Room Temperature	SCD (MCL spec)	45 units
3	SAM Analysis	Less than 10% growth in term of delamination	J-Std-020C (Jedec Standard)	45 units
4	Moisture Sensitivity Level 1	Bake at 125°C for 24 hours Soak at 85°C/85%RH for 168 hours Reflow 3 cycles at 260°C peak	J-Std-020C (Jedec Standard)	45 units

MSL TEST FLOW CHART




- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuits' applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits' standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the standard terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/terms/viewterm.html




Typical Performance Data


FREQUENCY	GAIN	ISOLATION	RETURN LOSS	RETURN LOSS
INEQUENCT	OAIN	ISOLATION	IN	OUT
(MHz)	(dB)	(dB)	(dB)	(dB)
	50 mA	50 mA	50 mA	50 mA
1	8.45	16.09	38.70	28.85
25	8.45	16.04	38.91	27.67
50	8.41	16.06	39.15	27.93
100	8.39	16.06	36.95	27.14
200	8.34	16.06	32.68	27.20
300	8.31	16.05	29.07	26.14
400	8.25	16.00	27.16	23.91
500	8.19	15.95	25.18	23.51
600	8.12	15.89	23.11	22.95
700	8.04	15.83	22.17	20.48
800	7.94	15.75	20.79	19.93
900	7.85	15.69	19.24	20.30
1000	7.73	15.60	18.77	17.80
1100	7.59	15.53	17.75	17.20
1200	7.50	15.43	16.60	18.04
1300	7.36	15.34	16.41	15.60
1400	7.21	15.29	15.53	15.17
1500	7.09	15.19	14.67	16.06
1600	6.93	15.12	14.64	13.89
1700	6.75	15.08	13.87	13.52
1800	6.65	14.97	13.24	14.45
1900	6.48	14.93	13.28	12.62
2000	6.27	14.91	12.60	12.20
2100	6.18	14.77	12.13	13.32
2200	6.00	14.76	12.25	11.68
2300	5.78	14.77	11.56	11.07
2400	5.71	14.63	11.13	12.58
2500	5.50	14.63	11.34	10.82
2600	5.28	14.65	10.75	10.23
2700	5.24	14.47	10.39	12.19
2800	5.01	14.52	10.62	10.14
2900	4.74	14.63	10.02	9.58
3000	4.74	14.43	9.86	12.08
3100	4.51	14.50	10.12	9.52
3200	4.25	14.55	9.53	9.11
3500	3.70	14.62	9.13	8.78
4000	2.93	14.64	8.98	7.81

Typical Performance Curves









Return Loss Out


Case Style




WW107

Outline Dimensions

PCB Land Pattern





Suggested Layout, Tolerance to be within ±.002

CASE#	A	В	С	D	Е	F	G	Н	J	K	L	M	N	P	Q	WT. GRAMS
WW107	.012 (0.30)	.10 (2.54)	.020 (0.51)	.092 (2.34)	.085 (2.16)	.060 (1.52)	.007 (0.18)	.026 (0.66)	.235 (5.97)	.118 (3.00)	.235 (5.97)	.118 (3.00)	.072 (1.83)	.040 (1.02)	.020 (0.51)	.015

Dimensions are in inches (mm). Tolerances: 2 Pl. ± .03; 3 Pl. ± .015

Notes:

- 1. Case material: Plastic.
- 2. Termination finish:

For RoHS Case Styles: Matte tin Plate.

For RoHS-5 Case Styles: Tin-Lead plate.

- 3. RF input termination (1) identified by one or both of the following at factory option:
 - (a) diagonally cut termination, which may be 45° (ref) in either direction;
 - (b) orientation mark on the case. Model dash number is identified by color dot or alphanumeric code on case. See specification data sheet.



INTERNET http://www.minicircuits.cc


P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500

Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-8

Mini-Circuite ISO 0001 & ISO 14001 Cortified

Tape & Reel Packaging TR-F4

DEVICE ORIENTATION IN T&R



DIRECTION OF FEED

Tape Width, mm	Device Cavity Pitch, mm	Reel Size, inches	Devices p	er Reel
12	8	7	Small quantity standards (see note)	20 50 100 200 500
		7	Standard	1000

Note: Please Consult individual model data sheet to determine device per reel availability.

Mini-Circuits carrier tape materials provide protection from ESD (Electro-Static Discharge) during handling and transportation. Tapes are static dissipative and comply with industry standards EIA-481/EIA-541.


Go to: www.minicircuits.com/pages/pdfs/tape.pdf



THIRD AND	SLE PROJECTION
\bigoplus	-[

		REVISIONS			
REV	ECN No.	DESCRIPTION	DATE	DR	AUTH
OR	M108436	NEW RELEASE	11/14/06	PW	IG
				·	

SUGGESTED MOUNTING CONFIGURATION FOR WW107 CASE STYLE, "cb" PIN CONNECTION



NOTES:

- 1. TRACE WIDTH IS SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS .030" \pm .002"; COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
- 2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.
- 3. IF PCB DESIGN RULES ALLOW, PLACE GROUND VIAS UNDER THE LAND PATTERN FOR BETTER RF PERFORMANCE. OTHERWISE PLACE GROUND VIAS AS CLOSE TO LAND PATTERN AS POSSIBLE.



DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER) DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

UNLESS OTHERWISE SPECIFIED		INITIALS	DATE
DIMENSIONS ARE IN INCHES	DRAWN	PW	11/11/06
TOLERANCES ON: 2 PL DECIMALS ±	CHECKED	IL	11/14/06
3 PL DECIMALS ± .005 ANGLES ±	APPROVED	IG	11/14/06
FRACTIONS ±			

	DKAWN	. "	11/11/00	
N: : ±	CHECKED	IL	11/14/06	
± .005	APPROVED	IG	11/14/06	
eg				
Mint Cinculta (D)				


THIS DOCUMENT AND ITS CONTENTS ARE THE PROPERTY OF MINI-CIRCUITS. EXCEPT FOR USE EXPRESSLY GRANTED, IN WRITING, TO ITS VENDORS, VEND AND THE UNITED STATES GOVERNMENT, MINI-CIRCUITS RESERVES ALL PRODESIGN, USE, MANUFACTURING AND REPRODUCTION RIGHTS THERETO. THESE CONTENTS SHALL NOT BE USED, DUPLICATED OR DISCLOSED TO ANY PARTY, IN WHOLE OR IN PART, WITHOUT WRITTEN PERMISSION OF MINI-CIRC

MRITING, TO ITS VENDORS, VENDEE —CIRCUITS RESERVES ALL PROPRIETARY DUCTION RIGHTS THERETO. PLICATED OR DISCLOSED TO ANY OUTSIDE	SIZE A	code ident 15542	DRAWING	^{но:} 98-PL	-253		REV:	R	
EETA1.DWG REV:A DATE:01/12/95	FILE:	98PL253	SCALE:	8:1	SHEET:	1	OF	1	
			-						_


Mini-Circuits® 13 Neptune Avenue Brooklyn NY 11235

PL, cb, WW107, MAR, TB-411-XX+

Evaluation Board and Circuit



TB-411-4+




COMPONENT	VALUE
A1	MAR-4SM(+)
C1 (NOTE 4)	2400 pF
C2 (NOTE 4)	2400 pF
C3 (bypass)	0.1 uF
R1	133 Ohms, 0.75W
R2	2.21 Ohms, 0.25W
CHK	Mini-Circuits TCCH-80+

Schematic Diagram

NOTE:

- 1. Vcc voltage: +12±0.2V.
- 2. SMA Female connectors.
- 3. PCB material: Rogers R04350 or equivalent, dielectric constant=3.5, dielectric thickness=.030 inch.
- 4. Capacitors, C1 & C2 should be free of resonance up to the highest frequency specified.



Mini-Circuits

Environmental Specifications

ENV08T3

All Mini-Circuits products are manufactured under exacting quality assurance and control standards, and are capable of meeting published specifications after being subjected to any or all of the following physical and environmental test.

Specification	Test/Inspection Condition	Reference/Spec
Operating Temperature	-40° to 85°C Ambient Environment	Individual Model Data Sheet
Storage Temperature	-55° to 100° C Ambient Environment	Individual Model Data Sheet
Thermal Shock	-55° to 100°C, 100 cycles	MIL-STD-202, Method 107, Condition A-3, except +100°C
Mechanical Shock	1.5Kg, 0.5 ms, 5 shock pulses, Y1 direction only	MIL-STD-883, Method 2002, Condition B, except Y1 direction only
Vibration (Variable Frequency)	50g peak	MIL-STD-883, Method 2007, Condition B
Autoclave	15 psig, 100% RH, 121°C, 96 hours	JESD22-A102, Condition C
HAST	130°C, 85% RH, 96 hours	JESD22-A110
Solderability	10X Magnification	J-STD-002, Para 4.2.5, Test S, 95% Coverage
Solder Reflow Heat	Sn-Pb Eutetic Process: 240°C peak Pb-Free Process: 260°C peak	J-STD-020, Table 4-1, 4-2 and 5-2; Figure 5-1
Moisture Sensitivity: Level 1	Bake at 125°C for 24 hours Soak at 85°C/85% RH for 168 hours, Reflow 3 cycles at 260°C peak	J-STD-020
Marking Resistance to Solvents	Isopropyl alcohol + mineral spirits at 25°C; terpene defluxer at 25°C; distilled water + proylene glycol monomethyl ether +	MIL-STD-202, Method 215

ENV08T3 Rev: B

12/02/10

M129510 File: ENV08T3.pdf

This document and its contents are the property of Mini-Circuits.



Environmental Specifications ENV08T3

All Mini-Circuits products are manufactured under exacting quality assurance and control standards, and are capable of meeting published specifications after being subjected to any or all of the following physical and environmental test.

Specification	Test/Inspection Condition	Reference/Spec

monoethanolamine at 63°C to 70°C

ENV08T3 Rev: B

12/02/10

M129510 File: ENV08T3.pdf

This document and its contents are the property of Mini-Circuits.