

# Fixed Attenuator

**RCAT-12+** 

50Ω 1.8 W 12 dB DC to 20 GHz

#### THE BIG DEAL

- Wide Bandwidth, DC to 20 GHz
- Excellent Power Handling, 1.8 W
- Excellent Attenuation Accuracy & Flatness
- Miniature Size, 2.25 x 2.25 x 1.1 mm
- Ceramic, Hermetic, Nitrogen Filled
- Aqueous Washable



Generic photo used for illustration purposes only

CASE STYLE: LZ1737

### +RoHS Compliant

The +Suffix identifies RoHS Compliance. See our website for methodologies and qualification

#### **APPLICATIONS**

- Cellular
- PCS
- Communications
- Radar
- Wideband Military
- Test and Measurement Equipment

#### **PRODUCT OVERVIEW**

RCAT-12+ (RoHS compliant) is a wideband fixed attenuator with excellent attenuation accuracy and flatness. It can handle up to 1.8 W. The integrated circuits comprising of thin film resistors is bonded in an optimized multi layer integrated LTCC substrate, and then hermetically sealed under a controlled nitrogen atmosphere with gold-plated covers and eutectic AuSn solder. These attenuators are capable of meeting MIL requirements for gross leak, fine leak, thermal shock, vibration, acceleration, mechanical shock, and HTOL. The testing can be done if requested.

#### **KEY FEATURES**

Feature	Advantages
Max Power Input 1.8 W	Thermally optimized design can operate reliably at much higher input power as compared to similar devices
Wide Bandwidth, DC to 20 GHz	Supports a broad band of applications with predictable and repeatable performance, excellent choice to buffer cascaded reflective components.
Ceramic Hermetic Package	Highly reliable hermetic package provides predictable and repeatable performance in military applications including ground, air, and ship requirements
Very Small Size	Miniature 2.25 mm x 2.25 mm and very low profile of 1.1 mm.

REV. C ECO-024243 RCAT-12+ MCL NY 250117





# Fixed Attenuator

**RCAT-12+** 

50Ω 1.8 W 12 dB DC to 20 GHz

#### ELECTRICAL SPECIFICATIONS¹ AT +25°C, 50Ω

Parameter	Condition (GHz)	Min.	Тур.	Max.	Unit
Frequency Range		DC		20	GHz
	1	11.5	12.0	12.5	
Attenuation	10	12.2	12.8	13.4	dB
	20	13.8	14.8	15.8	
	1		31.8		
Return Loss	10		20.3		dB
	20		15.7		

<sup>1.</sup> Tested using characterization test circuit as defined in Figure 1. See data and graphs for performance at all other frequencies.

#### ABSOLUTE MAXIMUM RATINGS<sup>2</sup>

Parameter	Ratings
Operating Case Temperature <sup>3</sup>	-55°C to +125°C
Storage Temperature	-65°C to +150°C
RF Input Power <sup>4</sup>	1.8 W at +25°C

<sup>2.</sup> Permanent damage may occur if any of these limits are exceeded.

3. Case is defined as ground lead.




<sup>4.</sup> RF Power at +25°C case temperature: 1.8 W. Derate linearly to 0.33 W at +125°C.



# Fixed Attenuator

**RCAT-12+** 

 $50\Omega$  1.8 W 12 dB DC to 20 GHz



#### **PAD DESCRIPTION**

Function	Pad Number	Description
RF-IN / RF-OUT	1	RF input / output pad
RF-OUT / RF-IN	3	RF input / output pad
GND	2,4	Connected to circuit ground

#### **CHARACTERIZATION TEST CIRCUIT**





Fig 1. Block diagram of Test Circuit used for characterization. Characterization was performed by Modelithics, conditions test board details are available at: <a href="https://www.modelithics.com/mvp/minicircuits">www.modelithics.com/mvp/minicircuits</a>

#### **PRODUCT MARKING**



Marking may contain other features or characters for internal lot control.




# Fixed Attenuator

**RCAT-12+** 

 $50\Omega$  1.8 W 12 dB DC to 20 GHz

#### **TYPICAL PERFORMANCE DATA AT +25°C**

Frequency (GHz)	Attenuation (dB)	VSWR (:1)
0.05	12.02	29.66
2.00	12.08	29.98
5.00	12.26	24.28
8.00	12.56	21.32
10.00	12.82	20.27
11.00	12.95	19.60
12.00	13.11	19.10
13.00	13.26	18.75
14.00	13.44	18.19
15.00	13.65	17.63
20.00	14.79	15.68







# Fixed Attenuator

**RCAT-12+** 

50Ω 12 dB DC to 20 GHz 1.8 W

### ADDITIONAL DETAILED TECHNICAL INFORMATION IS AVAILABLE ON OUR DASHBOARD. CLICK HERE

Parformence Data and Country	Data Table
Performance Data and Graphs	Swept Graphs
Case Style	LZ1737 Ceramic package, Terminal finish: Ni-Pd-Au
Tape & Reel	F66
Suggested Layout for PCB Design	PL-386
Evaluation Board	TB-668-12+
Environmental Ratings	ENV71

#### **ESD RATING**

Human Body Model (HBM): Class 1A (Pass 250 V) (JESD22-A114)

Machine Model (MM): Class B (Pass 200 V) (JESD22-A115)

#### **MSL RATING**

Moisture Sensitivity: MSL1 in accordance with IPC/JEDEC J-STD-020D

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the standard terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at <a href="https://www.minicircuits.com/terms/viewterm.html">www.minicircuits.com/terms/viewterm.html</a>




### **Fixed Attenuator**

### Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	RETURN LOSS (dB)
0.05	12.02	29.66
0.5	12.03	31.81
1.0	12.04	31.82
1.5	12.06	31.09
2.0	12.08	29.98
2.5	12.10	28.77
3.0	12.12	27.66
3.5	12.15	26.71
4.0	12.19	25.82
4.5	12.22	24.99
5.0	12.26	24.28
5.5	12.31	23.66
6.0	12.35	23.12
6.5	12.40	22.65
7.0	12.45	22.15
7.5	12.50	21.66
8.0	12.56	21.32
8.5	12.63	21.01
9.0	12.69	20.80
9.5	12.74	20.51
10.0	12.82	20.27
10.5	12.88	19.92
11.0	12.95	19.60
11.5	13.03	19.34
12.0	13.11	19.10
12.5	13.19	18.94
13.0	13.26	18.75
13.5	13.33	18.47
14.0	13.44	18.19
14.5	13.51	17.98
15.0	13.65	17.63
15.5	13.75	17.37
16.0	13.92	17.09
16.5	14.07	16.96
17.0	14.17	16.85
17.5	14.23	16.66
18.0	14.24	16.41
18.5	14.40	16.06
19.0	14.53	15.85
19.5	14.63	15.78
20.0	14.79	15.68

minicircuits.com


### Typical Performance Curves






### **Outline Dimensions**

**LZ1737** 



#### PCB LAND PATTERN



SUGGESTED LAYOUT
TOLERANCE TO BE WITHIN ±.002

#### NOTES:

1. DENOTES METALLIZATION

Weight: .015 grams

Dimensions are in inches [mm]. Tolerances: 2 Pl.±.01; 3 Pl. ±.005 Inch

**Notes:** 

1. Case material: Ceramic.

2. Base material: 36 mil thk laminate.

3. Termination finish: Electroless Nickel-Palladium-Gold Plate.






P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site

The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com

RF/IF MICROWAVE COMPONENTS

# Tape & Reel Packaging TR-F66

#### DEVICE ORIENTATION IN T&R



DIRECTION OF FEED

Tape Width, mm	Device Cavity Pitch, mm	Reel Size, inches		es per Reel ee note
8	4	7	Small quantity standard	20 50 100 200 500
		7	Standard	1000, 2000, 3000

Note: Please consult individual model data sheet to determine device per reel availability.

Mini-Circuits carrier tape materials provide protection from ESD (Electro-Static Discharge) during handling and transportation. Tapes are static dissipative and comply with industry standards EIA-481/EIA-541.


Go to: www.minicircuits.com/pages/pdfs/tape.pdf



THIRD A	NGLE PROJECT	ION
<b>(</b>	+ -{}	_

		REVISIONS			
REV	ECN No.	DESCRIPTION	DATE	DR	AUTH
OR	M138802	NEW RELEASE	12/07/12	AV	BT
A	M142XXX	REDESIGNED PL-DRAWING	07/17/13	IL	RD

# SUGGESTED MOUNTING CONFIGURATION FOR LZ1737 CASE STYLE, "04AF03" PIN CODE



#### **NOTES:**

- 1. COPLANAR WAVEGUIDE PARAMETERS ARE SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS .010"  $\pm$  .001"; COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH AND GAP MAY NEED TO BE MODIFIED.
- 2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.
- 3. IN ORDER TO ACHIEVE PERFORMANCE AT HIGHER FREQUENCIES, THICKNESS OF SOLDER MASK SHALL BE MINIMAL.



DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)



DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

UNLESS OTHERWISE SPECIFIED		INITIALS	DATE
DIMENSIONS ARE IN INCHES	DRAWN	AV	09/19/12
TOLERANCES ON: 2 PL DECIMALS ±	CHECKED	IL	10/11/12
3 PL DECIMALS ± .005	APPROVED	BT	12/07/12
ANGLES ± FRACTIONS ±			
	o: :1 /B\		

Mini-Circuits ®

THIS DOCUMENT AND ITS CONTENTS ARE THE PROPERTY OF MINI-CIRCUITS. EXCEPT FOR USE EXPRESSLY GRANTED, IN WRITING, TO ITS VENDORS, VENDEE AND THE UNITED STATES GOVERNMENT, MINI-CIRCUITS RESERVES ALL PROPRIETARY DESIGN, USE, MANUFACTURING AND REPRODUCTION RIGHTS THERETO. THESE CONTENTS SHALL NOT BE USED, DUPLICATED OR DISCLOSED TO ANY OUTSIDE PARTY, IN WHOLE OR IN PART, WITHOUT WRITTEN PERMISSION OF MINI-CIRCUITS.


ACHEETA1 DWC	DEV/AA	DATE:01/12/95
ASTEEIAI.UWU	REV:A	DAIE:U1/12/33

	Mini-	Circu	its®	13 Neptune Avenue Brooklyn NY 11235
--	-------	-------	------	--


PL, 04AF03, LZ1737, TB-668-XX+

SIZE A	code ident 15542	DRAWING		PL-386	}	REV:	A
FILE: 9	8PL386	SCALE:	10:1	SHEET:	1	OF	1

## Evaluation Board and Circuit



TB-668-12+



<u>Schematic Diagram</u>

#### Notes:

- 1. 50 Ohm SMA Female connectors.
- 2. PCB Material: R04350 or equivalent, Dielectric Constant=3.5, Thickness=.010 inch.

III Mini-Circuits®

## Mini-Circuits

#### **Environmental Specifications**

ENV71

All Mini-Circuits products are manufactured under exacting quality assurance and control standards, and are capable of meeting published specifications after being subjected to any or all of the following physical and environmental test.

Specification	Test/Inspection Condition	Reference/Spec
Operating Temperature	-55° to 125° C Ambient Environment	Individual Model Data Sheet
Storage Temperature	-65° to 150° C Ambient Environment	Individual Model Data Sheet
Thermal Shock (device level)	-55° to 125°C, 100 cycles	MIL-STD-202, Method 107
Thermal Shock (board level)	-55° to 150°C, 1000 cycles	MIL-STD-202, Method 107
HTOL	1000 hours, 25°C, @ rated power	MIL-STD-202, Method 108, cond D.
Constant Acceleration	Y1 plane only, 30 Kg	MIL-STD-883, Method 2001, Cond. E
Vibration	10-2000MHz sine, 20g, 3 axis	MIL-STD-202, Method 204, Cond. D
Mechanical Shock	50g, 11 ms, 1/2-sine, 18 shocks: 3 each direction, each of 3 axes	MIL-STD-202, Method 213, Condition A
PIND	20G's @130 Hz	MIL-STD-750, Method 2052.2
Resistance to Soldering Heat	3X Reflow, Peak Temperature 260°C	JESD22-B102
Moisture Sensitivity Level	Hermetic device, MSL-1 by construction	JESD22-A113, MSL1/260
Hermeticity	Fine Leak, Gross Leak	MIL-STD-202, Method 112, Cond. C&D

ENV71 Rev: A 03/21/13 M140986 File: ENV71.pdf This document and its contents are the property of Mini-Circuits.



#### **Environmental Specifications**

All Mini-Circuits products are manufactured under exacting quality assurance and control standards, and are capable of meeting published specifications after being subjected to any or all of the following physical and environmental test.

ENV71

Specification	Test/Inspection Condition	Reference/Spec
Autoclave	15 psig, 100% RH, 121°C, 96 hours	JESD22 - Method A102