



CASE STYLE: JF1258

SUM	PORT	17
PORT 1		3
PORT 2		5
PORT 3		7
PORT 4		9
GROUND	all others	

PCB Land Pattern

TOP SIDE

SIDE VIEW

BOTTOM SIDE

K TYP

L TYP

M

E TYP

G TYP

D

E TYP

F TYP

COPPER

Suggested Layout,
Tolerance to be within $\pm .002$

A	B	C	D	E	F	G
1.250	1.000	.200	.125	.100	.060	.040
31.75	25.40	5.08	3.18	2.54	1.52	1.02
H	J	K	L	M		wt
--	--	.050	.060	.920		grams
--	--	1.27	1.52	23.37		4.4

Notes

A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.

C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MC/Store/terms_iso

Parameter	Frequency (MHz)	Min.	Typ.	Max.	Unit
Frequency Range		690		2700	MHz
Insertion Loss Above 6.0 dB	800-2200 690-2700		1.0 1.5	1.6 2.6	dB
Isolation	690-2700	15	20		dB
Phase Unbalance	690-2700		4	7	Degree
Amplitude Unbalance	690-2700		0.4	0.8	dB
VSWR (Port S)	690-2700		1.5		:1
VSWR (Port 1-4)	690-2700		1.2		:1

Typical Performance Data														
Freq. (MHz)	Total Loss¹ (dB)				Amp. Unbal. (dB)	Isolation (dB)			Phase Unbal. (deg.)	VSWR S	VSWR 1	VSWR 2	VSWR 3	VSWR 4
	S-1	S-2	S-3	S-4		1-2	2-3	3-4						
600	6.80	7.23	7.19	6.77	0.46	17.21	17.55	17.13	0.63	2.31	1.29	1.41	1.42	1.30
700	6.56	6.99	6.94	6.54	0.45	19.79	19.35	19.70	0.49	1.96	1.23	1.33	1.33	1.25
1000	6.20	6.58	6.53	6.18	0.39	27.46	26.70	27.06	0.53	1.20	1.17	1.19	1.20	1.19
1100	6.21	6.56	6.52	6.18	0.38	25.76	29.38	25.39	0.67	1.10	1.16	1.16	1.17	1.18
1200	6.27	6.61	6.57	6.24	0.37	23.61	30.76	23.29	0.87	1.19	1.16	1.13	1.14	1.17
1400	6.48	6.79	6.76	6.44	0.35	20.89	29.04	20.61	1.34	1.47	1.14	1.08	1.09	1.15
1600	6.70	7.02	6.98	6.65	0.36	19.94	26.90	19.67	1.89	1.70	1.12	1.07	1.08	1.12
1800	6.81	7.17	7.13	6.77	0.40	20.51	25.91	20.21	2.36	1.77	1.11	1.14	1.15	1.12
2000	6.74	7.15	7.10	6.71	0.43	22.93	25.98	22.57	2.61	1.57	1.13	1.24	1.24	1.14
2100	6.67	7.09	7.05	6.65	0.44	25.05	26.20	24.59	2.67	1.41	1.14	1.29	1.29	1.15
2200	6.65	7.06	7.02	6.62	0.44	27.28	26.23	26.70	2.73	1.25	1.15	1.34	1.34	1.17
2300	6.70	7.09	7.04	6.67	0.42	27.31	25.62	26.86	2.79	1.20	1.19	1.40	1.40	1.20
2400	6.85	7.19	7.15	6.80	0.39	24.87	24.27	24.63	2.89	1.35	1.26	1.45	1.45	1.26
2600	7.44	7.67	7.61	7.37	0.30	20.70	20.83	20.54	3.55	1.95	1.50	1.50	1.51	1.48
2700	7.84	8.01	7.95	7.75	0.26	19.81	19.24	19.58	4.16	2.32	1.67	1.50	1.51	1.64

1. Total Loss = Insertion Loss + 6dB splitter theoretical loss

Frequency (MHz)	S-1 Total Loss (dB)	S-3 Total Loss (dB)
600	6.8	7.2
900	6.2	6.5
1100	6.1	6.5
1300	6.4	6.8
1500	6.6	7.0
1800	6.9	7.2
2100	6.8	7.0
2400	6.9	7.1
2700	7.8	8.0

4 Way-0° Power Splitter/Combiner

SEPS-4-272+

Typical Performance Data

FREQ. (MHz)	TOTAL LOSS ¹ (dB)				AMP. UNBAL. (dB)	ISOLATION (dB)			PHASE UNBAL. (deg.)	FREQ. (MHz)	VSWR (:1)				
	S-1	S-2	S-3	S-4		1-2	2-3	3-4			S	1	2	3	4
600.0	6.80	7.23	7.19	6.77	0.46	17.21	17.55	17.13	0.63	600.0	2.31	1.29	1.41	1.42	1.30
700.0	6.56	6.99	6.94	6.54	0.45	19.79	19.35	19.70	0.49	700.0	1.96	1.23	1.33	1.33	1.25
800.0	6.37	6.79	6.74	6.36	0.43	22.91	21.45	22.78	0.41	800.0	1.65	1.19	1.26	1.28	1.22
850.0	6.30	6.71	6.66	6.29	0.42	24.61	22.64	24.44	0.43	850.0	1.52	1.18	1.24	1.25	1.21
900.0	6.25	6.65	6.60	6.24	0.41	26.20	23.91	25.96	0.45	900.0	1.40	1.18	1.22	1.23	1.20
950.0	6.22	6.60	6.56	6.20	0.40	27.28	25.27	26.94	0.49	950.0	1.29	1.17	1.20	1.22	1.19
1000.0	6.20	6.58	6.53	6.18	0.39	27.46	26.70	27.06	0.53	1000.0	1.20	1.17	1.19	1.20	1.19
1050.0	6.19	6.56	6.52	6.18	0.39	26.82	28.14	26.42	0.60	1050.0	1.13	1.17	1.17	1.18	1.18
1100.0	6.21	6.56	6.52	6.18	0.38	25.76	29.38	25.39	0.67	1100.0	1.10	1.16	1.16	1.17	1.18
1150.0	6.23	6.58	6.54	6.21	0.37	24.63	30.31	24.29	0.76	1150.0	1.14	1.16	1.15	1.16	1.18
1200.0	6.27	6.61	6.57	6.24	0.37	23.61	30.76	23.29	0.87	1200.0	1.19	1.16	1.13	1.14	1.17
1250.0	6.31	6.64	6.60	6.28	0.36	22.73	30.70	22.43	0.97	1250.0	1.26	1.16	1.12	1.13	1.16
1300.0	6.36	6.69	6.65	6.33	0.36	21.99	30.29	21.70	1.10	1300.0	1.33	1.15	1.11	1.11	1.16
1350.0	6.42	6.74	6.70	6.38	0.36	21.38	29.69	21.10	1.22	1350.0	1.40	1.15	1.09	1.10	1.15
1400.0	6.48	6.79	6.76	6.44	0.35	20.89	29.04	20.61	1.34	1400.0	1.47	1.14	1.08	1.09	1.15
1450.0	6.53	6.85	6.82	6.49	0.36	20.50	28.38	20.22	1.48	1450.0	1.54	1.14	1.07	1.08	1.14
1500.0	6.59	6.91	6.87	6.55	0.36	20.22	27.83	19.94	1.60	1500.0	1.60	1.13	1.07	1.07	1.13
1550.0	6.65	6.97	6.93	6.60	0.36	20.04	27.32	19.76	1.77	1550.0	1.65	1.13	1.06	1.07	1.13
1600.0	6.70	7.02	6.98	6.65	0.36	19.94	26.90	19.67	1.89	1600.0	1.70	1.12	1.07	1.08	1.12
1650.0	6.74	7.07	7.03	6.70	0.37	19.93	26.53	19.65	2.05	1650.0	1.74	1.12	1.09	1.09	1.12
1700.0	6.78	7.11	7.08	6.73	0.38	20.01	26.23	19.73	2.17	1700.0	1.76	1.11	1.10	1.11	1.12
1750.0	6.80	7.15	7.11	6.76	0.39	20.21	26.06	19.92	2.27	1750.0	1.78	1.11	1.12	1.13	1.12
1800.0	6.81	7.17	7.13	6.77	0.40	20.51	25.91	20.21	2.36	1800.0	1.77	1.11	1.14	1.15	1.12
1850.0	6.81	7.19	7.15	6.78	0.41	20.92	25.85	20.61	2.46	1850.0	1.75	1.11	1.17	1.17	1.13
1900.0	6.80	7.18	7.14	6.77	0.42	21.45	25.85	21.13	2.51	1900.0	1.70	1.12	1.19	1.20	1.13
1950.0	6.77	7.17	7.13	6.74	0.43	22.12	25.90	21.79	2.58	1950.0	1.65	1.12	1.21	1.22	1.14
2000.0	6.74	7.15	7.10	6.71	0.43	22.93	25.98	22.57	2.61	2000.0	1.57	1.13	1.24	1.24	1.14
2050.0	6.70	7.11	7.07	6.68	0.44	23.92	26.09	23.52	2.67	2050.0	1.50	1.13	1.26	1.27	1.15
2100.0	6.67	7.09	7.05	6.65	0.44	25.05	26.20	24.59	2.67	2100.0	1.41	1.14	1.29	1.29	1.15
2150.0	6.65	7.07	7.03	6.63	0.44	26.25	26.26	25.73	2.71	2150.0	1.33	1.14	1.31	1.32	1.16
2200.0	6.65	7.06	7.02	6.62	0.44	27.28	26.23	26.70	2.73	2200.0	1.25	1.15	1.34	1.34	1.17
2300.0	6.70	7.09	7.04	6.67	0.42	27.31	25.62	26.86	2.79	2300.0	1.20	1.19	1.40	1.40	1.20
2400.0	6.85	7.19	7.15	6.80	0.39	24.87	24.27	24.63	2.89	2400.0	1.35	1.26	1.45	1.45	1.26
2500.0	7.10	7.39	7.34	7.04	0.34	22.41	22.55	22.26	3.12	2500.0	1.61	1.36	1.49	1.49	1.35
2600.0	7.44	7.67	7.61	7.37	0.30	20.70	20.83	20.54	3.55	2600.0	1.95	1.50	1.50	1.51	1.48
2700.0	7.84	8.01	7.95	7.75	0.26	19.81	19.24	19.58	4.16	2700.0	2.32	1.67	1.50	1.51	1.64

¹ Total Loss = Insertion Loss + 6dB Splitter Loss



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 • Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site
The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com



IF/RF MICROWAVE COMPONENTS








REV. OR
SEPS-4-272+
10/26/2012
Page 1 of 1

4 Way-0° Power Splitter/Combiner

SEPS-4-272+

Typical Performance Curves



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 • Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site
The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com




IF/RF MICROWAVE COMPONENTS




REV. OR
SEPS-4-272+
10/26/2012
Page 1 of 1

Outline Dimensions



PCB Land Pattern



Suggested Layout,
Tolerance to be within $\pm .002$

CASE #	A	B	C	D	E	F	G	H	J	K	L	M	WT. GRAM
JF1258	1.250 (31.75)	1.000 (25.40)	.200 (5.08)	.125 (3.17)	.100 (2.54)	.060 (1.52)	.040 (1.02)	-	-	.050 (1.27)	.060 (1.52)	.920 (23.37)	4.4

Dimensions are in inches (mm). Tolerances: 2 Pl. $\pm .03$; 3Pl. $\pm .015$

Notes:

- Case material: Nickel-Silver alloy.
- Base: Printed wiring laminate.
- Termination finish:
For RoHS Case Styles: 3-5 μ inch (.08-.13 μ m) Gold over 120-240 μ inch (3-6 μ m) Nickel plate.
All models, (+) suffix.




INTERNET <http://www.minicircuits.com>

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010

Mini-Circuits ISO 9001 & ISO 14001 Certified

Tape & Reel Packaging TR-F27



Tape Width, mm	Device Cavity Pitch, mm	Reel Size, inches	Devices per Reel
44	32	13	125

Mini-Circuits carrier tape materials provide protection from ESD (Electro-Static Discharge) during handling and transportation. Tapes are static dissipative and comply with industry standards EIA-481/EIA-541.

Go to: www.minicircuits.com/pages/pdfs/tape.pdf




INTERNET <http://www.minicircuits.com>

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661


Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010

Mini-Circuits ISO 9001 & ISO 14001 Certified



REVISIONS					
REV	ECN No.	DESCRIPTION	DATE	DR	AUTH
OR	M112242	NEW RELEASE	07/05/07	MMG	HY
A	M138952	PIN CONNECTION 22SP01 WAS "sq"	10/03/12	GF	WP

SUGGESTED MOUNTING CONFIGURATION FOR
JF1258 CASE STYLE, "22SP01" PIN CONNECTION



- NOTE: 1. TRACE WIDTH IS SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS .030" $\pm$.002"; COPPER: 1/2 OZ. EACH SIDE.
 FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
 2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.



DENOTES PCB COPPER LAYOUT WITH SMOBC
 (SOLDER MASK OVER BARE COPPER)



DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

UNLESS OTHERWISE SPECIFIED	INITIALS		DATE
DIMENSIONS ARE IN INCHES TOLERANCES ON: 2 PL DECIMALS $\pm$ 3 PL DECIMALS $\pm$.005 ANGLES $\pm$ FRACTIONS $\pm$	DRAWN	MMG	06/28/07
	CHECKED	AV	07/05/07
	APPROVED	HY	07/05/07



Mini-Circuits® 13 Neptune Avenue
 Brooklyn NY 11235



PL, 22SP01, JF1258, TB-441+

Mini-Circuits® THIS DOCUMENT AND ITS CONTENTS ARE THE PROPERTY OF MINI-CIRCUITS. EXCEPT FOR USE EXPRESSLY GRANTED, IN WRITING, TO ITS VENDORS, VENDEE AND THE UNITED STATES GOVERNMENT, MINI-CIRCUITS RESERVES ALL PROPRIETARY DESIGN, USE, MANUFACTURING AND REPRODUCTION RIGHTS THERETO. THESE CONTENTS SHALL NOT BE USED, DUPLICATED OR DISCLOSED TO ANY OUTSIDE PARTY, IN WHOLE OR IN PART, WITHOUT WRITTEN PERMISSION OF MINI-CIRCUITS.			
ASHEETA1.DWG REV:A DATE:01/12/95			

SIZE	CODE IDENT	DRAWING NO:	REV:
A	15542	98-PL-273	A
FILE:	98PL273	SCALE:	SHEET:
		3:1	1 OF 1

Evaluation Board and Circuit

For Pin Connections refer to Data Sheet of the DUT



Schematic Diagram

Notes:

1. SMA Female connectors.
2. PCB Material: Rogers R04350 or equivalent,
Dielectric Constant=3.5, Thickness=.030 inch.

 Mini-Circuits®



All Mini-Circuits products are manufactured under exacting quality assurance and control standards, and are capable of meeting published specifications after being subjected to any or all of the following physical and environmental test.

Specification	Test/Inspection Condition	Reference/Spec
Operating Temperature	-40° to 85°C Ambient Environment	Individual Model Data Sheet
Storage Temperature	-55° to 100° C Ambient Environment	Individual Model Data Sheet
Humidity	90 to 95% RH, 240 hours, 50°C	MIL-STD-202, Method 103, Condition A, Except 50°C and end-point electrical test done within 12 hours
Thermal Shock	-55° to 100°C, 100 cycles	MIL-STD-202, Method 107, Condition A-3, except +100°C
Solder Reflow Heat	Sn-Pb Eutetic Process: 225°C peak Pb-Free Process 245° - 250°C peak	J-STD-020, Table 4-1, 4-2 and 5-2, Figure 5-1
Solderability	10X Magnification	J-STD-002, 95% Coverage
Vibration (High Frequency)	20g peak, 10-2000 Hz, 12 times in each of three perpendicular directions (total 36)	MIL-STD-202, Method 204, Condition D
Mechanical Shock	50g, 11 ms, 1/2-sine, 18 shocks: 3 each direction, each of 3 axes	MIL-STD-202, Method 213, Condition A
Marking Resistance to Solvents	Isopropyl alcohol + mineral spirits at 25°C; terpene defluxer at 25°C; distilled water + proylene glycol monomethyl ether + monoethanolamine at 63°C to 70°C	MIL-STD-202, Method 215