

# Bandpass Filter

## SYBP-2640+

50Ω 2500 to 2780 MHz



CASE STYLE: TT1423

### Features

- High power handling
- Small size
- Temperature stable
- Excellent rejection

### Applications

- Satellite
- Mobile
- Lab use

### Electrical Specifications at 25°C


Parameter	F#	Frequency (MHz)	Min.	Typ.	Max.	Unit	
Pass Band	Center Frequency	—	—	2640	—	MHz	
	Insertion Loss	F1-F2	2500 - 2780	—	2.3	2.9	dB
	VSWR	F1-F2	2500 - 2780	—	2.0	2.5	:1
Stop Band, Lower	Insertion Loss	DC-F3	DC - 1780	20	23	—	dB
	VSWR	DC-F3	DC - 1780	—	15	—	:1
Stop Band, Upper	Insertion Loss	F4-F5	3800 - 6040	20	30	—	dB
	VSWR	F4-F5	3800 - 6040	—	10	—	:1

### Maximum Ratings


Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
RF Power Input	7W* max. at 25°C

\*Passband rating, derate linearly to 3W at 85°C ambient  
Permanent damage may occur if any of these limits are exceeded.

### Functional Schematic



### Typical Frequency Response






### +RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

### Typical Performance Data at 25°C

Frequency (MHz)	Insertion Loss (dB)	VSWR (:1)
10.00	71.24	66.50
100.00	54.17	47.56
500.00	44.39	34.98
1000.00	58.56	34.73
1520.00	36.11	28.34
1600.00	33.17	26.66
1780.00	24.59	21.89
2000.00	12.23	11.50
2500.00	2.33	1.87
2780.00	2.29	1.80
3000.00	3.22	2.54
3720.00	26.76	8.04
4000.00	31.36	8.73
5000.00	27.09	11.73
6040.00	35.70	7.78



### Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at [www.minicircuits.com/MCLStore/terms.jsp](http://www.minicircuits.com/MCLStore/terms.jsp)




### Bandpass Filter

#### Pin Connections


RF IN	4
RF OUT	6
GROUND	1,2,3,5

**Demo Board MCL P/N: TB-517+**  
**Suggested PCB Layout (PL-308)**




- NOTES:**
- COPLANAR WAVEGUIDE PARAMETERS ARE SHOWN FOR ROGERS R04350B WITH THICKNESS  $.030" \pm .002"$ ; COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH AND GAP MAY NEED TO BE MODIFIED.
  - BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.
- DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)
- DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

#### Outline Drawing



#### PCB Land Pattern



- METALLIZATION
- SOLDER RESIST

#### Outline Dimensions (inch)

A	B	C	D	E	F	G	H
.25	.31	.15	.090	.040	.065	.060	.065
6.35	7.87	3.81	2.29	1.02	1.65	1.52	1.65
J	K	L	N	Q			wt.
.300	.060	.060	.105	.070			grams
7.62	1.52	1.52	2.67	1.78			0.50

#### Notes







- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at [www.minicircuits.com/MCLStore/terms.jsp](http://www.minicircuits.com/MCLStore/terms.jsp)

*Typical Performance Data*


FREQ. (MHz)	INSERTION LOSS (dB)	INPUT RETURN LOSS (dB)	OUTPUT RETURN LOSS (dB)
10.0	71.24	0.26	0.19
50.0	59.59	0.32	0.31
100.0	54.17	0.37	0.40
200.0	48.78	0.43	0.49
400.0	44.80	0.49	0.51
500.0	44.39	0.50	0.50
600.0	45.12	0.50	0.50
800.0	50.21	0.50	0.55
1000.0	58.56	0.50	0.68
1100.0	49.17	0.51	0.76
1200.0	44.81	0.52	0.84
1300.0	41.98	0.54	0.92
1400.0	39.52	0.57	1.00
1500.0	36.76	0.60	1.09
1520.0	36.11	0.61	1.11
1600.0	33.17	0.65	1.17
1700.0	28.67	0.72	1.27
1760.0	25.64	0.77	1.33
1780.0	24.59	0.79	1.36
1800.0	23.52	0.82	1.39
1900.0	17.98	1.02	1.64
2000.0	12.23	1.51	2.32
2100.0	6.83	3.06	4.52
2200.0	3.51	6.55	9.99
2260.0	2.82	8.12	11.50
2300.0	2.65	8.49	10.80
2360.0	2.55	8.74	9.71
2400.0	2.50	9.02	9.37
2460.0	2.40	9.73	9.33
2500.0	2.33	10.37	9.52
2520.0	2.30	10.70	9.65
2540.0	2.27	11.02	9.80
2560.0	2.25	11.32	9.94
2580.0	2.23	11.58	10.07
2600.0	2.21	11.79	10.20
2620.0	2.20	11.91	10.31
2640.0	2.19	11.95	10.41
2660.0	2.19	11.92	10.49
2680.0	2.20	11.84	10.55
2700.0	2.21	11.70	10.61
2720.0	2.22	11.53	10.66
2740.0	2.24	11.31	10.71
2760.0	2.26	11.08	10.74
2780.0	2.29	10.84	10.77
2800.0	2.32	10.60	10.78
2860.0	2.45	9.80	10.67
2900.0	2.59	9.16	10.28
2960.0	2.91	8.03	9.11
3000.0	3.22	7.22	8.05
3200.0	5.78	4.40	3.69
3400.0	9.69	4.23	1.82
3600.0	18.20	2.94	0.94
3640.0	20.71	2.63	0.87
3680.0	23.53	2.37	0.81
3720.0	26.76	2.17	0.77
3760.0	30.53	2.03	0.75
3800.0	34.77	1.93	0.72
4000.0	31.36	2.00	0.68
4200.0	31.43	2.61	0.68
4400.0	45.99	2.68	0.69
4600.0	34.35	2.10	0.70
4800.0	29.08	1.69	0.72
5000.0	27.09	1.48	0.74
5400.0	26.63	1.44	0.75
5800.0	32.22	1.77	0.80
6040.0	35.70	2.24	0.94




## Typical Performance Curves





### Outline Dimensions



### PCB Land Pattern



Suggested Layout,  
Tolerance to be within  $\pm 0.002$

 METALLIZATION  
 SOLDER RESIST

CASE #	A	B	C	D	E	F	G	H	J	K	L	M
TT1423	.25 (6.35)	.31 (7.87)	.15 (3.81)	.090 (2.29)	.040 (1.02)	.065 (1.65)	.060 (1.52)	.065 (1.65)	.300 (7.62)	.060 (1.52)	.060 (1.52)	- -

CASE #	N	P	Q	WT. GRAM
TT1423	.105 (2.67)	- -	.070 (1.78)	.50

Dimensions are in inches (mm). Tolerances: 2Pl.  $\pm .01$ ; 3 Pl.  $\pm .005$

### Notes:

- Case material: Plastic.
- Terminations: 2-10  $\mu$  inch (.05-.25 microns) Gold over 100-300  $\mu$  inch (2.54-7.62 microns) Nickel plate.

 **Mini-Circuits**  
ISO 9001 ISO 14001 CERTIFIED

ALL NEW  
 minicircuits.com


P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site



The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: [www.minicircuits.com](http://www.minicircuits.com)

RF/IF MICROWAVE COMPONENTS

# Tape & Reel Packaging TR-F2



Tape Width, mm	Device Cavity Pitch, mm	Reel Size, inches	Devices per Reel See note
16	12	7	10
			20
			50
			100
			200
		13	500

Note: Please consult individual model data sheet to determine device per reel availability

Mini-Circuits carrier tape materials provide protection from ESD (Electro-Static Discharge) during handling and transportation. Tapes are static dissipative and comply with industry standards EIA-481/EIA-541.

Go to: [www.minicircuits.com/pages/pdfs/tape.pdf](http://www.minicircuits.com/pages/pdfs/tape.pdf)




INTERNET <http://www.minicircuits.com>

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010

Mini-Circuits ISO 9001 & ISO 14001 Certified


THIRD ANGLE PROJECTION



REVISIONS

REV	ECN No.	DESCRIPTION	DATE	DR	AUTH
OR	M123346	NEW RELEASE	07/10/09	AV	DY

**SUGGESTED MOUNTING CONFIGURATION  
FOR TT1423 CASE STYLE "06FL04" PIN CONNECTION**



**NOTES:**

1. COPLANAR WAVEGUIDE PARAMETERS ARE SHOWN FOR ROGERS RO4350B WITH THICKNESS .030" ± .002"; COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH AND GAP MAY NEED TO BE MODIFIED.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.



DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)



DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

UNLESS OTHERWISE SPECIFIED

DIMENSIONS ARE IN INCHES  
TOLERANCES ON:  
2 PL DECIMALS ±  
3 PL DECIMALS ± .005  
ANGLES ±  
FRACTIONS ±

	INITIALS	DATE
DRAWN	AV	06/22/09
CHECKED	IL	07/10/09
APPROVED	DY	07/10/09



**Mini-Circuits®**

13 Neptune Avenue  
Brooklyn NY 11235

PL, 06FL04, TT1423, SYBP, TB-517+


THIS DOCUMENT AND ITS CONTENTS ARE THE PROPERTY OF MINI-CIRCUITS. EXCEPT FOR USE EXPRESSLY GRANTED, IN WRITING, TO ITS VENDORS, VENDEE AND THE UNITED STATES GOVERNMENT, MINI-CIRCUITS RESERVES ALL PROPRIETARY DESIGN, USE, MANUFACTURING AND REPRODUCTION RIGHTS THERETO. THESE CONTENTS SHALL NOT BE USED, DUPLICATED OR DISCLOSED TO ANY OUTSIDE PARTY, IN WHOLE OR IN PART, WITHOUT WRITTEN PERMISSION OF MINI-CIRCUITS.

Mini-Circuits®


ASHEETA1.DWG REV:A DATE:01/12/95

SIZE	CODE IDENT	DRAWING NO:	REV:
A	15542	98-PL-308	OR
FILE:	98PL308	SCALE:	8:1
SHEET:	1	OF	1

# Evaluation Board and Circuit




TB-517+



Schematic Diagram

## Notes:

1. 50 Ohm SMA Female connectors.
2. PCB Material: R04350 or equivalent,  
Dielectric Constant=3.5, Thickness=.020 inch.

 Mini-Circuits®



All Mini-Circuits products are manufactured under exacting quality assurance and control standards, and are capable of meeting published specifications after being subjected to any or all of the following physical and environmental test.

Specification	Test/Inspection Condition	Reference/Spec
Operating Temperature	-40° to 85°C Ambient Environment	Individual Model Data Sheet
Storage Temperature	-55° to 100° C Ambient Environment	Individual Model Data Sheet
Humidity	90 to 95% RH, 240 hours, 50°C	MIL-STD-202, Method 103, Condition A, Except 50°C and end-point electrical test done within 12 hours
Thermal Shock	-55° to 100°C, 100 cycles	MIL-STD-202, Method 107, Condition A-3, except +100°C
Solder Reflow Heat	Sn-Pb Eutetic Process: 225°C peak Pb-Free Process 245° - 250°C peak	J-STD-020, Table 4-1, 4-2 and 5-2, Figure 5-1
Solderability	10X Magnification	J-STD-002, 95% Coverage
Vibration (High Frequency)	20g peak, 10-2000 Hz, 12 times in each of three perpendicular directions (total 36)	MIL-STD-202, Method 204, Condition D
Mechanical Shock	50g, 11 ms, 1/2-sine, 18 shocks: 3 each direction, each of 3 axes	MIL-STD-202, Method 213, Condition A
Marking Resistance to Solvents	Isopropyl alcohol + mineral spirits at 25°C; terpene defluxer at 25°C; distilled water + proylene glycol monomethyl ether + monoethanolamine at 63°C to 70°C	MIL-STD-202, Method 215