

CASE STYLE: GU1840

The Big Deal

- Wideband, 20 to 2500 MHz
- Very low insertion loss, 0.4 dB
- Excellent VSWR, 1.05:1
- Tiny size, 0.15 x 0.15 x 0.14"

Product Overview

Mini-Circuits' TCBT-2R5GL+ is an ultra-wideband surface-mount bias tee covering applications from 20 to 2500 MHz with low insertion loss, excellent VSWR, and high DC-RF isolation over its entire frequency range. This model is capable of handling up to +30 dBm (1W) RF input power and DC input current up to 200mA. The unit features core and wire construction mounted on a ceramic base (0.15 x 0.15 x 0.14") with Mini-Circuits Top-Hat feature for faster, more accurate pick and place assembly.

Key Features


Feature	Advantages
Wideband, 20 to 2500 MHz	Supports a wide range of applications with a single device, including biasing broadband amplifiers, laser diodes, active antennas and more.
Low insertion loss, 0.4 dB	Preserves signal strength from input to output and minimizes overall system loss
Excellent VSWR, 1.05:1	Provides excellent matching for 50Ω systems with minimal signal reflection.
RF power handling up to 1W	This model supports applications with a variety of power requirements.
Excellent DC-RF isolation	High DC-RF isolation (44 dB typ. at midband) minimizes RF leakage and interference with other elements in the system.
Miniature size, 0.15 x 0.15 x 0.14"	Small footprint makes the TCBT-2R5GL+ a space-saver in dense PCB-layouts.
Top-Hat feature	Improves speed and accuracy of pick and place assembly.
Leads for excellent solderability.	This model features leads to facilitate soldering on PCB assemblies.

top hat®

Surface Mount Bias-Tee

50Ω Wideband 20 to 2500 MHz

TCBT-2R5GL+



Generic photo used for illustration purposes only

CASE STYLE: GU1840

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications



Available Tape and Reel
at no extra cost

Reel Size	Devices/Reel
7"	20, 50, 100, 200, 500, 1000
13"	2000

Features

- wideband, 20 to 2500 MHz
- low insertion loss, 0.4 dB typ.
- miniature surface mount 0.15"x0.15"
- aqueous washable
- protected by US Patent 7,012,486

Applications

- biasing amplifiers
- biasing of laser diodes
- biasing of active antennas

Electrical Specifications

Parameter	Frequency (MHz)	Min.	Typ.	Max.	Unit
Frequency Range		20		2500	MHz
Insertion Loss	20-200	—	0.2	0.8	dB
	200-1250	—	0.35	0.8	
	1250-2500	—	0.7	1.2	
Isolation	20-200	40	65	—	dB
	200-1250	25	44	—	
	1250-2500	20	40	—	
VSWR	20-200	—	1.05	1.5	:1
	200-1250	—	1.05	1.2	
	1250-2500	—	1.1	1.25	
DC Resistance, DC to RF and DC port		—	0.2	—	ohms

Maximum Ratings


Parameter	Ratings
Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
RF Power	30 dBm max.
Voltage at DC port	25 V max.
DC Current	200mA

Permanent damage may occur if any of these limits are exceeded.


Pad Terminations

Function	Pad Number
RF	4
RF&DC	3
DC	1
ISOLATE (see PCB Layout)	2

Product Marking




Functional Schematic




TCBT-2R5GL+

Outline Drawing




PCB Land Pattern



Outline Dimensions (inch mm)

A	B	C	D	E	F
.166	.150	.155	.100	.037	.025
4.22	3.81	3.94	2.54	0.94	0.64
G	H	J	K	L	wt
.012	.060	.184	.030	0.004	grams
0.30	1.52	4.67	0.76	0.10	0.10

Demo Board MCL P/N: TB-268 Suggested PCB Layout (PL-146)



NOTES:




1. COPLANAR WAVEGUIDE PARAMETERS ARE SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS 0.020 ± 0.0015 ; COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH AND GAP MAY NEED TO BE MODIFIED.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.

■ DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER).

■ DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK.




Typical Performance Data

Frequency (MHz)	INSERTION LOSS (dB)	VSWR (:1)		Isolation 0 mA	
		RF	RF&DC	RF-DC	RF&DC-DC
20.00	0.26	1.13	1.11	59.24	58.93
50.00	0.24	1.05	1.04	59.60	75.37
100.00	0.22	1.02	1.02	69.83	72.61
500.00	0.28	1.02	1.01	51.83	51.15
1000.00	0.43	1.04	1.04	40.89	38.59
1500.00	0.64	1.06	1.08	35.46	31.24
2000.00	0.72	1.04	1.11	33.88	26.97
2200.00	0.74	1.04	1.13	33.78	25.75
2400.00	0.75	1.03	1.14	33.55	24.74
2500.00	0.75	1.03	1.14	33.30	24.28




Typical Performance Data

FREQUENCY (MHz)	INSERTION LOSS (dB)	VSWR (:1)		ISOLATION 0mA (dB)	
		RF	RF& DC	RF-DC	RF& DC-DC
20	0.26	1.13	1.11	59.24	58.93
30	0.24	1.08	1.07	64.71	65.30
40	0.23	1.06	1.05	71.63	70.39
50	0.24	1.05	1.04	59.60	75.37
60	0.22	1.04	1.03	66.16	78.33
70	0.22	1.03	1.03	75.55	78.99
80	0.22	1.03	1.03	71.86	76.64
90	0.22	1.03	1.02	72.41	74.82
100	0.22	1.02	1.02	69.83	72.61
150	0.22	1.02	1.02	63.37	67.07
200	0.23	1.02	1.01	62.23	63.67
250	0.24	1.02	1.01	60.64	60.71
300	0.25	1.02	1.01	57.72	58.48
350	0.25	1.01	1.01	56.39	56.47
400	0.26	1.02	1.01	54.74	54.58
450	0.27	1.02	1.01	53.29	52.83
500	0.28	1.02	1.01	51.83	51.15
550	0.29	1.02	1.01	50.47	49.58
600	0.30	1.02	1.01	49.15	48.07
650	0.31	1.02	1.01	47.94	46.66
700	0.33	1.02	1.01	46.79	45.32
750	0.36	1.02	1.01	45.66	44.07
800	0.39	1.02	1.02	44.63	42.85
850	0.39	1.02	1.03	43.62	41.71
900	0.40	1.03	1.03	42.65	40.63
950	0.41	1.03	1.03	41.74	39.58
1000	0.43	1.04	1.04	40.89	38.59
1050	0.45	1.04	1.04	40.10	37.65
1100	0.47	1.04	1.05	39.38	36.76
1150	0.50	1.05	1.05	38.71	35.91
1200	0.52	1.05	1.05	38.10	35.13
1250	0.55	1.05	1.06	37.54	34.37
1300	0.57	1.05	1.06	37.04	33.68
1350	0.59	1.05	1.07	36.57	33.01
1400	0.61	1.05	1.07	36.16	32.39
1450	0.63	1.05	1.08	35.80	31.80
1500	0.64	1.06	1.08	35.46	31.24
1550	0.65	1.06	1.09	35.19	30.71
1600	0.67	1.06	1.09	34.94	30.21
1650	0.68	1.06	1.09	34.70	29.74
1700	0.69	1.05	1.09	34.51	29.29
1750	0.70	1.05	1.10	34.36	28.85
1800	0.70	1.05	1.10	34.21	28.44
1850	0.71	1.05	1.10	34.11	28.05
1900	0.72	1.05	1.11	33.99	27.68
1950	0.72	1.05	1.11	33.93	27.32
2000	0.72	1.04	1.11	33.88	26.97
2050	0.73	1.04	1.12	33.86	26.64
2100	0.73	1.04	1.12	33.84	26.33
2150	0.73	1.04	1.12	33.82	26.04
2200	0.74	1.04	1.13	33.78	25.75
2250	0.74	1.03	1.13	33.75	25.48
2300	0.74	1.03	1.13	33.71	25.23
2350	0.74	1.03	1.13	33.64	24.98
2400	0.75	1.03	1.14	33.55	24.74
2450	0.75	1.03	1.14	33.44	24.51
2500	0.75	1.03	1.14	33.30	24.28

Typical Performance Curves

Outline Dimensions

GU1840



CASE #	A	B	C	D	E	F	G	H	J	K	L	WT.GRAMS
GU1840	.166 (4.22)	.150 (3.81)	.155 (3.94)	.100 (2.54)	.037 (.94)	.025 (.64)	.012 (.30)	.060 (1.52)	.184 (4.67)	.030 (.76)	.004 (0.10)	.10

Dimensions are in inches (mm). Tolerances: 2 Pl. ± .01; 3 Pl. ± .005

Notes:

1. Open style, Ceramic Base.
2. Termination finish: Palladium Silver.
3. Must be isolated from external conductors on mounting surface. Suggested solder mask area is .025 x .025.
At Mini-Circuits option via may be removed.
4. Top-Hat total thickness: .013 inches MAX.
5. Orientation Dot on Top Hat corresponds to Pin #1.




P.O. Box 350186, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site




The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com

RF/IF MICROWAVE COMPONENTS

Tape & Reel Packaging TR-F77



Note: The shape of the pocket may differ



Note: The location and shape of the metallization may differ

Applicable Case Styles

GU1604, GU1804, GU2644,
TT1618-2

Applicable Case Styles

MZ4532C, NM1812C,
NM1812C-1, NM1812C-2,
NM1812C-3, NM1812C-5,
NM1812C-6, NM3237

Tape Width, mm	Device Cavity Pitch, mm	Reel Size, inches	Devices per Reel	
12	8	7	Small quantity standards (see note)	20
				50
				100
				200
				500
				1000
		13	Standard	2000

Note: Please Consult individual model data sheet to determine device per reel availability.

Mini-Circuits carrier tape materials provide protection from ESD (Electro-Static Discharge) during handling and transportation. Tapes are static dissipative and comply with industry standards EIA-481/EIA-541.

Go to: www.minicircuits.com/pages/pdfs/tape.pdf




INTERNET <http://www.minicircuits.com>

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661


Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010

Mini-Circuits ISO 9001 & ISO 14001 Certified



REVISIONS					
REV	ECN No.	DESCRIPTION	DATE	DR	AUTH
B	M102713	ADDED "...WITH SMOBC"	01/12/06	GF	IL
C	M103775	.010 uF WAS .010 mF	03/01/06	MMG	DJ
D	M154947	CHANGED PIN1 & PIN CONNECTION	02/03/16	ITG	DJ
E	M167305	CHANGED CASE STYLE & PIN CONNECT.	04/18/18	ITG	IG


SUGGESTED MOUNTING CONFIGURATION FOR
GU1604 CASE STYLE, "04BT01" PIN CONNECTION



CAPACITOR C1: .010 uF, 0603 SIZE

NOTES:

1. COPLANAR WAVEGUIDE PARAMETERS ARE SHOWN FOR ROGERS R04350B WITH DIELECTRIC THICKNESS 0.020 ± 0.0015 ; COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH AND GAP MAY NEED TO BE MODIFIED.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.

 DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER).

 DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK.

UNLESS OTHERWISE SPECIFIED	INITIALS		DATE
DIMENSIONS ARE IN INCHES TOLERANCES ON: 2 PL DECIMALS \pm 3 PL DECIMALS \pm .005 ANGLES \pm FRACTIONS \pm	DRAWN	AV	10/13/03
	CHECKED	IL	10/23/03
	APPROVED	DJ	10/23/03




Mini-Circuits® 13 Neptune Avenue
Brooklyn NY 11235

PL, 04BT01, GU1604, TCBT, TB-268


Mini-Circuits® THIS DOCUMENT AND ITS CONTENTS ARE THE PROPERTY OF MINI-CIRCUITS. EXCEPT FOR USE EXPRESSLY GRANTED, IN WRITING, TO ITS VENDORS, VENDEE AND THE UNITED STATES GOVERNMENT, MINI-CIRCUITS RESERVES ALL PROPRIETARY DESIGN, USE, MANUFACTURING AND REPRODUCTION RIGHTS THERETO. THESE CONTENTS SHALL NOT BE USED, DUPLICATED OR DISCLOSED TO ANY OUTSIDE PARTY, IN WHOLE OR IN PART, WITHOUT WRITTEN PERMISSION OF MINI-CIRCUITS.			
ASHEETA1.DWG REV:A DATE:01/12/95			

SIZE	CODE IDENT	DRAWING NO:	REV:
A	15542	98-PL-146	E
FILE:	98PL146	SCALE:	10:1
		SHEET:	1 OF 1

Evaluation Board and Circuit




TB-268



Schematic Diagram

Notes:

1. SMA Female connectors.
2. PCB Material: Rogers R04350 or equivalent, Dielectric Constant=3.5, Thickness=.020 inch.

 **Mini-Circuits®**



All Mini-Circuits products are manufactured under exacting quality assurance and control standards, and are capable of meeting published specifications after being subjected to any or all of the following physical and environmental test.

Specification	Test/Inspection Condition	Reference/Spec
Operating Temperature	-40° to 85°C Ambient Environment	Individual Model Data Sheet
Storage Temperature	-55° to 100° C Ambient Environment	Individual Model Data Sheet
Humidity	90 to 95% RH, 240 hours, 50°C	MIL-STD-202, Method 103, Condition A, Except 50°C and end-point electrical test done within 12 hours
Thermal Shock	-55° to 100°C, 100 cycles	MIL-STD-202, Method 107, Condition A-3, except +100°C
Solder Reflow Heat	Sn-Pb Eutetic Process: 225°C peak Pb-Free Process 245° - 250°C peak	J-STD-020, Table 4-1, 4-2 and 5-2, Figure 5-1
Solderability	10X Magnification	J-STD-002, 95% Coverage
Vibration (High Frequency)	20g peak, 10-2000 Hz, 12 times in each of three perpendicular directions (total 36)	MIL-STD-202, Method 204, Condition D
Mechanical Shock	50g, 11 ms, 1/2-sine, 18 shocks: 3 each direction, each of 3 axes	MIL-STD-202, Method 213, Condition A
Marking Resistance to Solvents	Isopropyl alcohol + mineral spirits at 25°C; terpene defluxer at 25°C; distilled water + proylene glycol monomethyl ether + monoethanolamine at 63°C to 70°C	MIL-STD-202, Method 215