

DC Pass

NON-CATALOG

Power Splitter/Combiner

ZC8PD-900

8 Way-0° 50Ω 800 to 900 MHz

Maximum Ratings


Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
Power Input (as a splitter)	10W max.
Internal Dissipation	0.875W max.
DC Current	3.2A(400mA for each port)

Permanent damage may occur if any of these limits are exceeded.

Coaxial Connections

SUM PORT	S
PORT 1,2,3,4,5,6,7,8	1,2,3,4,5,6,7,8

Outline Drawing



Outline Dimensions (inch/mm)

A	B	C	D	E	F
4.76	3.00	.53	.150	4.610	1.500
120.90	76.20	13.46	3.81	117.09	38.10


G	H	J	K	L	wt
.125	.38	.25	.88	.50	grams
3.18	9.65	6.35	22.35	12.70	201

Features

- low insertion loss, 0.4 dB typ.
- high isolation, 30 dB typ.
- up to 10W power input as splitter
- rugged shielded case

Applications

- cellular
- communication systems
- signal processing



CASE STYLE: AB186

Connectors	Model
SMA	ZC8PD-900-S

HT-Series
Tight Spot
SMA Wrench
From \$24.95

Electrical Specifications


FREQ. RANGE (MHz)	ISOLATION (dB)		INSERTION LOSS (dB) ABOVE 9.0 dB		PHASE UNBALANCE (Degrees)	AMPLITUDE UNBALANCE (dB)
$f_L - f_U$	Typ.	Min.	Typ.	Max.	Max.	Max.
800-900	30	20	0.4	0.7	5.0	0.4

Typical Performance Data


Freq. (MHz)	Total Loss ¹ (dB)						Amplitude Unbalance (dB)				Isolation (dB)			VSWR		
	S-1	S-2	S-3	S-4	S-6	S-8	1-2	1-7	3-4	5-7	1-2	1-7	3-4	S	1	8
800.00	9.32	9.31	9.33	9.30	9.25	9.25	0.16	28.16	36.50	25.78	29.05	1.15	1.04	1.05		
804.00	9.32	9.31	9.34	9.30	9.26	9.25	0.24	28.68	36.78	26.24	29.29	1.14	1.04	1.05		
808.00	9.32	9.31	9.34	9.30	9.26	9.25	0.26	29.24	37.14	26.70	29.51	1.14	1.04	1.05		
814.00	9.32	9.33	9.34	9.31	9.26	9.25	0.24	30.14	37.66	27.47	29.90	1.13	1.04	1.05		
820.00	9.34	9.33	9.36	9.32	9.27	9.27	0.09	31.02	38.25	28.33	30.29	1.12	1.04	1.04		
826.00	9.35	9.35	9.38	9.35	9.30	9.29	0.09	31.89	38.81	29.19	30.69	1.11	1.04	1.04		
832.00	9.38	9.38	9.41	9.37	9.33	9.31	0.10	32.66	39.46	30.23	31.12	1.11	1.04	1.04		
838.00	9.40	9.40	9.44	9.40	9.34	9.33	0.11	33.27	40.03	31.29	31.56	1.10	1.04	1.04		
846.00	9.40	9.41	9.44	9.40	9.35	9.34	0.10	33.63	40.79	32.70	32.13	1.09	1.04	1.04		
855.00	9.38	9.37	9.41	9.37	9.31	9.30	0.11	33.23	41.55	33.75	32.77	1.09	1.04	1.04		
867.00	9.32	9.32	9.35	9.31	9.26	9.24	0.11	31.80	42.17	33.40	33.59	1.08	1.03	1.04		
879.00	9.32	9.32	9.37	9.31	9.27	9.26	0.11	30.15	42.09	33.02	34.47	1.07	1.03	1.03		
888.00	9.33	9.35	9.40	9.33	9.28	9.28	0.12	28.93	41.64	31.55	35.13	1.07	1.03	1.03		
894.00	9.33	9.34	9.41	9.34	9.27	9.29	0.13	28.16	41.19	30.80	35.51	1.07	1.03	1.03		
900.00	9.33	9.34	9.42	9.34	9.27	9.27	0.15	27.41	40.63	30.00	35.87	1.07	1.03	1.03		

ZC8PD-900
TOTAL LOSS


1. Total Loss = Insertion Loss + 9dB splitter loss.




ZC8PD-900
ISOLATION



ZC8PD-900
VSWR



electrical schematic



Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

REV. D
M160892
ZC8PD-900
HY/TD/CP/AM
170512

8 Way-0° Power Splitter/Combiner

ZC8PD-900

Typical Performance Data

FREQ. (MHz)	TOTAL LOSS ¹ (dB)						AMP. UNBAL. (dB)	ISOLATION (dB)				PHASE UNBAL. (deg.)	FREQ. (MHz)	VSWR (:1)		
	S-1	S-2	S-3	S-4	S-6	S-8		1-2	1-8	3-4	6-7			S	1	8
800.0	9.32	9.31	9.33	9.30	9.25	9.25	0.16	28.16	36.50	25.78	29.05	2.64	800.0	1.15	1.04	1.05
802.0	9.33	9.32	9.35	9.30	9.26	9.24	0.24	28.43	36.62	26.02	29.17	2.61	802.0	1.14	1.04	1.05
804.0	9.32	9.31	9.34	9.30	9.26	9.25	0.24	28.68	36.78	26.24	29.29	2.61	804.0	1.14	1.04	1.05
806.0	9.32	9.32	9.34	9.30	9.26	9.25	0.27	28.97	36.94	26.45	29.41	2.65	806.0	1.14	1.04	1.05
808.0	9.32	9.31	9.34	9.30	9.26	9.25	0.26	29.24	37.14	26.70	29.51	2.65	808.0	1.14	1.04	1.05
810.0	9.33	9.32	9.35	9.31	9.26	9.25	0.16	29.54	37.28	26.94	29.63	2.66	810.0	1.13	1.04	1.05
812.0	9.33	9.32	9.34	9.30	9.25	9.24	0.22	29.83	37.41	27.19	29.78	2.65	812.0	1.13	1.04	1.05
814.0	9.32	9.33	9.34	9.31	9.26	9.25	0.24	30.14	37.66	27.47	29.90	2.64	814.0	1.13	1.04	1.05
816.0	9.33	9.32	9.36	9.30	9.27	9.25	0.13	30.41	37.84	27.74	30.02	2.67	816.0	1.13	1.04	1.05
818.0	9.33	9.32	9.35	9.33	9.27	9.27	0.08	30.75	38.06	28.01	30.16	2.75	818.0	1.12	1.04	1.04
820.0	9.34	9.33	9.36	9.32	9.27	9.27	0.09	31.02	38.25	28.33	30.29	2.70	820.0	1.12	1.04	1.04
822.0	9.34	9.34	9.37	9.33	9.29	9.28	0.09	31.30	38.41	28.61	30.42	2.66	822.0	1.12	1.04	1.04
824.0	9.35	9.35	9.38	9.35	9.30	9.28	0.10	31.62	38.61	28.90	30.56	2.75	824.0	1.12	1.04	1.04
826.0	9.35	9.35	9.38	9.35	9.30	9.29	0.09	31.89	38.81	29.19	30.69	2.79	826.0	1.11	1.04	1.04
828.0	9.37	9.36	9.39	9.35	9.30	9.30	0.09	32.18	39.02	29.50	30.82	2.77	828.0	1.11	1.04	1.04
830.0	9.36	9.37	9.40	9.35	9.30	9.30	0.10	32.42	39.23	29.85	30.98	2.73	830.0	1.11	1.04	1.04
832.0	9.38	9.38	9.41	9.37	9.33	9.31	0.10	32.66	39.46	30.23	31.12	2.69	832.0	1.11	1.04	1.04
834.0	9.38	9.39	9.42	9.37	9.34	9.32	0.10	32.92	39.65	30.58	31.25	2.76	834.0	1.11	1.04	1.04
836.0	9.40	9.40	9.43	9.39	9.35	9.33	0.10	33.13	39.82	30.92	31.46	2.79	836.0	1.10	1.04	1.04
838.0	9.40	9.40	9.44	9.40	9.34	9.33	0.11	33.27	40.03	31.29	31.56	2.70	838.0	1.10	1.04	1.04
840.0	9.40	9.41	9.44	9.40	9.35	9.33	0.12	33.44	40.27	31.62	31.69	2.71	840.0	1.10	1.04	1.04
843.0	9.41	9.41	9.45	9.40	9.36	9.34	0.11	33.55	40.60	32.18	31.93	2.71	843.0	1.10	1.04	1.04
846.0	9.40	9.41	9.44	9.40	9.35	9.34	0.10	33.63	40.79	32.70	32.13	2.80	846.0	1.09	1.04	1.04
849.0	9.39	9.39	9.44	9.40	9.35	9.33	0.11	33.57	41.06	33.12	32.35	2.77	849.0	1.09	1.04	1.04
852.0	9.38	9.38	9.42	9.38	9.33	9.32	0.10	33.42	41.33	33.47	32.53	2.80	852.0	1.09	1.04	1.04
855.0	9.38	9.37	9.41	9.37	9.31	9.30	0.11	33.23	41.55	33.75	32.77	2.91	855.0	1.09	1.04	1.04
858.0	9.34	9.35	9.39	9.35	9.30	9.28	0.10	32.95	41.76	33.91	32.96	2.92	858.0	1.09	1.04	1.04
861.0	9.33	9.34	9.37	9.33	9.29	9.27	0.10	32.59	41.95	33.78	33.16	2.92	861.0	1.08	1.03	1.04
864.0	9.32	9.31	9.36	9.31	9.27	9.25	0.11	32.22	42.01	33.50	33.38	2.88	864.0	1.08	1.03	1.04
867.0	9.32	9.32	9.35	9.31	9.26	9.24	0.11	31.80	42.17	33.40	33.59	2.93	867.0	1.08	1.03	1.04
870.0	9.30	9.31	9.36	9.31	9.26	9.24	0.12	31.39	42.18	33.36	33.79	2.94	870.0	1.08	1.03	1.03
873.0	9.30	9.31	9.36	9.31	9.26	9.24	0.12	30.96	42.26	33.22	34.03	2.96	873.0	1.08	1.03	1.03
876.0	9.31	9.31	9.36	9.31	9.26	9.24	0.12	30.57	42.17	32.97	34.25	2.94	876.0	1.08	1.03	1.03
879.0	9.32	9.32	9.37	9.31	9.27	9.26	0.11	30.15	42.09	33.02	34.47	2.98	879.0	1.07	1.03	1.03
882.0	9.33	9.33	9.38	9.33	9.28	9.27	0.11	29.72	42.01	32.27	34.73	2.95	882.0	1.07	1.03	1.03
885.0	9.33	9.35	9.40	9.34	9.29	9.27	0.14	29.35	41.85	31.88	34.90	2.94	885.0	1.07	1.03	1.03
888.0	9.33	9.35	9.40	9.33	9.28	9.28	0.12	28.93	41.64	31.55	35.13	3.00	888.0	1.07	1.03	1.03
891.0	9.34	9.35	9.42	9.34	9.28	9.29	0.14	28.55	41.46	31.16	35.34	3.12	891.0	1.07	1.03	1.03
894.0	9.33	9.34	9.41	9.34	9.27	9.29	0.13	28.16	41.19	30.80	35.51	3.13	894.0	1.07	1.03	1.03
897.0	9.34	9.35	9.42	9.33	9.27	9.29	0.15	27.78	40.94	30.38	35.65	3.02	897.0	1.07	1.03	1.03
900.0	9.33	9.34	9.42	9.34	9.27	9.27	0.15	27.41	40.63	30.00	35.87	3.00	900.0	1.07	1.03	1.03

¹ Total Loss = Insertion Loss+ 9dB Splitter Loss



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED • RoHS compliant
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see








REV. X2
ZC8PD-900
100627
Page 1 of 1

8 Way-0° Power Splitter/Combiner

ZC8PD-900

Typical Performance Curves




REV. X2
ZC8PD-900
100627
Page 1 of 1



Mini-Circuits®
IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS 9100 CERTIFIED • RoHS compliant
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661
The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



Outline Dimensions



CASE #	A	B	C	D	E	F	G	H	J	K	L	WT. GRAM
AB186	4.76 (120.90)	3.00 (76.20)	.53 (13.46)	.150 (3.81)	4.610 (117.09)	1.500 (38.10)	.125 (3.18)	.38 (9.65)	.25 (6.35)	.88 (22.35)	.50 (12.70)	201

Dimensions are in inches (mm). Tolerances: 2Pl. $\pm .03$; 3Pl. $\pm .015$

Notes:

- Case material: Aluminum alloy.
- Case finish:
For RoHS Case Styles: Clear chemical conversion coating, non-chrome or trivalent chrome based.



INTERNET <http://www.minicircuits.com>

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010

Mini-Circuits ISO 9001 & ISO 14001 Certified



All Mini-Circuits products are manufactured under exacting quality assurance and control standards, and are capable of meeting published specifications after being subjected to any or all of the following physical and environmental test.

Specification	Test/Inspection Condition	Reference/Spec
Operating Temperature	-55° to 100°C Ambient Environment	Individual Model Data Sheet
Storage Temperature	-55° to 100° C Ambient Environment	Individual Model Data Sheet
Barometric Pressure	100,000 Feet	MIL-STD-202, Method 105, Condition D
Humidity	90% RH, 65°C Units may require bake-out after humidity to restore full performance.	MIL-STD-202, Method 103
Thermal Shock	-65° to 125°C, 5 cycles	MIL-STD-202, Method 107, Condition B
Vibration (High Frequency)	20g peak, 10-2000 Hz, 12 times in each of three perpendicular directions (total 36)	MIL-STD-202, Method 204, Condition D
Mechanical Shock	100g, 6ms sawtooth, 3 shocks each direction 3 axes (total 18)	MIL-STD-202, Method 213, Condition I