

Coaxial Bi-Directional Coupler

50Ω Up to 10W 800 to 900 MHz

ZFBDC20-900HP



Generic photo used for illustration purposes only

CASE STYLE: J17

Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
Permanent damage may occur if any of these limits are exceeded.	

Coaxial Connections

INPUT	2
OUTPUT	3
COUPLED (forward)	1
COUPLED (reverse)	S

Features

- very low mainline loss, 0.1 dB typ.
- excellent directivity, 28 dB typ.
- excellent VSWR, 1.1: typ.
- high power operation, 10W

Applications

- VSWR measurement
- power monitoring of cellular transmitters
- power levelling


Connectors	Model
SMA	ZFBDC20-900HP
BRACKET (OPTION "B")	

Bi-Directional Coupler Electrical Specifications

FREQ. (MHz)	COUPLING (dB)		MAINLINE LOSS ¹ (dB)		DIRECTIVITY (dB)		VSWR (:1)	POWER INPUT (W)
f_c - f_u	Nom.	Flatness	Typ.	Max.	Typ.	Min.	Typ.	Max.
800-900	20.7±0.6	±0.6	0.1	0.4	28	20	1.1	10

1. Mainline loss includes theoretical power loss at coupled port.

Outline Drawing



Outline Dimensions (inch mm)




A	B	C	D	E	F	G
1.25	1.25	.75	.63	.38	1.000	.125 1.0
31.75	31.75	19.05	16.00	9.65	25.40	3.18 25.

J	K	L	M	N	P	Q
--	--	.125	1.688	2.18	.75	.07 gra
--	--	3.18	42.88	55.37	19.05	1.78 7!


For option B with N-Type connectors, dimension "C" increases to 0.94 inches.

Typical Performance Data

Frequency (MHz)	Mainline Loss (dB)		Coupling (dB)		Directivity (dB)		Return Loss (dB)			
	In-Out	In-Cpl Fwd	Out-Cpl Rev	Out-Cpl Fwd	In-Cpl Rev	In	Out	Cpl Fwd	Cpl Rev	
800.00	0.13	20.24	20.31	27.20	24.84	23.29	23.46	27.07	27.50	
811.25	0.11	20.20	20.24	26.84	25.58	23.46	23.61	27.44	27.82	
830.00	0.13	20.13	20.19	26.62	25.41	23.69	23.88	28.08	28.28	
841.25	0.13	20.08	20.15	26.22	25.63	23.80	23.97	28.43	28.53	
848.75	0.13	20.05	20.11	26.10	25.73	23.91	24.10	28.69	28.74	
860.00	0.13	20.00	20.07	26.12	26.00	24.05	24.22	29.09	29.10	
871.25	0.13	19.96	20.03	25.83	26.34	24.16	24.39	29.54	29.37	
875.00	0.13	19.95	20.00	25.57	26.37	24.20	24.44	29.58	29.44	
890.00	0.13	19.89	19.96	25.56	26.84	24.38	24.62	30.18	29.85	
901.25	0.13	19.86	19.91	25.69	26.80	24.47	24.70	30.59	30.08	



Electrical Schematic



Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCStore/terms.jsp



www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

REV. D
ECO-015369
ZFBDC-20-900HP
WP/TD/CP/AM
211018
Page 1 of 1

Bi-Directional Coupler

ZFBDC20-900HP

Typical Performance Data

FREQ. (MHz)	INSERTION LOSS (dB) IN-OUT	COUPLING (dB)		DIRECTIVITY (dB)		RETURN LOSS (dB)			
		IN-FWD	OUT-REV	IN-REV	OUT-FWD	IN	OUT	FWD	REV
800.00	0.13	20.24	20.31	24.84	27.20	23.29	23.46	27.07	27.50
811.25	0.11	20.20	20.24	25.58	26.84	23.46	23.61	27.44	27.82
830.00	0.13	20.13	20.19	25.41	26.62	23.69	23.88	28.08	28.28
841.25	0.13	20.08	20.15	25.63	26.22	23.80	23.97	28.43	28.53
848.75	0.13	20.05	20.11	25.73	26.10	23.91	24.10	28.69	28.74
860.00	0.13	20.00	20.07	26.00	26.12	24.05	24.22	29.09	29.10
871.25	0.13	19.96	20.03	26.34	25.83	24.16	24.39	29.54	29.37
875.00	0.13	19.95	20.00	26.37	25.57	24.20	24.44	29.58	29.44
890.00	0.13	19.89	19.96	26.84	25.56	24.38	24.62	30.18	29.85
901.25	0.13	19.86	19.91	26.80	25.69	24.47	24.70	30.59	30.08

REV. X1
ZFBDC20-900HP
070405
Page 1 of 1







Mini-Circuits®
IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED • RoHS compliant
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661
The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see




Bi-Directional Coupler

Typical Performance Curves

ZFBDC20-900HP



Outline Dimensions



CASE#	A	B	C	D	E	F	G	H	J	K	L	M	N
J17	1.25 (31.75)	1.25 (31.75)	.75 (19.05)	.63 (16.00)	.38 (9.65)	1.000 (25.40)	.125 (3.18)	1.000 (25.40)	--	--	.125 (3.18)	1.688 (42.88)	2.18 (55.37)

CASE#	P	Q	WT. GRAMS
J17	.75 (19.05)	.07 (1.78)	75.0

Dimensions are in inches (mm). Tolerances: 2 Pl. $\pm .03$; 3 Pl. $\pm .015$

Notes:

- Case material: Aluminum alloy.
- Case finish:
For RoHS Case Styles: Clear chemical conversion coating, non-chrome or trivalent chrome based.
- Mounting bracket available on request. Add suffix B to part number
- For bracket version, option B, dimension "C" changes from .75 to .94 inches when connectors are type N.



All Mini-Circuits products are manufactured under exacting quality assurance and control standards, and are capable of meeting published specifications after being subjected to any or all of the following physical and environmental test.

Specification	Test/Inspection Condition	Reference/Spec
Operating Temperature	-55° to 100°C Ambient Environment	Individual Model Data Sheet
Storage Temperature	-55° to 100° C Ambient Environment	Individual Model Data Sheet
Barometric Pressure	100,000 Feet	MIL-STD-202, Method 105, Condition D
Humidity	90% RH, 65°C Units may require bake-out after humidity to restore full performance.	MIL-STD-202, Method 103
Thermal Shock	-65° to 125°C, 5 cycles	MIL-STD-202, Method 107, Condition B
Vibration (High Frequency)	20g peak, 10-2000 Hz, 12 times in each of three perpendicular directions (total 36)	MIL-STD-202, Method 204, Condition D
Mechanical Shock	100g, 6ms sawtooth, 3 shocks each direction 3 axes (total 18)	MIL-STD-202, Method 213, Condition I