

Engineering Development Model

Power Splitter/Combiner

ZFSCJ-ED13132

2 Way-180°

Important Note

This model has been designed, built and tested in our engineering department. Performance data represents model capability.

At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.



Please click "Back", and then click "Contact Us" for Applications support.


CASE STYLE : 99-01-1299

ELECTRICAL SPECIFICATIONS 50Ω @ +25°C				
Parameter		Min.	Typ.	Max. Units
Frequency		180		580 MHz
Isolation	180 - 580 MHz		25	
			25	
Insertion Loss Above 3.0 dB	180 - 580 MHz		0.54	
Phase Unbalance	180 - 580 MHz		177.50	
Amplitude Unbalance	180 - 580 MHz		0.30	
VSWR	SUM Port		1.20	
	OUT Ports		1.40	

MAXIMUM RATINGS	
Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C

PIN CONNECTIONS	
Sum Port	S
Port 1	1
Port 2	2

Functional Diagram



2 Way-180° Power Splitter/Combiner

ZFSCJ-ED13132

Typical Performance Data






FREQ. (MHz)	TOTAL LOSS ¹ (dB)		AMP. UNBAL. (dB)	ISOLATION (dB) 1-2	PHASE UNBAL. (deg.)	FREQ. (MHz)	VSWR (:1)		
	S-1	S-2					S	1	2
180.0	3.52	3.84	0.32	15.44	178.50	180.0	1.50	1.53	1.66
200.0	3.37	3.60	0.23	16.84	179.34	200.0	1.40	1.36	1.29
220.0	3.37	3.41	0.05	18.76	178.55	220.0	1.32	1.22	1.07
225.0	3.38	3.38	0.00	19.33	178.48	225.0	1.31	1.19	1.06
235.0	3.41	3.33	0.08	20.60	178.41	235.0	1.30	1.14	1.10
245.0	3.45	3.30	0.15	22.09	178.37	245.0	1.29	1.13	1.16
255.0	3.48	3.28	0.20	23.84	178.31	255.0	1.28	1.15	1.21
265.0	3.51	3.27	0.24	25.96	178.19	265.0	1.27	1.20	1.25
275.0	3.54	3.27	0.27	28.59	178.00	275.0	1.26	1.25	1.27
285.0	3.56	3.27	0.29	32.03	177.74	285.0	1.23	1.31	1.29
295.0	3.58	3.26	0.31	36.17	177.44	295.0	1.20	1.36	1.29
305.0	3.60	3.26	0.33	37.48	177.11	305.0	1.17	1.40	1.29
315.0	3.61	3.27	0.35	34.01	176.81	315.0	1.13	1.44	1.29
325.0	3.63	3.27	0.36	30.72	176.59	325.0	1.09	1.46	1.30
335.0	3.65	3.28	0.36	28.33	176.48	335.0	1.06	1.48	1.30
345.0	3.67	3.30	0.36	26.57	176.48	345.0	1.06	1.49	1.32
355.0	3.68	3.33	0.35	25.25	176.62	355.0	1.08	1.50	1.35
365.0	3.69	3.37	0.32	24.23	176.92	365.0	1.11	1.50	1.38
375.0	3.69	3.41	0.28	23.47	177.40	375.0	1.14	1.50	1.42
385.0	3.69	3.47	0.22	22.90	178.00	385.0	1.16	1.49	1.46
395.0	3.67	3.53	0.14	22.49	178.69	395.0	1.17	1.48	1.51
405.0	3.64	3.59	0.05	22.21	179.45	405.0	1.16	1.47	1.56
415.0	3.59	3.65	0.06	22.06	179.77	415.0	1.15	1.46	1.60
425.0	3.54	3.72	0.18	22.01	179.02	425.0	1.13	1.46	1.65
435.0	3.49	3.78	0.30	22.04	178.37	435.0	1.09	1.45	1.69
445.0	3.44	3.84	0.40	22.20	177.84	445.0	1.05	1.44	1.73
450.0	3.42	3.87	0.45	22.30	177.62	450.0	1.03	1.44	1.75
455.0	3.40	3.90	0.50	22.42	177.44	455.0	1.01	1.44	1.77
460.0	3.39	3.92	0.53	22.56	177.29	460.0	1.01	1.43	1.78
465.0	3.38	3.94	0.56	22.72	177.17	465.0	1.03	1.43	1.80
470.0	3.37	3.96	0.59	22.90	177.07	470.0	1.05	1.42	1.81
480.0	3.37	3.98	0.61	23.35	176.96	480.0	1.09	1.41	1.82
500.0	3.42	3.95	0.53	24.61	176.88	500.0	1.16	1.37	1.80
520.0	3.51	3.84	0.32	26.61	176.64	520.0	1.21	1.33	1.71
540.0	3.62	3.66	0.05	29.93	175.89	540.0	1.21	1.28	1.55
560.0	3.68	3.49	0.19	34.53	174.62	560.0	1.15	1.23	1.34
580.0	3.69	3.39	0.30	31.15	173.17	580.0	1.05	1.19	1.13

¹ Total Loss = Insertion Loss+ 9dB Splitter Loss

2 Way-180° Power Splitter/Combiner

ZFSCJ-ED13132

Typical Performance Curves





All Mini-Circuits products are manufactured under exacting quality assurance and control standards, and are capable of meeting published specifications after being subjected to any or all of the following physical and environmental test.

Specification	Test/Inspection Condition	Reference/Spec
Operating Temperature	-55° to 100°C Ambient Environment	Individual Model Data Sheet
Storage Temperature	-55° to 100° C Ambient Environment	Individual Model Data Sheet
Barometric Pressure	100,000 Feet	MIL-STD-202, Method 105, Condition D
Humidity	90% RH, 65°C Units may require bake-out after humidity to restore full performance.	MIL-STD-202, Method 103
Thermal Shock	-65° to 125°C, 5 cycles	MIL-STD-202, Method 107, Condition B
Vibration (High Frequency)	20g peak, 10-2000 Hz, 12 times in each of three perpendicular directions (total 36)	MIL-STD-202, Method 204, Condition D
Mechanical Shock	100g, 6ms sawtooth, 3 shocks each direction 3 axes (total 18)	MIL-STD-202, Method 213, Condition I