

Suspended Substrate Stripline Filters and Multiplexers

50Ω DC to 26 GHz

The Big Deal

- Low insertion loss
- Ultra-wide passband width
- Fast roll-off with wide stopband
- Good power handling and temperature stability
- Passband up to 26 GHz
- Stopband up to 26.5 GHz can extend to 40 GHz



Product Overview

Mini-Circuits' Suspended Substrate Stripline filters offer low insertion loss by implementing printed circuit board suspended between two parallel ground planes, providing high Q. Low insertion loss combined with wide stopband makes them an excellent choice for wideband instruments and systems like ECM, ECCM, ELINT and ultra-broadband receivers.

Low pass, high pass, band pass, band stop, diplexer and multiplexer designs can be realized with this technology. Advanced filter design and construction can achieve stopband width greater than 6x the center frequency, and temperature stability will be better than other printed circuit realizations because the fields are mainly in the air rather than in a dielectric. The inside walls of the housing hold the circuit and prevent movement that could be caused by vibration or mechanical shock, making these designs excellent candidates for harsh operating environments.

Suspended substrate stripline filters can be realized in small form factors with high-quality, precise machining for applications where size is critical. Excellent repeatability across units is achieved through precise tuning and process control.

Key Features

Feature	Advantages
Low insertion loss	Low signal loss results in better SNR in receiver front end and better power delivery to antenna in transmitters
Fast roll-off	Higher selectivity results in better adjacent channel rejection and dynamic range
Wide stopband	Wide, spur-free stop band results in better receiver sensitivity
High power handling	Well suited for transmitter applications
Excellent temperature stability	Ensures minimal variation in electrical performance across temperature

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



Suspended substrate stripline High Pass Filter

50Ω 11000 to 24000 MHz

ZHSS-11G-S+



Generic photo used for illustration purposes only

CASE STYLE: RP2464

Connectors	Model
SMA-F	ZHSS-11G-S+

Electrical Specifications at 25°C

Parameter		F#	Frequency (MHz)	Min.	Typ.	Max.	Unit
Stop Band	Rejection Loss	DC-F1	DC - 6000	60	80	-	dB
		F1-F2	6000 - 8250	40	60	-	dB
		F2-F3	8250 - 9000	20	30	-	dB
Pass Band	Insertion Loss	F4-F5	11000 - 24000	-	1.5	2.5	dB
	VSWR	F4-F5	11000 - 24000	-	2.0	-	:1

Maximum Ratings


Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
RF Power Input	3 W @ 25°C

Permanent damage may occur if any of these limits are exceeded.


Typical Performance Data at 25°C

Frequency (MHz)	Insertion Loss (dB)	VSWR (:1)	Frequency (MHz)	Group Delay (ns)
25	113.99	1965.13	11000	0.45
100	123.79	1090.23	11500	0.37
1000	118.08	1767.40	12000	0.32
2000	91.77	441.02	12500	0.29
3000	98.42	533.53	13000	0.26
6000	82.82	186.23	13500	0.25
6500	82.11	105.48	14000	0.24
8250	59.74	67.43	14500	0.23
9000	40.03	44.32	15000	0.22
9275	30.17	32.18	15500	0.21
9500	21.79	23.26	16000	0.21
10050	3.41	3.01	16500	0.20
11000	0.82	1.34	17000	0.20
15000	0.39	1.14	17500	0.19
20000	0.57	1.43	18000	0.19
20200	0.58	1.44	20000	0.18
20500	0.57	1.44	21000	0.17
21000	0.56	1.38	22000	0.17
23000	0.58	1.33	23000	0.17
24000	0.95	1.87	24000	0.16

Functional Schematic







Typical Frequency Response



+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications



Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuits' applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp




www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

REV.A
ECO-005696
ZHSS-11G-S+
EDU3015
URJ
210107
Page 2 of 3

Coaxial Connections

PORT - 1	SMA-Female
PORT - 2	SMA-Female

Outline Drawing



Outline Dimensions ($\frac{\text{inch}}{\text{mm}}$)

A	B	C	D	E	F	G	H	J	K	Wt.
Max	Max	Max	-	-	-	-	-	-	-	grams
.70	.50	.50	.25	.25	.43	.350	.25	.170	.065	30
17.78	12.70	12.70	6.35	6.35	10.92	8.89	6.35	4.32	1.65	





Note: Please refer to case style drawing for details

Notes
A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

Typical Performance Data


FREQ.	Insertion Loss	Input Return Loss	Output Return Loss	FREQ.	Group Delay
(MHz)	(dB)	(dB)	(dB)	(MHz)	(ns)
25	113.99	0.01	0.01	11000	0.45
50	112.90	0.02	0.01	11250	0.40
150	119.33	0.01	0.01	11500	0.37
250	125.29	0.02	0.01	11750	0.35
750	115.04	0.01	0.03	12000	0.32
1250	121.26	0.01	0.01	12250	0.31
1500	106.47	0.02	0.01	12500	0.29
1750	106.19	0.01	0.00	12750	0.27
2000	91.77	0.03	0.04	13000	0.26
2250	100.14	0.05	0.05	13250	0.26
2500	105.40	0.02	0.06	13500	0.25
2750	104.78	0.05	0.05	13750	0.24
3000	98.42	0.04	0.03	14000	0.24
3250	95.14	0.05	0.05	14250	0.24
3500	88.89	0.08	0.06	14500	0.23
3750	96.62	0.08	0.07	14750	0.23
4000	89.55	0.10	0.09	15000	0.22
4250	92.36	0.09	0.08	15250	0.22
4500	87.82	0.10	0.10	15500	0.21
4750	88.51	0.10	0.08	15750	0.21
5000	85.74	0.09	0.10	16000	0.21
5250	85.01	0.10	0.09	16250	0.20
5300	85.95	0.11	0.10	16500	0.20
5500	85.11	0.10	0.10	16750	0.20
5750	84.43	0.12	0.10	17000	0.20
5800	82.40	0.12	0.13	17250	0.19
6000	82.82	0.11	0.09	17500	0.19
6250	83.60	0.14	0.12	17750	0.19
6450	81.14	0.12	0.14	18000	0.19
6500	82.11	0.17	0.16	18250	0.19
6650	87.23	0.16	0.21	18500	0.19
6700	84.44	0.16	0.15	18750	0.18
6900	88.32	0.17	0.20	19000	0.18
7000	89.05	0.19	0.19	19250	0.18
7050	84.46	0.19	0.21	19500	0.18
7100	83.89	0.21	0.21	19750	0.18
7700	85.70	0.23	0.21	20000	0.18
8000	72.69	0.24	0.23	20100	0.18
8250	63.73	0.27	0.26	20200	0.17
9000	40.03	0.40	0.39	20300	0.17
10000	4.32	5.02	4.75	20400	0.17
11000	0.82	16.60	16.72	20500	0.17
12000	0.84	11.99	11.97	20600	0.17
13000	0.92	9.92	9.81	20700	0.17
14000	0.62	12.87	12.98	20800	0.17
15000	0.39	22.28	23.51	20900	0.17
16000	0.35	34.12	35.27	21000	0.17
17000	0.36	28.75	30.78	21100	0.17
18000	0.36	32.72	29.95	21200	0.17
19000	0.43	19.23	19.02	21300	0.17
20000	0.57	14.15	14.97	21400	0.17
20500	0.57	14.00	14.82	21500	0.17
21000	0.56	14.80	15.85	21600	0.17
21500	0.52	17.06	18.55	21700	0.17
22000	0.46	23.25	25.55	21800	0.17
22500	0.47	26.58	27.60	22000	0.17
23000	0.58	16.31	16.94	22500	0.17
23500	0.76	11.79	12.57	23000	0.17
23750	0.88	10.50	11.23	23500	0.17
24000	0.95	9.72	10.36	24000	0.16

Typical Performance Curves



Outline Dimensions

RP2464



CASE#	A (Max)	B (Max)	C (Max)	D	E	F	G	H	J	K	WT. GRAMS
RP2464	.70 (17.8)	.50 (12.7)	.50 (12.7)	.25 (6.4)	.25 (6.4)	.43 (10.9)	.350 (8.89)	.25 (6.4)	.170 (4.32)	.065 (1.65)	30

Dimensions are in inches (mm). Tolerances: 2 Pl. $\pm .10$; 3 Pl. $\pm .015$

Notes:

1. Case material: Brass.
2. Case finish: Powder coated over silver plating
3. Refer to the individual model data sheet for the type of connectors available.



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site



Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com

RF/IF MICROWAVE COMPONENTS



All Mini-Circuits products are manufactured under exacting quality assurance and control standards, and are capable of meeting published specifications after being subjected to any or all of the following physical and environmental test.

Specification	Test/Inspection Condition	Reference/Spec
Operating Temperature	-55° to 100°C Ambient Environment	Individual Model Data Sheet
Storage Temperature	-55° to 100° C Ambient Environment	Individual Model Data Sheet
Humidity	90 to 95% RH, 40°C, 96 hours; Units may require bake-out after humidity to restore full performance.	MIL-STD-202, Method 103, Condition B
Thermal Shock	-55° to 100°C, 100 cycles	MIL-STD-202, Method 107, Condition A-3, except +100°C
Vibration (High Frequency)	20g peak, 10-2000 Hz, 12 times in each of three perpendicular directions (total 36)	MIL-STD-202, Method 204, Condition D
Mechanical Shock	50g, 11ms half-sine, 3 shocks each direction 3 axes (total 18)	MIL-STD-202, Method 213, Condition A