

Coaxial Low Noise Amplifier

ZQL-1900LNW+ ZQL-1900LNW

50Ω 1700 to 2000 MHz

Features

- Very low noise figure, 1.6 dB max.
- High IP3, +37 dBm typ.
- Rugged, shielded case

Applications

- PCS
- UMTS
- Mobile satellite service



Case Style: CW686

Connectors	Model
SMA	ZQL-1900LNW(+)

+RoHS Compliant


The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Electrical Specifications

Parameter	Condition (MHz)	Min.	Typ.	Max.	Units
Frequency Range		1700		2000	MHz
Noise Figure	1700-2000	—	—	1.6	dB
Gain	1700-2000	14	—	—	dB
Gain Flatness	1700-2000	—	—	±1.8	dB
Output Power at 1dB compression	1700-2000	—	+18.5	—	dBm
Output third order intercept point	1700-2000	—	+37	—	dBm
Input VSWR	1700-2000	—	1.15	—	:1
Output VSWR	1700-2000	—	1.25	—	:1
DC Supply Voltage	1700-2000	—	15	—	V
Supply Current	1700-2000	—	—	160	mA

Open load is not recommended, potentially can cause damage.
With no load derate max input power by 20 dB

Outline Drawing



Maximum Ratings

Parameter	Ratings
Operating Temperature	-40°C to 70°C
Storage Temperature	-55°C to 100°C
DC Voltage	+17V
Input RF Power (no damage)	+10 dBm

Permanent damage may occur if any of these limits are exceeded.

Outline Dimensions (inch mm)

A	B	C	D	E	F	G	H	J	K	L	M	N	P	wt
1.77	2.42	.55	.13	.12	2.165	1.535	.126	.22	.28	.51	.61	.39	0.22	grams
44.96	61.47	13.97	3.30	3.05	55.0	39.0	3.20	5.59	7.11	12.95	15.49	9.91	5.59	71.0

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp








www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

REV. B
M151107
ZQL-1900LNW
151005
Page 1 of 2

Typical Performance Data/Curves

ZQL-1900LNW+ ZQL-1900LNW

FREQUENCY (MHz)	GAIN (dB)	DIRECTIVITY (dB)	VSWR (:1)		NOISE FIGURE (dB)	POUT at 1 dB COMPR. (dBm)
	15V	15V	IN	OUT		
1700.00	17.42	9.30	1.16	1.15	0.76	21.49
1800.00	17.01	9.50	1.03	1.17	0.69	21.28
1850.00	16.74	9.80	1.06	1.23	0.79	21.41
1865.00	16.63	9.80	1.08	1.26	0.78	21.73
1874.00	16.56	9.90	1.09	1.27	0.78	21.43
1886.00	16.44	10.00	1.10	1.28	0.79	21.44
1901.00	16.34	10.40	1.12	1.30	0.83	21.74
1910.00	16.26	10.30	1.13	1.31	0.85	21.41
1940.00	16.08	10.50	1.16	1.34	0.79	21.48
2000.00	15.47	11.40	1.16	1.35	0.86	21.46



Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



Low Noise Amplifier

ZQL-1900LNW+

Typical Performance Data

FREQUENCY (MHz)	GAIN (dB) 15V	DIRECTIVITY (dB) 15V	VSWR IN (:1) 15V	VSWR OUT (:1) 15V	NOISE FIGURE (dB) 15V	Pout at 1dB Comp. (dBm) 15V
1700.0	17.42	9.30	1.16	1.15	0.76	21.49
1800.0	17.01	9.54	1.03	1.17	0.69	21.28
1850.0	16.74	9.81	1.06	1.23	0.79	21.41
1865.0	16.63	9.77	1.08	1.26	0.78	21.73
1874.0	16.56	9.93	1.09	1.27	0.78	21.43
1886.0	16.44	10.00	1.10	1.28	0.79	21.44
1901.0	16.34	10.41	1.12	1.30	0.83	21.74
1910.0	16.26	10.31	1.13	1.31	0.85	21.41
1940.0	16.08	10.54	1.16	1.34	0.79	21.48
2000.0	15.47	11.39	1.16	1.35	0.86	21.46

REV. X1

ZQL-1900LNW+

060917

Page 1 of 1



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661








The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see




Low Noise Amplifier

ZQL-1900LNW+

Typical Performance Curves



Outline Dimensions



CASE#	A	B	C	D	E	F	G	H	J	K	L	M	N
CW686	1.77 (44.96)	2.42 (61.47)	.55 (13.97)	.13 (3.30)	.12 (3.05)	2.165 (54.99)	1.535 (38.99)	.126 (3.20)	.22 (5.59)	.28 (7.11)	.51 (12.95)	.61 (15.49)	.39 (9.91)

CASE#	P	Q	WT. GRAMS
CW686	.22 (5.59)	--	71

Dimensions are in inches (mm). Tolerances: 2 Pl. $\pm .03$; 3 Pl. $\pm .015$

Notes:

- Case material: Aluminum alloy.
- Case finish:

For RoHS Case Styles:

Clear chemical conversion coating, non-chrome or trivalent chrome based.



INTERNET <http://www.minicircuits.com>

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010

Mini-Circuits ISO 9001 & ISO 14001 Certified



All Mini-Circuits products are manufactured under exacting quality assurance and control standards, and are capable of meeting published specifications after being subjected to any or all of the following physical and environmental test.

Specification	Test/Inspection Condition	Reference/Spec
Operating Temperature	-40° to 70° C Ambient Environment	Individual Model Data Sheet
Storage Temperature	-55° to 100° C Ambient Environment	Individual Model Data Sheet
Stabilization Bake	(non-operating) 125°C, 24 hours	- - -
Burn-in at Elevated Temp.	(DC on) 160 hours at 85° C	MIL-STD-202, Method 108
Thermal Shock	-55° to 85°C, 5 cycles	MIL-STD-202, Method 107, Condition A