

# Frequency Mixer

## ZX05-C42-S+

### Level 7 (LO Power +7 dBm) 1000 to 4200 MHz


#### Maximum Ratings

|                                                                 |                |
|-----------------------------------------------------------------|----------------|
| Operating Temperature                                           | -40°C to 85°C  |
| Storage Temperature                                             | -55°C to 100°C |
| RF Power                                                        | 50mW           |
| IF Current                                                      | 40mA           |
| Permanent damage may occur if any of these limits are exceeded. |                |

#### Coaxial Connections

|    |   |
|----|---|
| LO | 1 |
| RF | 2 |
| IF | 3 |

#### Outline Drawing



#### Outline Dimensions (inch/mm)

| A     | B     | C     | D     | E    | F    | G     |  |
|-------|-------|-------|-------|------|------|-------|--|
| .74   | .90   | .54   | .50   | .04  | .16  | .29   |  |
| 18.80 | 22.86 | 13.72 | 12.70 | 1.02 | 4.06 | 7.37  |  |
| H     | J     | K     | L     | M    | N    | wt    |  |
| .37   | --    | .122  | .496  | .106 | .122 | grams |  |
| 9.40  | --    | 3.10  | 12.60 | 2.69 | 3.10 | 20.0  |  |

#### Features

- rugged construction
- small size
- low conversion loss
- high L-R isolation
- protected by US Patents 6,790,049 & 7,027,795

#### Applications

- cellular
- PCS
- instrumentation
- satellite communication



Generic photo used for illustration purposes only

CASE STYLE: FL905

| Connectors | Model       |
|------------|-------------|
| SMA        | ZX05-C42-S+ |

#### +RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

#### Electrical Specifications (T<sub>AMB</sub>=25°C)


| FREQUENCY (MHz)        |         | CONVERSION LOSS (dB) |          |                  | LO-RF ISOLATION (dB) |      | LO-IF ISOLATION (dB) |      | IP3 at center band (dBm) |
|------------------------|---------|----------------------|----------|------------------|----------------------|------|----------------------|------|--------------------------|
| LO/RF<br>$f_L$ - $f_U$ | IF      | Mid-Band             |          | Total Range Max. | Typ.                 | Min. | Typ.                 | Min. |                          |
|                        |         | $\overline{X}$       | $\sigma$ |                  |                      |      |                      |      |                          |
| 1000-4200              | DC-1500 | 6.1                  | 0.1      | 8.9              | 35                   | 23   | 20                   | 12   | 10                       |

1 dB COMP.: +1 dBm typ.

#### Typical Performance Data

| Frequency (MHz) |         | Conversion Loss (dB) | Isolation L-R (dB) | Isolation L-I (dB) | VSWR RF Port (:1) | VSWR LO Port (:1) |
|-----------------|---------|----------------------|--------------------|--------------------|-------------------|-------------------|
| RF              | LO      | LO +7dBm             | LO +7dBm           | LO +7dBm           | LO +7dBm          | LO +7dBm          |
| 1000.10         | 1030.10 | 5.73                 | 35.29              | 21.91              | 2.12              | 5.32              |
| 1164.20         | 1134.20 | 6.05                 | 41.25              | 24.47              | 3.16              | 5.54              |
| 1328.31         | 1298.31 | 5.89                 | 40.08              | 24.96              | 2.94              | 2.63              |
| 1492.41         | 1462.41 | 5.70                 | 36.55              | 22.84              | 2.78              | 2.90              |
| 1656.51         | 1626.51 | 5.91                 | 35.28              | 23.54              | 3.02              | 3.12              |
| 1820.61         | 1790.61 | 5.55                 | 36.80              | 22.18              | 2.57              | 3.13              |
| 2066.77         | 2036.77 | 5.55                 | 36.27              | 23.23              | 2.01              | 3.23              |
| 2230.87         | 2200.87 | 5.55                 | 36.40              | 19.76              | 1.94              | 3.70              |
| 2394.97         | 2364.97 | 5.72                 | 38.33              | 17.59              | 1.97              | 4.46              |
| 2559.07         | 2529.07 | 6.07                 | 42.54              | 18.56              | 1.97              | 5.18              |
| 2723.18         | 2693.18 | 6.11                 | 39.02              | 19.78              | 2.46              | 4.39              |
| 2887.28         | 2857.28 | 6.29                 | 40.35              | 20.29              | 2.91              | 3.52              |
| 3051.38         | 3021.38 | 5.91                 | 40.44              | 22.56              | 3.17              | 3.25              |
| 3215.49         | 3185.49 | 5.79                 | 35.48              | 25.07              | 3.18              | 3.64              |
| 3379.59         | 3349.59 | 5.75                 | 32.18              | 25.81              | 2.38              | 3.10              |
| 3543.69         | 3513.69 | 6.03                 | 29.88              | 26.80              | 2.50              | 2.58              |
| 3707.79         | 3677.79 | 6.07                 | 28.78              | 27.73              | 2.72              | 2.28              |
| 3871.90         | 3841.90 | 6.43                 | 26.62              | 27.44              | 2.88              | 2.40              |
| 4036.00         | 4006.00 | 6.59                 | 25.92              | 26.97              | 3.40              | 2.97              |
| 4200.10         | 4170.10 | 6.51                 | 26.28              | 20.14              | 3.47              | 3.83              |








#### Electrical Schematic



#### Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at [www.minicircuits.com/MCLStore/terms.jsp](http://www.minicircuits.com/MCLStore/terms.jsp)





## Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at [www.minicircuits.com/MCLStore/terms.jsp](http://www.minicircuits.com/MCLStore/terms.jsp)



# Frequency Mixer

**ZX05-C42+**

## Typical Performance Data

| RF<br>(MHz) | LO<br>(MHz) | CONVERSION LOSS<br>(dB) |      |      | LO<br>(MHz) | LO-RF ISOLATION<br>(dB) |       |       | LO-IF ISOLATION<br>(dB) |       |       | LO<br>(MHz) | RF<br>(MHz) | IP3<br>Input<br>(dBm)<br>@LO<br>(dBm)<br>+7 |
|-------------|-------------|-------------------------|------|------|-------------|-------------------------|-------|-------|-------------------------|-------|-------|-------------|-------------|---------------------------------------------|
|             |             | @LO (dBm)               |      |      |             | @LO (dBm)               |       |       | @LO (dBm)               |       |       |             |             |                                             |
|             |             | +4                      | +7   | +10  |             | +4                      | +7    | +10   | +4                      | +7    | +10   |             |             |                                             |
| 1000.0      | 1030.0      | 7.65                    | 7.06 | 6.61 | 1030.0      | 30.45                   | 30.82 | 31.34 | 19.72                   | 21.95 | 23.91 | 2380.0      | 2350.0      | 8.93                                        |
| 1050.0      | 1080.0      | 7.48                    | 6.95 | 6.60 | 1080.0      | 31.29                   | 31.84 | 32.51 | 20.23                   | 22.56 | 24.57 | 2430.0      | 2400.0      | 9.32                                        |
| 1100.0      | 1130.0      | 7.07                    | 6.73 | 6.47 | 1130.0      | 33.20                   | 33.92 | 34.41 | 20.90                   | 23.18 | 25.08 | 2480.0      | 2450.0      | 9.56                                        |
| 1150.0      | 1180.0      | 7.36                    | 7.00 | 6.86 | 1180.0      | 35.84                   | 36.31 | 36.56 | 21.18                   | 23.24 | 25.03 | 2530.0      | 2500.0      | 8.94                                        |
| 1250.0      | 1280.0      | 6.90                    | 6.82 | 6.50 | 1280.0      | 40.12                   | 40.04 | 40.01 | 22.02                   | 23.40 | 24.14 | 2580.0      | 2550.0      | 9.19                                        |
| 1300.0      | 1330.0      | 6.97                    | 6.56 | 6.51 | 1330.0      | 41.57                   | 41.27 | 40.80 | 22.27                   | 23.15 | 23.40 | 2630.0      | 2600.0      | 9.23                                        |
| 1350.0      | 1380.0      | 6.59                    | 6.49 | 6.55 | 1380.0      | 44.08                   | 42.74 | 41.45 | 22.46                   | 22.71 | 22.43 | 2680.0      | 2650.0      | 9.90                                        |
| 1400.0      | 1430.0      | 6.68                    | 6.74 | 6.48 | 1430.0      | 45.00                   | 43.15 | 41.52 | 22.42                   | 22.28 | 21.79 | 2730.0      | 2700.0      | 9.35                                        |
| 1450.0      | 1480.0      | 6.68                    | 6.69 | 6.60 | 1480.0      | 44.52                   | 41.97 | 39.96 | 22.29                   | 21.98 | 21.45 | 2780.0      | 2750.0      | 7.52                                        |
| 1500.0      | 1530.0      | 6.70                    | 6.55 | 6.54 | 1530.0      | 42.67                   | 40.58 | 38.51 | 22.23                   | 21.81 | 21.30 | 2880.0      | 2850.0      | 6.07                                        |
| 1600.0      | 1630.0      | 7.06                    | 6.65 | 6.63 | 1630.0      | 39.72                   | 37.40 | 35.71 | 23.75                   | 22.79 | 21.70 |             |             |                                             |
| 1700.0      | 1730.0      | 7.12                    | 6.82 | 6.83 | 1730.0      | 35.97                   | 34.24 | 32.96 | 23.12                   | 22.29 | 21.62 |             |             |                                             |
| 1800.0      | 1830.0      | 7.33                    | 7.09 | 6.83 | 1830.0      | 40.17                   | 37.36 | 35.46 | 23.64                   | 23.02 | 22.53 |             |             |                                             |
| 1900.0      | 1930.0      | 7.40                    | 7.16 | 7.07 | 1930.0      | 40.03                   | 39.01 | 38.26 | 24.41                   | 24.51 | 24.52 |             |             |                                             |
| 2000.0      | 2030.0      | 7.69                    | 7.37 | 7.26 | 2030.0      | 37.52                   | 37.53 | 37.51 | 24.33                   | 25.73 | 27.05 |             |             |                                             |
| 2100.0      | 2130.0      | 7.54                    | 7.15 | 6.99 | 2130.0      | 38.98                   | 38.01 | 37.29 | 22.46                   | 23.66 | 24.59 |             |             |                                             |
| 2200.0      | 2230.0      | 7.32                    | 6.89 | 6.70 | 2230.0      | 38.39                   | 36.75 | 35.64 | 20.01                   | 19.90 | 19.65 |             |             |                                             |
| 2300.0      | 2330.0      | 7.73                    | 7.23 | 6.79 | 2330.0      | 38.71                   | 36.32 | 34.51 | 18.54                   | 17.58 | 16.80 |             |             |                                             |
| 2400.0      | 2430.0      | 7.13                    | 6.71 | 6.39 | 2430.0      | 36.44                   | 34.38 | 32.61 | 19.20                   | 17.61 | 16.55 |             |             |                                             |
| 2500.0      | 2530.0      | 6.93                    | 6.55 | 6.37 | 2530.0      | 35.79                   | 33.12 | 30.87 | 21.14                   | 19.16 | 17.80 |             |             |                                             |
| 2600.0      | 2630.0      | 7.64                    | 6.76 | 6.38 | 2630.0      | 41.26                   | 35.83 | 31.73 | 23.11                   | 20.59 | 19.16 |             |             |                                             |
| 2700.0      | 2730.0      | 8.03                    | 7.22 | 6.74 | 2730.0      | 44.71                   | 38.56 | 35.10 | 24.39                   | 21.86 | 20.45 |             |             |                                             |
| 2800.0      | 2830.0      | 7.40                    | 6.85 | 6.33 | 2830.0      | 45.04                   | 43.97 | 41.14 | 25.20                   | 22.58 | 21.11 |             |             |                                             |
| 2900.0      | 2930.0      | 7.06                    | 6.30 | 5.94 | 2930.0      | 43.57                   | 45.43 | 47.79 | 26.38                   | 23.71 | 22.21 |             |             |                                             |
| 3000.0      | 3030.0      | 6.55                    | 5.73 | 5.47 | 3030.0      | 41.19                   | 43.61 | 49.53 | 27.37                   | 25.27 | 23.96 |             |             |                                             |
| 3100.0      | 3130.0      | 6.40                    | 5.66 | 5.48 | 3130.0      | 42.04                   | 42.98 | 42.44 | 27.27                   | 25.76 | 25.03 |             |             |                                             |
| 3200.0      | 3230.0      | 6.11                    | 5.55 | 5.58 | 3230.0      | 41.12                   | 41.05 | 39.13 | 26.55                   | 25.87 | 25.84 |             |             |                                             |
| 3300.0      | 3330.0      | 5.98                    | 5.51 | 5.64 | 3330.0      | 36.32                   | 35.56 | 34.96 | 25.85                   | 25.90 | 26.33 |             |             |                                             |
| 3400.0      | 3430.0      | 6.15                    | 5.65 | 5.63 | 3430.0      | 35.36                   | 33.39 | 32.07 | 26.31                   | 26.90 | 27.37 |             |             |                                             |
| 3500.0      | 3530.0      | 6.39                    | 5.94 | 5.95 | 3530.0      | 34.21                   | 32.16 | 30.75 | 26.12                   | 27.12 | 27.75 |             |             |                                             |
| 3600.0      | 3630.0      | 6.83                    | 6.44 | 6.14 | 3630.0      | 32.48                   | 32.16 | 31.62 | 25.68                   | 26.88 | 28.06 |             |             |                                             |
| 3700.0      | 3730.0      | 6.85                    | 6.35 | 6.12 | 3730.0      | 32.15                   | 31.11 | 30.05 | 23.42                   | 25.04 | 26.75 |             |             |                                             |
| 3800.0      | 3830.0      | 7.25                    | 6.65 | 6.39 | 3830.0      | 31.79                   | 30.72 | 29.69 | 23.22                   | 24.99 | 26.94 |             |             |                                             |
| 3850.0      | 3880.0      | 7.42                    | 6.73 | 6.49 | 3880.0      | 32.29                   | 30.94 | 29.69 | 23.42                   | 25.33 | 27.23 |             |             |                                             |
| 3900.0      | 3930.0      | 7.38                    | 6.69 | 6.60 | 3930.0      | 34.50                   | 32.26 | 30.47 | 23.29                   | 25.20 | 27.12 |             |             |                                             |
| 3950.0      | 3980.0      | 7.54                    | 6.76 | 6.55 | 3980.0      | 34.21                   | 34.88 | 32.87 | 22.48                   | 24.52 | 26.24 |             |             |                                             |
| 4000.0      | 4030.0      | 7.97                    | 7.14 | 6.84 | 4030.0      | 30.30                   | 32.36 | 32.88 | 20.46                   | 22.14 | 23.97 |             |             |                                             |
| 4100.0      | 4130.0      | 8.56                    | 7.68 | 7.25 | 4130.0      | 30.05                   | 31.18 | 32.02 | 18.26                   | 19.40 | 21.09 |             |             |                                             |
| 4150.0      | 4180.0      | 8.48                    | 7.66 | 7.19 | 4180.0      | 29.66                   | 30.82 | 31.41 | 16.98                   | 18.11 | 19.67 |             |             |                                             |
| 4200.0      | 4230.0      | 8.94                    | 7.64 | 7.28 | 4230.0      | 30.07                   | 31.30 | 32.12 | 16.82                   | 17.53 | 18.76 |             |             |                                             |

REV. X1  
ZX05-C42+  
080717  
Page 1 of 2



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED • RoHS compliant  
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661



The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



# Frequency Mixer

**ZX05-C42+**

## Typical Performance Data

| RF/LO<br>(MHz) | RF VSWR<br>(:1) |      |      | LO VSWR<br>(:1) |      |      | IF<br>(MHz) | IF VSWR<br>(:1) |      |      |
|----------------|-----------------|------|------|-----------------|------|------|-------------|-----------------|------|------|
|                | @LO (dBm)       |      |      | @LO (dBm)       |      |      |             | @LO (dBm)       |      |      |
|                | +4              | +7   | +10  | +4              | +7   | +10  |             | +4              | +7   | +10  |
| 1030.0         | 2.88            | 2.66 | 2.44 | 3.18            | 4.00 | 5.20 | 10.0        | 1.42            | 1.04 | 1.16 |
| 1080.0         | 3.25            | 3.09 | 2.91 | 2.54            | 3.32 | 4.36 | 20.0        | 1.44            | 1.05 | 1.16 |
| 1130.0         | 3.48            | 3.35 | 3.31 | 2.14            | 2.81 | 3.74 | 30.0        | 1.46            | 1.06 | 1.17 |
| 1180.0         | 3.79            | 3.77 | 3.68 | 1.81            | 2.47 | 3.29 | 40.0        | 1.48            | 1.07 | 1.17 |
| 1280.0         | 3.96            | 3.88 | 3.93 | 1.39            | 1.90 | 2.52 | 50.0        | 1.49            | 1.08 | 1.18 |
| 1330.0         | 3.89            | 3.78 | 3.73 | 1.26            | 1.77 | 2.38 | 60.0        | 1.50            | 1.10 | 1.18 |
| 1380.0         | 4.04            | 3.78 | 3.65 | 1.24            | 1.75 | 2.39 | 70.0        | 1.51            | 1.11 | 1.18 |
| 1430.0         | 4.02            | 3.70 | 3.43 | 1.32            | 1.84 | 2.55 | 80.0        | 1.51            | 1.12 | 1.19 |
| 1480.0         | 3.91            | 3.70 | 3.39 | 1.43            | 1.94 | 2.68 | 90.0        | 1.52            | 1.13 | 1.19 |
| 1530.0         | 3.91            | 3.59 | 3.28 | 1.56            | 2.07 | 2.75 | 150.0       | 1.61            | 1.23 | 1.24 |
| 1630.0         | 3.28            | 3.04 | 2.82 | 1.83            | 2.29 | 2.92 | 200.0       | 1.72            | 1.32 | 1.29 |
| 1730.0         | 3.25            | 3.03 | 2.77 | 1.98            | 2.52 | 3.21 | 250.0       | 1.81            | 1.40 | 1.33 |
| 1830.0         | 3.25            | 3.01 | 2.86 | 2.06            | 2.71 | 3.50 | 300.0       | 1.92            | 1.49 | 1.39 |
| 1930.0         | 3.29            | 3.13 | 3.01 | 2.21            | 3.01 | 3.95 | 350.0       | 2.03            | 1.57 | 1.45 |
| 2030.0         | 3.40            | 3.25 | 3.08 | 2.58            | 3.34 | 4.30 | 400.0       | 2.15            | 1.66 | 1.51 |
| 2130.0         | 3.30            | 3.10 | 2.92 | 2.94            | 3.61 | 4.50 | 450.0       | 2.26            | 1.74 | 1.56 |
| 2230.0         | 3.09            | 2.86 | 2.66 | 3.23            | 3.58 | 4.14 | 500.0       | 2.36            | 1.82 | 1.62 |
| 2330.0         | 2.85            | 2.64 | 2.47 | 3.63            | 3.76 | 4.18 | 550.0       | 2.44            | 1.88 | 1.66 |
| 2430.0         | 3.02            | 2.69 | 2.45 | 4.03            | 4.08 | 4.50 | 600.0       | 2.61            | 1.99 | 1.74 |
| 2530.0         | 3.11            | 2.65 | 2.34 | 4.28            | 4.18 | 4.46 | 650.0       | 2.67            | 2.04 | 1.78 |
| 2630.0         | 3.69            | 3.07 | 2.67 | 5.16            | 4.85 | 5.23 | 700.0       | 2.81            | 2.15 | 1.84 |
| 2730.0         | 4.06            | 3.50 | 3.06 | 7.11            | 6.22 | 6.62 | 750.0       | 2.96            | 2.23 | 1.91 |
| 2830.0         | 3.87            | 3.44 | 3.10 | 6.93            | 5.28 | 5.29 | 800.0       | 3.11            | 2.32 | 1.97 |
| 2930.0         | 3.39            | 2.75 | 2.37 | 7.33            | 4.61 | 4.27 | 850.0       | 3.25            | 2.40 | 2.01 |
| 3030.0         | 2.70            | 2.18 | 1.96 | 8.47            | 5.13 | 4.29 | 900.0       | 3.49            | 2.51 | 2.08 |
| 3130.0         | 2.36            | 1.92 | 1.74 | 7.34            | 4.68 | 3.67 | 950.0       | 3.49            | 2.51 | 2.05 |
| 3230.0         | 2.17            | 1.69 | 1.53 | 6.03            | 3.81 | 2.96 | 1000.0      | 3.45            | 2.47 | 2.02 |
| 3330.0         | 2.02            | 1.56 | 1.40 | 4.97            | 2.98 | 2.28 | 1050.0      | 3.44            | 2.43 | 1.99 |
| 3430.0         | 1.99            | 1.56 | 1.37 | 3.60            | 2.29 | 1.81 | 1100.0      | 3.25            | 2.28 | 1.89 |
| 3530.0         | 2.23            | 1.86 | 1.64 | 2.62            | 1.85 | 1.61 | 1150.0      | 3.27            | 2.25 | 1.86 |
| 3630.0         | 2.35            | 2.11 | 1.90 | 2.28            | 1.72 | 1.64 | 1200.0      | 3.25            | 2.23 | 1.89 |
| 3730.0         | 2.42            | 2.20 | 2.00 | 2.18            | 1.72 | 1.71 | 1250.0      | 3.22            | 2.27 | 1.98 |
| 3830.0         | 2.43            | 2.24 | 2.07 | 2.04            | 1.72 | 1.81 | 1300.0      | 3.18            | 2.34 | 2.13 |
| 3880.0         | 2.39            | 2.20 | 2.05 | 2.09            | 1.82 | 1.95 | 1325.0      | 3.10            | 2.33 | 2.17 |
| 3930.0         | 2.33            | 2.15 | 2.02 | 2.16            | 1.93 | 2.07 | 1350.0      | 3.16            | 2.47 | 2.33 |
| 3980.0         | 2.41            | 2.21 | 2.07 | 2.32            | 2.09 | 2.21 | 1375.0      | 3.03            | 2.45 | 2.37 |
| 4030.0         | 2.66            | 2.45 | 2.31 | 2.72            | 2.37 | 2.46 | 1400.0      | 2.98            | 2.48 | 2.47 |
| 4130.0         | 3.30            | 3.03 | 2.87 | 3.88            | 3.10 | 3.01 | 1425.0      | 2.94            | 2.59 | 2.63 |
| 4180.0         | 3.59            | 3.20 | 3.04 | 5.11            | 3.78 | 3.46 | 1450.0      | 2.86            | 2.63 | 2.74 |
| 4230.0         | 4.24            | 3.63 | 3.38 | 5.97            | 4.28 | 3.62 | 1500.0      | 2.77            | 2.79 | 3.00 |

REV. X1  
ZX05-C42+  
080717  
Page 2 of 2



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant  
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661




The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see




## Typical Performance Curves


Conversion Loss




IP3 Input




LO-RF Isolation




LO-IF Isolation




RF VSWR




LO VSWR



IF VSWR



### Outline Dimensions



| CASE #. | A              | B              | C              | D              | E             | F             | G             | H             | J      | K              | L               | M              | N              | WT,<br>GRAM |
|---------|----------------|----------------|----------------|----------------|---------------|---------------|---------------|---------------|--------|----------------|-----------------|----------------|----------------|-------------|
| FL905   | .74<br>(18.80) | .90<br>(22.86) | .54<br>(13.72) | .50<br>(12.70) | .04<br>(1.02) | .16<br>(4.06) | .29<br>(7.37) | .37<br>(9.40) | -<br>- | .122<br>(3.10) | .496<br>(12.60) | .106<br>(2.69) | .122<br>(3.10) | 20.0        |

Dimensions are in inches (mm). Tolerances: 2Pl.  $\pm .03$ ; 3Pl.  $\pm .015$ .

Tolerance on hole size and interaxes dimensions to be  $\pm .005$ .

#### Notes:

- Case material: Brass.
- Case finish: Nickel plate.



INTERNET <http://www.minicircuits.com>

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010

Mini-Circuits ISO 9001 & ISO 14001 Certified



All Mini-Circuits products are manufactured under exacting quality assurance and control standards, and are capable of meeting published specifications after being subjected to any or all of the following physical and environmental test.

| Specification              | Test/Inspection Condition                                                              | Reference/Spec                       |
|----------------------------|----------------------------------------------------------------------------------------|--------------------------------------|
| Operating Temperature      | -40° to 85°C                                                                           | Individual Model Data Sheet          |
| Storage Temperature        | -55° to 100° C<br>Ambient Environment                                                  | Individual Model Data Sheet          |
| Barometric Pressure        | 100,000 Feet                                                                           | MIL-STD-202, Method 105, Condition D |
| Humidity                   | 90% RH, 65°C<br>Units may require bake-out after humidity to restore full performance. | MIL-STD-202, Method 103              |
| Thermal Shock              | -65° to 125°C, 5 cycles                                                                | MIL-STD-202, Method 107, Condition B |
| Vibration (High Frequency) | 20g peak, 10-2000 Hz, 12 times in each of three perpendicular directions (total 36)    | MIL-STD-202, Method 204, Condition D |
| Mechanical Shock           | 100g, 6ms sawtooth, 3 shocks each direction 3 axes (total 18)                          | MIL-STD-202, Method 213, Condition I |