

Adaptor 2.4mm-Female to 2.92mm-Male**24F-KM+***Typical Performance Data*

FREQ.	INSERTION LOSS	2.4mm-FEMALE VSWR	2.92mm-MALE VSWR
(GHz)	(dB)	(:1)	(:1)
0.01	0.08	1.05	1.01
0.05	0.01	1.01	1.00
0.10	0.01	1.00	1.01
1.00	0.03	1.01	1.02
2.00	0.03	1.02	1.03
3.00	0.04	1.03	1.04
4.00	0.04	1.03	1.04
5.00	0.05	1.04	1.04
6.00	0.05	1.04	1.04
7.00	0.05	1.04	1.04
8.00	0.05	1.03	1.03
9.00	0.06	1.03	1.03
10.00	0.06	1.02	1.02
11.00	0.06	1.02	1.01
12.00	0.06	1.02	1.01
13.00	0.07	1.03	1.02
14.00	0.07	1.03	1.03
15.00	0.07	1.03	1.03
16.00	0.07	1.03	1.04
17.00	0.08	1.03	1.04
18.00	0.08	1.03	1.05
19.00	0.08	1.03	1.04
20.00	0.08	1.03	1.05
21.00	0.09	1.04	1.06
22.00	0.09	1.05	1.07
23.00	0.09	1.05	1.07
24.00	0.10	1.05	1.07
25.00	0.10	1.04	1.06
26.00	0.10	1.03	1.04
27.00	0.10	1.02	1.03
28.00	0.10	1.01	1.01
29.00	0.10	1.02	1.02
30.00	0.10	1.04	1.04
31.00	0.11	1.05	1.05
32.00	0.11	1.05	1.05
33.00	0.11	1.03	1.03
34.00	0.11	1.02	1.02
35.00	0.12	1.03	1.04
36.00	0.11	1.04	1.05
37.00	0.11	1.05	1.06
38.00	0.12	1.06	1.05
39.00	0.11	1.06	1.06
40.00	0.12	1.06	1.06



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 • Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site
The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com



IF/RF MICROWAVE COMPONENTS

REV. OR
24F-KM+
7/18/2025
Page 1 of 1