

Adapter 2.4mm-Female to 2.92mm-Female

24FR-KF+

Typical Performance Data

FREQ.	INSERTION LOSS	2.4mm-FEMALE VSWR	2.92mm-FEMALE VSWR
(GHz)	(dB)	(:1)	(:1)
0.01	0.01	1.01	1.01
0.05	0.02	1.00	1.00
0.10	0.03	1.00	1.01
1.00	0.07	1.02	1.03
2.00	0.08	1.03	1.05
3.00	0.10	1.04	1.06
4.00	0.10	1.04	1.04
5.00	0.11	1.02	1.02
6.00	0.11	1.01	1.01
7.00	0.12	1.03	1.03
8.00	0.12	1.06	1.06
9.00	0.13	1.09	1.09
10.00	0.14	1.10	1.11
11.00	0.14	1.11	1.12
12.00	0.15	1.11	1.10
13.00	0.15	1.09	1.09
14.00	0.15	1.06	1.07
15.00	0.14	1.03	1.04
16.00	0.15	1.02	1.04
17.00	0.16	1.05	1.06
18.00	0.17	1.08	1.08
19.00	0.17	1.10	1.09
20.00	0.18	1.12	1.10
21.00	0.19	1.14	1.11
22.00	0.19	1.14	1.13
23.00	0.20	1.15	1.15
24.00	0.21	1.13	1.14
25.00	0.21	1.13	1.13
26.00	0.22	1.12	1.12
27.00	0.22	1.10	1.10
28.00	0.21	1.07	1.07
29.00	0.22	1.02	1.02
30.00	0.22	1.03	1.04
31.00	0.23	1.07	1.06
32.00	0.23	1.06	1.07
33.00	0.23	1.05	1.05
34.00	0.23	1.03	1.01
35.00	0.26	1.07	1.06
36.00	0.25	1.11	1.09
37.00	0.26	1.13	1.11
38.00	0.28	1.15	1.13
39.00	0.28	1.17	1.15
40.00	0.28	1.16	1.15



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 • Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site
 The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com

IF/RF MICROWAVE COMPONENTS

REV. OR
 24FR-KF+
 11/19/2025
 Page 1 of 1