

Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.01	10.19	1.00
0.05	10.22	1.00
0.1	10.22	1.00
0.2	10.23	1.00
0.3	10.24	1.00
0.4	10.26	1.00
0.5	10.27	1.00
0.6	10.27	1.00
0.7	10.27	1.00
0.8	10.27	1.00
0.9	10.28	1.00
1.0	10.28	1.01
1.4	10.30	1.02
1.8	10.31	1.03
2.0	10.33	1.04
2.4	10.33	1.06
2.8	10.34	1.09
3.0	10.34	1.09
3.4	10.35	1.10
3.8	10.35	1.10
4.0	10.34	1.09
4.4	10.34	1.08
4.8	10.33	1.07
5.0	10.32	1.06
5.4	10.32	1.05
5.8	10.32	1.04
6.0	10.31	1.05
6.4	10.31	1.07
6.8	10.30	1.08
7.0	10.29	1.09
7.4	10.28	1.09
7.8	10.27	1.11
8.0	10.27	1.11
8.4	10.26	1.13
8.8	10.26	1.16
9.0	10.26	1.13
9.4	10.27	1.13
9.8	10.26	1.15
10.0	10.27	1.10
10.4	10.24	1.13
10.8	10.26	1.16
11.0	10.23	1.15
11.4	10.30	1.20
11.8	10.30	1.21
12.0	10.35	1.22
12.4	10.37	1.25
12.8	10.41	1.24
13.0	10.38	1.24
13.4	10.36	1.24
13.8	10.36	1.22
14.0	10.35	1.25
14.4	10.35	1.20
14.8	10.33	1.16
15.0	10.29	1.14
15.4	10.27	1.08
15.8	10.24	1.12
16.0	10.20	1.08
16.4	10.25	1.11
16.8	10.26	1.11
17.0	10.22	1.08
17.4	10.32	1.10
17.8	10.35	1.13
18.0	10.39	1.12