

Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.01	10.08	1.00
0.05	10.12	1.00
0.1	10.12	1.00
0.2	10.15	1.00
0.3	10.16	1.00
0.4	10.17	1.01
0.5	10.18	1.01
0.6	10.19	1.02
0.7	10.20	1.02
0.8	10.21	1.02
0.9	10.21	1.03
1.0	10.22	1.03
1.4	10.25	1.04
1.8	10.27	1.04
2.0	10.27	1.04
2.4	10.27	1.04
2.8	10.27	1.05
3.0	10.27	1.05
3.4	10.26	1.04
3.8	10.25	1.06
4.0	10.25	1.07
4.4	10.23	1.06
4.8	10.21	1.03
5.0	10.21	1.01
5.4	10.19	1.03
5.8	10.18	1.06
6.0	10.17	1.06
6.4	10.15	1.02
6.8	10.13	1.04
7.0	10.11	1.05
7.4	10.08	1.04
7.8	10.05	1.02
8.0	10.04	1.04
8.4	10.02	1.07
8.8	9.99	1.06
9.0	9.97	1.06
9.4	9.96	1.09
9.8	9.93	1.15
10.0	9.89	1.19
10.4	9.83	1.22
10.8	9.79	1.15
11.0	9.78	1.10
11.4	9.78	1.02
11.8	9.77	1.03
12.0	9.76	1.05
12.4	9.73	1.07
12.8	9.71	1.11
13.0	9.71	1.13
13.4	9.69	1.14
13.8	9.63	1.12
14.0	9.56	1.12
14.4	9.42	1.22
14.8	9.34	1.32
15.0	9.37	1.32
15.4	9.42	1.29
15.8	9.47	1.24
16.0	9.48	1.21
16.4	9.46	1.10
16.8	9.43	1.13
17.0	9.44	1.20
17.4	9.42	1.34
17.8	9.45	1.41
18.0	9.45	1.40